

## STERILE SYRINGE FILTER

These filters are designed for applications where sterility of the affluent is mandatory (Sterile Compounding and Pharmaceutical use). The product contains a pharmaceutical grade PTFE membrane (Sterilizing Grade) and the filters are built in a 10,000-class clean room, flushed, dried and 100% integrity tested prior to packaging. The product is factory sterilized by Ethylene Oxide gas (ETO) ensuring sterility.

## Technical Data Sheet

**Catalog Number: D50CF100020FLM-PH-ETO**



### Materials of Construction

**Filter Membrane:** 1.0 um Pre-filter/0.2 um final, Pharmaceutical Grade Teflon (PTFE) Sterilizing Grade - Hydrophobic

**Supports:** Polypropylene

**Capsule Body:** Polypropylene

### Filter Dimensions and Specifications

**Outer Diameter:** 54 mm (2.12")

**Capsule Body Thickness:** 8 mm (0.314")

**Length, Fitting to Fitting:** 32 mm (1.25")


**Filter Area:** 15.9 cm<sup>2</sup> (2.5 in<sup>2</sup>)

**Sterilization:** The filter is factory sterilized by Ethylene Oxide Gas (ETO)

**Inlet Fitting:** Luer Loc Female

**Outlet Fitting:** Luer Loc Male

**Volume Filtered:** 280 ml to 1,175 ml



### **Integrity Data**

Pore Size	Min, Bubble Point, 25°C	Challenge Microorganisms	CFU per cm <sup>2</sup>
0.20 µm	≥3.5 bar (50 psi)	Brevundimonas Diminuta (ATCC 19146)	7

### **Operating Parameters**

Maximum Working Pressure: 5.5 bar (80 Psi) @ 25 °C (77 °F)

Maximum differential Pressure (forward): 4.1 bar (60 Psi) @ 25 °C (77 °F)

Maximum differential Pressure (reverse): 2.1 bar (30 Psi) @ 25 °C (77 °F)

Maximum Operating Temperature: 80 °C (176 °F)

Recommended Replacement Pressure: 2.4 bar (35.3 Psi)

### **Safety**

UPS Bacteria Endotoxins: ≤25 EU/ml

Factory Sterilized: Ethylene Oxide Gas (ETO)

Product was 100% Integrity Tested and flushed with filtered water @ 0.05 µm

### **Regulatory**

Complies with USP 797 Guidelines

ASTM F838-05 - Bacterial Retention

FDA 21 CFR 177.1655

USP Class VI - Biological Reactivity

ISO 10993-Part 1. 5 - Cytotoxicity

ISO 14001; ISO 13485; OHSMS 18001 Certified.

ASTM Hemolysis testing



www.internationalfilterproducts.com  
 11070 Fleetwood St. Unit B  
 Sun Valley, CA 91352  
 Tel: (818) 504-8115 - Office  
 Tel: (818) 917-9538 - Cell  
 E-mail: sales@internationalfilterproducts.com

