

4

3

2

1

THIS DOCUMENT IS FOR REFERENCE ONLY AND IS PROPRIETARY INFORMATION BELONGING TO INTERNATIONAL FILTER PRODUCTS UNAUTHORIZED COPIES OR USE FOR OTHER PURPOSES STRICTLY PROHIBITED.

REVISIONS				
ZONE	REV	DESCRIPTION	DATE	APPROVED
	-	SALES DRAWING	10/28/2022	YA ZANKI

D

D

C

C

B

B

A

A

1.4 in [36 mm]

90°

3 X .72 in [18.3 mm]

2.9 in [72 mm]

.8 in [21 mm]

ID: 5/16"

ID: 5/16"

ID: 5/16"

.4 in [10.7 mm]

NOTE:

- 1.0 Material: Polypropylene
- 2.0 Can be Sterilized by Gamma Radiation
- 3.0 Max. Working Pressure @ 200 °F (93.3 °C): 100 PSI
- 4.0 Max. Working Pressure @ 72 °F (22.2 °C): 250 PSI
- 5.0 Max. Working Temperature: 200 °F (93.3 °C)
- 6.0 Manufactured and Packaged in a Certified Clean Room
- 7.0 Regulatory Information is Found in Catalog

DRAWN NV GABRIEL	10/7/2022	<b>International Filter Products</b>		
CHECKED YA ZANKI	10/28/2022	7914 AJAY DRIVE	PHONE: 818-504-8115	
APPROVED YA ZANKI	10/28/2022	SUN VALLEY, CA 91352	FAX: 818-841-2947	email: charlie@internationalfilterproducts.com
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES		TITLE		
DECIMALS X +/- .030	FRACTIONS +/- 1/16	FITTING, TEE, 3 WAY, ID 0.3125 in, PP		
XX +/- .015	ANGLES +/- 1/2	SIZE	ISOF NO	DWG NO
XXX +/- .005	SURFACE ROUGHNESS 125	A		PFT312PPAF
CONCENTRICITIES .010 (FIM)		SCALE	WEIGHT	REV
INTERNAL RADII .015~.030		NA		-
BREAK CORNERS .005~.015		SHEET		1 OF 1