



## Bay Area AQMD Regulation 8 Rule 45

VOC Less Water Less Exempt Limits for version amended 12/3/08



Coating Category	Effective 10/1/09	Effective 1/1/10	
	lbs/gal (g/L)	lbs/gal (g/L)	
Solvent (Surface Cleaner)	.21 (25)*	.21 (25)*	
Pretreatments Coating	5.5 (660)	5.5 (660)	
Primer	2.1 (250)	2.1 (250)	
Primer Sealer	2.8 (340)	2.1 (340)	
Single-Stage Coating	3.5 (420)	2.8 (340)	
Color Coating	3.5 (420)	3.5 (420)	
Clear Coating	2.1 (250)	2.1 (250)	
Uniform Finish Coating	4.5 (540)	4.5 (540)	
Adhesion Promoter	7.0 (840)	4.5 (540)	* VOC content applies to this category only

Product Code & Name	Reducer	Mix Ratio	VOC content
<b>Solvent (Substrate Cleaner)</b>	<b>Limit:</b>	<b>0.21 lbs/gal (25 g/L)</b>	
SWX350 H2O-So-Clean Wax & Grease Remover	-	-	0.17 (20)
SWX360 Waterborne Pre-Cleaner	water	1 : 2	0.20 (24)

Product Code & Name	Hardener/Activator	Reducer	Mix Ratio	Applied VOC Less Water Less Exempt
<b>Pretreatment Coating</b>		<b>Limit:</b>	<b>5.5 lbs/gal (660 g/L)</b>	
SX1071 Etch Prime	SX1072	-	1 : 1	5.48 (657)
SXA1031 Etch Primer – Gray	-	-	Aerosol	N/A

Product Code & Name	Hardener/Activator	Additives	Reducer	Mix Ratio	Applied VOC Less Water Less Exempt
<b>Primer</b>			<b>Limit:</b>	<b>2.1 lbs/gal (250 g/L)</b>	
DPU217 2.1 VOC Polyurethane Primer	DPU218	DX39	-	5 : 1 + 6 oz / RTS gal	2.07 (248)
MP211 2K High Solids Primer	MP212	MX200	-	5 : 1 + 6 oz / RTS gal	2.07 (248)
<b>Single-Stage Coating</b>			<b>Limit:</b>	<b>2.84 lbs/gal (340 g/L)</b>	
DHS 2.8 Polyurethane	DDH526	-	-	2 : 1	2.81 (337)
DHS 2.8 Polyurethane – <u>Low Gloss</u> color + DX595 mixed 1 : 1	DDH526	-	-	2 : 1	2.75 (330)
DHS 2.8 Polyurethane – <u>Semi Gloss</u> color + DX595 mixed 3 : 1	DDH526	-	-	4 : 2	2.78 (333)
DVHS Fast Dry 2.8 VOC Polyurethane	DFHS528	DX39	-	4 : 1 + 4 oz / RTS gal	2.81 (337)
<b>Color Coating</b>			<b>Limit:</b>	<b>3.5 lbs/gal (420 g/L)</b>	<b>Color Coating</b>
DUHS Basecoat (see FL507)	DDH526	DHSX589	-	2 : 1 : ¼ - 1	3.50 (419)
MCV Basecoat (see OB21)	MFA360	M300	-	4 : ½ - 1 : 1	3.50 (419)
<b>Clear Coating</b>			<b>Limit:</b>	<b>2.1 lbs/gal (250 g/L)</b>	<b>Clear Coating</b>
MC262 OMNI SV 2.1 Clear	MH266, MH267	-	-	4 : 1	2.08 (249)



# Bay Area AQMD Regulation 8 Rule 45

VOC Less Water Less Exempt Limits for version amended 12/3/08



**Additional Products: (listing not intended to be all inclusive)**

SLV73 Fisheye Eliminator	SXA840 OneChoice Blending Solvent	
SU4901 Clean and Scuff Sponge		
SUA4903 Advanced Plastic Bond		

This "Bay Area AQMD Rule 8-45 (PPG Delta / OMNI CV)" wall chart is intended to provide INFORMATION to PPG's customers. In providing this wall chart, PPG makes no separate or additional warranties, express or implied, and assumes no liability or responsibility arising out of its use. It is the responsibility of each customer, RE-SELLER AND END USER of PPG's products to independently ascertain that their practices are legal, appropriate and constitute sound product stewardship. This "Bay Area AQMD Rule 8-45 (PPG Delta / OMNI CV)" wall chart does not include all currently compliant Delta / OMNI CV products. The representative products listed are compliant with Rule 8-45 VOC limits as of the date of this wall chart; however, subsequent changes in Rule 8-45 may change the compliance status of the listed products. It is the responsibility of the end user to review and comply with current regulations, including applicable coating category VOC limits, as of the date of product purchase and/or use. This document is not INTENDED to define or create legal rights or obligations. It is the responsibility of each customer, RE-SELLER AND END USER to comply with all applicable federal, state and local laws.