



Eastern Kern APCD
Motor Vehicle and Mobile Equipment
Refinishing Operations
Rule 410.4A
 Amended: 03/13/2014 | In Effect: 03/13/2014



Coating Category	lbs/gal (g/L)	Limit: VOC Regulatory (Less Water Less Exempts)			
Solvent (Surface Cleaner)	0.21 (25)*	* VOC content applies to this category only			
Pretreatments Coating/Wash Primer	5.5 (660)				
Primer/Primer Surfacer	2.1 (250)				
Primer Sealer	2.1 (250)				
Single-Stage Coating	2.8 (340)				
Color Coating	3.5 (420)				
Clear Coating	2.1 (250)				
Uniform Finish Coating	4.5 (540)				
Adhesion Promoter	4.5 (540)				
Product Code & Name		Reducer	Mix Ratio	VOC Content	
Solvent (Substrate Cleaner)		Limit: 0.21 lbs/gal (25 g/L)			
CFX435LV - Low VOC Cleaner		Water	1 : 1	0.20 (25)	
SWX350 H2O-SO-CLEAN® Wax and Grease Remover		-	-	0.17 (20)	
SX1009 2.9 VOC Bug and Tar Remover*		-	-	2.89 (346)	
*Rule 410.4A V. E allows the use of surface preparation solvents to clean plastic parts just prior to coating or VOC-containing materials for the removal of wax and grease provided that non-aerosol, hand-held spray bottles are used with a maximum solvent VOC content of 780 g/l and the total volume of the solvent does not exceed 20 gallons per year per facility. Records of solvent usage shall be kept in accordance with Section VII.C.4 of this rule.					
Product Code & Name	Hardener/Activator	Reducer	Mix Ratio	Applied VOC Less Water Less Exempt	
Pretreatment Coating/Wash Primer		Limit: 5.5 lbs/gal (660 g/L)			
F4945 5.5 VOC Wash Primer	F4946	-	1 : 1	5.32 (637)	
SXA1031 Etch Primer – Gray	-	-	Aerosol	N/A	
Product Code & Name	Hardener/Activator	Additives	Reducer	Mix Ratio	Applied VOC Less Water Less Exempt
Primer/Primer Surfacer		Limit: 2.1 lbs/gal (250 g/L)			
ESU410 2.1/2.8 Polyurethane Primer	ESU419	ESX590	-	5 : 1 + 6 oz / RTS gal	1.99 (238)
ESU470 2.1 VOC Wet on Wet Epoxy Primer - Gray	ESU479	-	ESR300 or ESR310	2 : 1 : 1 or 2 : 1 : 2 (reducer last)	2.07 (248)
ESU480/481/482 2.1 VOC Epoxy Primer	ESU489	-	-	4 : 1	250 (2.09)
F3970/BK/WH Ultra High Solids Primer	F3971	F3400 or F3405	F3385, F3390 or F3395	3 : 1 + 6 oz / RTS gal + 10% optional reducer	2.07 (248)
F3998 2.1 VOC Primer Surfacer	F3999	-	-	2 : 1	1.99 (238)
F4921/BK/WH 2.1 VOC Epoxy Primer	F4922	-	F3385, F3390 or F3395	3 : 1 : 1	2.05 (246)
F4932/BK/WH 2.1 VOC Fast Dry Urethane Surfacer	F4933	-	F3385, F3390 or F3395	4 : 1 : 1	2.08 (249)
F4935/36/37 High Solids Epoxy Primers	F4938	-	-	1 : 1	2.08 (249)
Single-Stage Coating		Limit: 2.8 lbs/gal (340 g/L)			
ESSS Single Stage Polyurethane Enamel	ESH200	ESX5XX	-	6 : 1 : 1	2.76 (331)
FDGU Single Stage Ultra high Solids Polyurethane Enamel	F3260	F3400, F3405 or F3410	F3385, F3390 or F3395	3 : 1 + 6 oz /RTS gal + 10% reducer	2.82 (338)
FDSU Ultra HS Polyurethane Single Stage	F3260	F3400, F3405 or F3410	F3385, F3390 or F3395	3 : 1 + 6 oz /RTS gal + 10% reducer	2.82 (338)

Eastern Kern APCD Rule 410.4A– PPG DELFLEET® Evolution and DELFLEET ESSENTIAL®



Eastern Kern APCD
Motor Vehicle and Mobile Equipment
Refinishing Operations
Rule 410.4A
 Amended: 03/13/2014 | In Effect: 03/13/2014



Product Code & Name	Hardener/ Activator	Additives	Reducer	Mix Ratio	Applied VOC Less Water Less Exempt
Color Coating					Limit: 3.5 lbs/gal (420 g/L)
ESSS Polyurethane Basecoat	ESH210	ESB800	-	2 : 1 : 1	3.64 (304)
FBCH High Solids Polyurethane Basecoat	F3200, F3259 or F3260	F3440, F3441 or F3442	-	3 : 1 : 1	3.47 (416)
FBCS High Solids Basecoat - Fast	F3200 or F3260-	-	F3385	3 : 1 + 10%	3.04 (364)
FBCS High Solids Basecoat - Fast	F3200 or F3260-	-	F3330, F3340, F3350 or F3360	3 : 1 + 10%	3.41 (409)
Product Code & Name	Hardener/ Activator	Additives	Reducer	Mix Ratio	Applied VOC Less Water Less Exempt
Clear Coating					Limit: 2.1 lbs/gal (250 g/L)
ESC621 2.1 VOC Clearcoat	ESH200	-	ESX711, ESX721, ESR300 or ESR310	4 : 1 : 1	2.06 (247)
F3921 2.1 VOC Clearcoat	F3210 or F3211	-	F3385, F3390 or F3395	3 : 1 : 1/2	2.05 (246)
Additional Products: (listing not intended to be all inclusive)					
FBCH500 FBCH Blending Clear	SLV73 Fisheye Eliminator			SUA4903 Advanced Plastic Bond	
FDGU500 FDGU Blending Clear	SU4901 Clean and Scuff Sponge			SXA840 Blending Solvent	

Eastern Kern APCD Rule 410.4A – DELFLEET® Evolution and DELFLEET ESSENTIAL®

This “Eastern Kern APCD Rule 410.4A (PPG *Delfleet*)” wall chart is intended to provide INFORMATION to PPG’s customers. In providing this wall chart, PPG makes no separate or additional warranties, express or implied, and assumes no liability or responsibility arising out of its use. It is the responsibility of each customer, RE-SELLER AND END USER of PPG’s products to independently ascertain that their practices are legal, appropriate and constitute sound product stewardship. This “Eastern Kern APCD Rule 410.4A (PPG *Delfleet*)” wall chart does not include all currently compliant *Delfleet* products. The representative products listed are compliant with Eastern Kern APCD Rule 410.4A VOC limits as of the date of this wall chart; however, subsequent changes in Eastern Kern APCD Rule 410.4A may change the compliance status of the listed products. It is the responsibility of the end user to review and comply with current regulations, including applicable coating category VOC limits, as of the date of product purchase and/or use. This document is not INTENDED to define or create legal rights or obligations. It is the responsibility of each customer, RE-SELLER AND END USER to comply with all applicable federal, state and local laws.



PPG Industries
 Commercial Coatings
 19699 Progress Drive
 Strongsville, OH 44149
 1-800-647-6050

PPG Canada Inc.
 2301 Royal Windsor Drive, Unit #6
 Mississauga, Ontario L5J 1K5
 1-888-310-4762