



# 2.1 VOC Epoxy Primers



## Speed Up Your Prime Times!

### Features & Benefits:

- 2.1 VOC compliant
- Available in: 274528SP Gray, 274530SP White, 274531SP Black
- Extremely fast dry times
- Corrosion resistant
- Can be applied to properly prepared Stainless Steel and so many other substrates
- Allow 8-12 hours dry time before sanding, if necessary

### May be Applied Over:

- Properly cleaned and sanded:
  - Steel/stainless steel
  - Blasted steel
  - Carbon steel
  - Galvanized steel
  - Aluminum
  - Fiberglass
- Previously painted surfaces with proper prep
- MAP® Ultra Low VOC satin or gloss
- MAP®
- SATIN MAP®
- SVOC MAP®
- VOC MAP®
- Body fillers
- Masonry
- Wood



**Dry Times at 70°F (21°C):**

- Dust Free..... 15 - 20 minutes
- Dry to Touch ..... 20 - 30 minutes
- Dry to Handle..... 30 - 45 minutes
- Dry to Topcoat..... 30 - 45 minutes



### The Complete Matthews Paint System:



### Learn More:

760 Pittsburgh Drive • Delaware, OH 43015  
 Toll Free: 800.323.6593 • Fax: 800.947.0377  
[www.matthewspaint.com](http://www.matthewspaint.com)

