



Yolo-Solano AQMD

Motor Vehicle and Mobile Equipment Coating Operations

Rule 2.26

Amended: 12/10/2008 | In Effect: 7/1/2010



| Coating Category | lbs/U.S. gal (g/L) Limit: VOC Regulatory (Less Water Less Exempts). |
|----------------------------|---|
| Solvent (Surface Cleaner)* | 0.21 (25) |
| Pretreatment Coating | 5.5 (660) |
| Primer / Primer Surfacer | 2.1 (250) |
| Primer Sealer | 2.1 (250) |
| Single Stage Coating | 2.8 (340) |
| Color Coating | 3.5 (420) |
| Underbody Coating | 3.6 (430) |
| Clear Coating | 2.1 (250) |
| Uniform Finish Coating | 4.5 (540) |
| Adhesion Promoter | 4.5 (540) |

*VOC content applies to this category only.

| Product Code & Name | Hardener/Activator | Reducer | Mix Ratio | VOC Content |
|--|--------------------|---------|-----------|------------------------------|
| Solvent (Surface Cleaner) | | | | Limit: 0.21 lbs/gal (25 g/L) |
| SWX350 H ₂ O-SO-CLEAN [®] Wax & Grease Remover | - | - | - | 0.17 (20) |

| Product Code & Name | Hardener/Activator | Reducer | Additives | Mix Ratio | Applied VOC Less Water Less Exempt |
|--|--------------------|---------------------|-----------|-------------|---------------------------------------|
| Pre-Treatment Coatings | | | | | Limit: 5.5 lbs/gal (660 g/L) |
| SX1071 ECOBASE [®] 5.5 Etch Prime | SX1072 | - | - | 1:1 | 5.48 (657) |
| SXA1031 Etch Primer - Gray | - | - | - | Aerosol | N/A |
| Primer Surfacer | | | | | Limit 2.1 lbs/gal (250 g/L) |
| P565-540X HS Plus Primer Surfacer | P210-5475 | P850-1775 | - | 4:1 | 2.08 (249) |
| P565-540X HS Plus Primer Surfacer | P210-5475 | P850-1775 | - | 4:1:1 | 2.08 (249) |
| P565-540X HS Plus Primer Surfacer | P210-5475 | P850-1775 | P275-2157 | 4:1:1 + 10% | 2.09 (250) |
| P950-5505 Waterborne Primer Surfacer | - | P980-5000 | - | 1:13% | 0.72 (86) |
| DPLV 2.1 Epoxy Primer | DP401LV | D8764, D8774, D8767 | - | 2:1:1 | 2.09 (250) |
| Primer Sealer (apply over previously coated surfaces) | | | | | Limit: 2.1 lbs/gal (250 g/L) |
| P565-314X HS Plus Wet-On-Wet Sealer LV | P210-5475 | P850-1775 | - | 4:1:1 | 1.82 (218) |
| Single Stage Coating | | | | | Limit: 2.8 lbs/gal (340 g/L) |
| P989 AQUABASE [®] Plus Interior System | P210-9136 | P980-5000 | - | 100:15:15 | 2.79 (334) |
| Basecoat for Multi Stage Topcoat System | | | | | Limit: 3.5 lbs/gal (420 g/L) |
| P989 Aquabase Plus Basecoat | - | P980-5000 | - | 100:10 | 3.35 (401) |
| P989 Aquabase Plus Basecoat | - | P980-5000 | - | 100:20 | 3.40 (407) |
| P989 Aquabase Plus Basecoat | - | P980-5000 | - | 100:30 | 3.50 (419) |
| P989 Aquabase Plus Basecoat | - | - | P935-1250 | 100:10 | 3.36 (403) |
| P989 Aquabase Plus Basecoat | - | P980-5000 | P935-1250 | 100:10:10 | 3.38 (405) |
| P989 Aquabase Plus Basecoat | - | P980-5000 | P935-1250 | 100:20:10 | 3.40 (407) |
| P989 Aquabase Plus Basecoat | P210-9120 | P980-5000 | - | 100:10:10 | 3.05 (336) |
| P989 Aquabase Plus Basecoat | P210-9120 | P980-5000 | - | 100:10:20 | 3.09 (370) |
| P989 Aquabase Plus Basecoat | P210-9120 | P980-5000 | - | 100:10:30 | 3.11 (373) |



Yolo-Solano AQMD

Motor Vehicle and Mobile Equipment Coating Operations

Rule 2.26

Amended: 12/10/2008 | In Effect: 7/1/2010



| Product Code & Name | Hardener/Activator | Reducer | Additives | Mix Ratio | Applied VOC Less Water Less Exempt |
|--|------------------------|------------------------|-----------|----------------|---------------------------------------|
| Underbody Coatings (Specialty) | | | | | Limit: 3.6 lbs/gal (430 g/L) |
| P989 Aquabase Plus Engine Bay Color | P210-9120 | P980-5000 | - | 100:15:15 | 3.08 (369) |
| Clear Coating | | | | | Limit: 2.1 lbs/gal (250 g/L) |
| P190-6490 Scratch Resistant Clearcoat | P210-8490 | - | - | 2:1 | 2.00 (240) |
| P190-6730 HS Plus Clearcoat | P210-65XX | P850-1775 | - | 3:1:10% | 2.05 (246) |
| P190-6759 Express Clearcoat LV | P210-87X | P850-1775 | - | 3:1:1.5 | 2.08 (249) |
| P190-6759 Express Clearcoat LV | P210-87X | P850-1775 | P275-2200 | 3:1:1.5% | 2.08 (249) |
| P190-6759 Express Clearcoat LV | P210-87X | P850-1775 | P275-2200 | 3:1:1.5:5% | 2.08 (249) |
| P190-6759 Express Clearcoat LV | P210-87X | P850-1775 | - | 3:1:1 | 2.08 (249) |
| P190-6790 HS Clearcoat LV | P210-87X | P850-1775 | - | 3:1:1 | 2.08 (249) |
| P190-6790 HS Clearcoat LV | P210-87X | P850-1775 | - | 3:1:1.5 | 2.08 (249) |
| P190-6800 HS Express Clearcoat | P210-6875 P210-6875 | P850-1775 P852-1683 | - | 4:1:1 4:1:1 | 1.90 (228) 2.08 (249) |
| P190-6930 Performance Clearcoat | P210-6975 | P850-691X | - | 3:1:1 | 1.94 (232) |
| P190-6950 Extended Performance Clearcoat | P210-6975 | P850-691X | - | 3:1:1 | 2.01 (241) |
| P910-5510 Waterborne Clearcoat | P210-8860 | P980-5000 | - | 5:2:2 | 2.09 (250) |

| Additional Products (listing not intended to be all inclusive) | | |
|---|---|---|
| P100-2021 Flexible Additive | SLV898 Retarder | SXA1044 High Build Flexible Surfacers |
| SLV4985 Universal Flattening Agent | SU470LV 1K Compliant Adhesion Promoter | SXA1050 Plastic Adhesion Promoter |
| SLV73 Fisheye Eliminator | SU4901 Clean and Scuff Sponge | SX1047 High Build WB Flexible Surfacers |
| SLV814 Universal Flexibilizer | SUA4903 Advanced Plastic Bond (Aerosol) | SWX100 Waterborne Gun Cleaner |
| SLV840 Uniform Finish Blender | SXA1030 Black Guide Coat (Aerosol) | |
| SXA840 Uniform Finish Blender | SXA1041 Bumper Black (Aerosol) | |

This "Yolo-Solano AQMD Rule 2.26 PPG Nexa Autocolor" wall chart is intended to provide INFORMATION to PPG's customers. In providing this wall chart, PPG makes no separate or additional warranties, express or implied, and assumes no liability or responsibility arising out of its use. It is the responsibility of each customer, RE-SELLER AND END USER of PPG's products to independently ascertain that their practices are legal, appropriate and constitute sound product stewardship. This "Yolo-Solano AQMD Rule 2.26 PPG Nexa Autocolor" wall chart does not include all currently compliant PPG Nexa Autocolor products. The representative products listed are compliant with Rule 2.26 VOC limits as of the date of this wall chart; however, subsequent changes in Rule 2.26 may change the compliance status of the listed products. It is the responsibility of the end user to review and comply with current regulations, including applicable coating category VOC limits, as of the date of product purchase and/or use. This document is not INTENDED to define or create legal rights or obligations. It is the responsibility of each customer, RE-SELLER AND END USER to comply with all applicable federal, state and local laws.