



State of Delaware
Title 7 Regulation 1124 Section 11.0
Mobile Equipment Repair and Refinishing
 (adopted and effective 10/11/10)



Coating Category	Effective 10/11/10 lbs/gal (g/L)	
Solvent (Surface Cleaner)*	0.21 (25)	
Pretreatment Coating	5.5 (660)	
Primer / Primer Sealer / Primer Surfacer	2.1 (250)	
Single-Stage Coating	2.8 (340)	
Color Coating (Basecoat)	3.5 (420)	
Underbody Coating	3.6 (430)	
Clear Coating	2.1 (250)	
Uniform Finish Coating	4.5 (540)	
Adhesion Promoter	4.5 (540)	* VOC concentration of a Surface Cleaner applies to this category

Product Code & Name	Reducer	Mix Ratio	VOC content
Solvent (Substrate Cleaner)			Limit: 0.21 lb/gal (25 g/L)
SWX350 H2O-So-Clean Wax & Grease Remover	-	-	0.17 ((20)
SWX360 Waterborne Pre-Cleaner	water	1:2	0.20 (24)
CFX435LV Low VOC Cleaner	water	1:1	0.21 (25)
SX1009 2.9 VOC Bug and Tar Remover*	water	1:1	0.21 (25)

*11.3.2.1 Special cleaning solvent for use in specific and difficult cleaning tasks associated with surface preparation with a VOC content no greater than 350 g/l may be used at a volume equal to 2.5% of the preceding years annual coating usage up to a maximum of 40 gallons per year.

Product Code & Name	Hardener/ Activator	Additives	Mix Ratio	Applied VOC Less Water Less Exempt
Pretreatment Coating				Limit: 5.5 lb/gal (660 g/L)
SXA1031 Etch Primer – Gray	-	-	Aerosol	N/A
F3946 5.5 Wash Primer	F3947	-	1:1	5.48 (657)
Primer				Limit: 2.1 lb/gal (250 g/L)
CRE-X21 Series Epoxy Primers	CRE-211H	-	2:1	2.08 (249)
CRE-X21 Series Epoxy Primers	CRE-211H	-	2:1:1/2 Exempt Solvent	2.08 (249)
MBE-200 Medium Build Epoxy Primer	MBE-201	-	3:1	2.08 (249)
ERP-X20 Fast Multi-Use Epoxy Primers	ERP-201	-	1:1	2.03 (243)
HSP-2128 2.1 VOC Tintable Polyurethane Primer	HSP-211	UA-11	102 : 20 : 6	2.05 (246)
MV390-9300 Aquacron Waterborne Acrylic Primer	-	-	RTS	1.78 (213)
Single-Stage Coating				Limit: 2.8 lb/gal (340 g/L)
ALK-280 Low VOC Acrylic Modified Alkyd Enamel	-	-	RTS	2.24 (268)
AUE-120 2K HS Interior Polyurethane Enamel	AUE-3606A	-	4:1	2.81 (337)
AUE-120 2K HS Interior Polyurethane Enamel	AUE-3606A	-	4: 1 :1/2 Exempt Solvent	2.81 (337)
AUE-280 2.8 VOC Polyurethane Enamel	AUE-281	UA-11 or UE-28	4:1+ 6 oz. rts gal	2.76 (331)
AUE-280 LG 2.8 VOC Polyurethane Enamel	AUE-281	-	6 :1	2.64 (316)
AUE-370 DTM Polyurethane	AUE-3501	UA-11	5:1 + 6 oz. rts gal	2.65 (318)
AUE-370 DTM Polyurethane	GXH1086	UA-11	4:1 + 6 oz. rts gal	2.8 (336)
WPM-495 Grey Water Reducible DTM	-	-	RTS	1.1 (132)
WPM-901LG Black Water Reducible DTM	-	-	RTS	1.09 (131)
MV488 Aquacron Water Reducible Alkyd	-	-	RTS	2.8 (336)
MV380 Aquacron Waterborne Acrylic	-	-	RTS	2.1 (250)

This "State of Delaware Title 7 Regulation 1124 Section 11.0 (PPG CPC) wall chart is intended to provide INFORMATION to PPG's customers. In providing this wall chart, PPG makes no separate or additional warranties, express or implied, and assumes no liability or responsibility arising out of its use. It is the responsibility of each customer, RE-SELLER AND END USER of PPG's products to independently ascertain that their practices are legal, appropriate and constitute sound product stewardship. This "State of Delaware Title 7 Regulation 1124 Section 11.0 (PPG CPC)" wall chart does not include all currently compliant CPC products. The representative products listed are compliant with Title 7 Regulation 1124 Section 11.0 VOC limits as of the date of this wall chart; however, subsequent changes in Title 7 Regulation 1124 Section 11.0 may change the compliance status of the listed products. It is the responsibility of the end user to review and comply with current regulations, including applicable coating category VOC limits, as of the date of product purchase and/or use. This document is not INTENDED to define or create legal rights or obligations. It is the responsibility of each customer, RE-SELLER AND END USER to comply with all applicable federal, state and local laws.