

SAMSON



FARM BACKHOE SKID STEER

Backhoe Rear- Industrial Plus R-4 XHD



(R-4A model shown)

Catalog No.	Size/Ply	Type	Pattern	Speed Symbol	Section Width (in.)	Overall Diameter (in.)	Inflation Pressure (psi)	Max Load (lbs)	Tread Depth (32nds)
99060H-2	14.9L-24/12	TBLS	R-4A	A8	14.9	48.9	42	6395	32.0
99010L-2	16.9L-24/12	TBLS	R-4A	A8	16.9	51.5	38	7165	32.0
99010H-2	16.9L-24/12	TBLS	R-4A	A8	16.9	51.5	38	7165	32.0
99020L-2	17.5L-24/12	TBLS	R-4A	A8	17.5	48.9	38	6605	32.0
99020H-2	17.5L-24/12	TBLS	R-4A	A8	17.5	48.9	38	6605	32.0
99030H-2	19.5L-24/14	TBLS	R-4A	A8	19.5	51.7	38	8145	35.9
99040H-2	21L-24/16	TBLS	R-4A	A8	21.0	54.3	41	9920	40.1

Tire Features & Benefits

- Ultimate backhoe tire.
- Extra wide tread design for high flotation and super stability in extreme conditions.
- Large center bars for superior road-ability, extra deep tread for superior traction.
- Reinforced sidewall with curb and rim guard to provide extra protection against rim and sidewall damage.

Backhoe Rear- Industrial Plus R-4 XHD Ultra



(R-4B model shown)

Catalog No.	Size/Ply	Type	Pattern	Speed Symbol	Section Width (in.)	Overall Diameter (in.)	Inflation Pressure (psi)	Max Load (lbs)	Tread Depth (32nds)
99110-2	16.9-24/12	TBLS	R-4B	A8	16.9	51.5	38	7165	35.3
99120-2	17.5L-24/12	TBLS	R-4B	A8	17.5	48.9	38	6605	32.0
99130-2	19.5L-24/12	TBLS	R-4B	A8	19.5	51.7	33	7605	35.9
99140-2	21L-24/12	TBLS	R-4B	A8	21.0	54.3	32	8545	36.5
99160-2	14.9-24/12	TBLS	R-4B	A8	14.9	48.9	42	6395	32.0

Tire Features & Benefits

- Provides tight center bars for excellent road-ability.
- Reinforced sidewall with curb and rim guard to provide extra protection against rim and sidewall damage.
- Deep tread lugs deliver excellent traction in muddy soil conditions.
- Excellent self cleaning tread design.

Backhoe Rear- Industrial Ultra R-4 XHD



(R-4 model shown)

Catalog No.	Size/Ply	Type	Pattern	Speed Symbol	Section Width (in.)	Overall Diameter (in.)	Inflation Pressure (psi)	Max Load (lbs)	Tread Depth (32nds)
98010L-2	16.9-24/12	TBLS	R-4	A6	16.9	51.5	35	5465	32.8
98020L-2	17.5L-24/12	TBLS	R-4	A6	17.5	48.9	33	4255	33.4
98030L-2	19.5L-24/12	TBLS	R-4	A6/*A8	19.5	51.7	30/*30	4730/*5200	37.2
98040L-2	21L-24/12	TBLS	R-4	A6/*A8	21.0	54.3	28/*28	5310/*5840	37.2

Tire Features & Benefits

- Wide foot print for high flotation and stability, delivers excellent traction.
- Premium tread width and depth provide increased tire life and trouble-free performance.

Backhoe Front- Industrial F-3 XHD



(F-3 model shown)

Catalog No.	Size/Ply	Type	Pattern	Speed Symbol	Section Width (in.)	Overall Diameter (in.)	Inflation Pressure (psi)	Max Load (lbs)	Tread Depth (32nds)
19502-2	11L-15/14	TBLS	F-3	A6	11.0	32.0	73	2855	16.0
19521-2	11L-16/14	TBLS	F-3	A6	11.0	33.0	73	3055	16.0

Tire Features & Benefits

- Applicable for agricultural tractors in industrial service and backhoes.
- Deep tread offers excellent impact, cut and puncture resistance.
- Provides superior traction on hard soil, asphalt and concrete.

Backhoe Front I-3 Bias Tires



(L-2D model shown)

Catalog No.	Size/Ply	Type	Pattern	Speed Symbol	Section Width (in.)	Overall Diameter (in.)	Inflation Pressure (psi)	Max Load (lbs)	Tread Depth (32nds)
19532-2	10.5/80-18/12	TBLS	L-2D	A6	10.8	34.7	62	3230	20.2
19542-2	12.5/80-18/14	TBLS	L-2D	A6	12.1	37.9	62	4675	25.2
19552-2	10-16.5/10	TBLS	L-2D	A2	10.4	30.4	75	4710	20.2
19562-2	12-16.5/12	TBLS	L-2D	A2	12.1	32.7	80	6320	23.9

Tire Features & Benefits

- Applicable for front backhoe service.
- Durable tread pattern for high flotation and super stability.
- Designed to resist chunking and tearing.
- Features also include rim guard and heavy duty sidewall.

I-3 Trak-Tor Industrial



(R-4C model shown)

Catalog No.	Size/Ply	Type	Pattern	Speed Symbol	Section Width (in.)	Overall Diameter (in.)	Inflation Pressure (psi)	Max Load (lbs)	Tread Depth (32nds)
19530-2	10.5/80-18/14	TBLS	R-4C	A6	10.8	34.7	70	3375	32.0
19534-2	12.5/80-18/16	TBLS	R-4C	A6	12.1	37.9	71	4805	32.0
19536-2	10-16.5/12	TBLS	R-4C	A2	10.4	30.4	90	5240	21.4
19537-2	12-16.5/14	TBLS	R-4C	A2	12.1	32.7	90	6780	26.5

Tire Features & Benefits

- Premium tire for front backhoe service with deeper tread for longer service life.
- Durable tread pattern for high flotation and super stability.
- Designed to resist chunking and tearing.
- Features also include rim guard and heavy duty sidewall.

Skid Steer- Premium Skid Steer



(L-2D model shown)

Catalog No.	Size/Ply	Type	Pattern	Speed Symbol	Section Width (in.)	Overall Diameter (in.)	Inflation Pressure (psi)	Max Load (lbs)	Tread Depth (32nds)
16051-2	10-16.5/8	TBLS	L-2D	A2	10.4	30.4	59	4140	20.2
16052-2	10-16.5/10	TBLS	L-2D	A2	10.4	30.4	75	4710	20.2
16055-2	12-16.5/10	TBLS	L-2D	A2	12.1	32.7	65	5600	23.9
16056-2	12-16.5/12	TBLS	L-2D	A2	12.1	32.7	80	6320	23.9
16058-2	14-17.5/16	TBLS	L-2D	A2	13.7	36.3	100	8260	27.7
16059-2	15-19.5/16	TBLS	L-2D	A2	15.3	40.1	80	10880	31.5

Tire Features & Benefits

- Applicable for skid-steer and backhoe service.
- Durable tread pattern for high flotation and super stability.
- Designed against resistance to chunking and tearing.
- Features also include rim guard and heavy duty sidewall.

Skid Steer- Sidewinder Mudder XHD



(L-2E model shown)

Catalog No.	Size/Ply	Type	Pattern	Speed Symbol	Section Width (in.)	Overall Diameter (in.)	Inflation Pressure (psi)	Max Load (lbs)	Tread Depth (32nds)
16000-2	5.70x12/8	TBLS	L-2B	A2	5.7	22.4	90	1875	18.9
16002-2	23X8.50-12/8	TBLS	L-2B	A2	8.4	22.6	65	2170	18.9
16004-2	27X8.50-15/10	TBLS	L-2B	A2	8.4	26.7	70	2270	18.9
16050-2	10-16.5/8	TBLS	L-2E	A2	10.4	31.4	59	4140	21.4
16054-2	10-16.5/10	TBLS	L-2E	A2	10.4	31.4	75	4710	21.4
16028-2	10-16.5/12	TBLS	L-2E	A2	10.4	31.4	90	5240	21.4
16030-2	10-16.5/14	TBLS	L-2E	A2	10.4	31.4	104	6040	21.4
16038-2	12-16.5/14	TBLS	L-2E	A2	12.4	34.1	90	6780	26.5
16040-2	12-16.5/16	TBLS	L-2E	A2	12.4	34.1	110	7920	26.5
16042-2	33X15.50-16.5/12	TBLS	L-2E	A2	15.5	33.0	61	8005	32.1

Tire Features & Benefits

- Ultra heavy duty skid-steer tire.
- Features reinforced sidewalls and rim guard that provides extra protection against sidewall damage.
- Extra deep tread for superior traction and longer tread life.
- Triple step lug provides self cleaning capabilities.

Skid Steer- Heavy Duty L4A

S = STEEL BELTED N = NYLON BELTED



(L-4A model shown)

Catalog No.	Size/Ply	Type	Pattern	Speed Symbol	Section Width (in.)	Overall Diameter (in.)	Inflation Pressure (psi)	Max Load (lbs)	Tread Depth (32nds)
16150-2 (S)	10-16.5/10	TBLS	L-4A	A2	10.4	30.4	75	4710	34.0
16152-2 (S)	10-16.5/12	TBLS	L-4A	A2	10.4	30.4	90	5240	34.0
16160-2 (S)	12-16.5/12	TBLS	L-4A	A2	12.1	32.7	80	6320	42.2
16162-2 (S)	12-16.5/14	TBLS	L-4A	A2	12.1	32.7	90	6780	42.2
16170-2 (S)	14-17.5/16	TBLS	L-4A	A2	13.7	36.3	100	8260	47.2
16180-2 (S)	15-19.5/14	TBLS	L-4A	A2	15.3	40.1	70	10060	47.2
16151-2 (N)	10-16.5/10	TBLS	L-4A	A2	10.4	30.4	75	4710	34.0
16153-2 (N)	10-16.5/12	TBLS	L-4A	A2	10.4	30.4	90	5240	34.0
16164-2 (N)	12-16.5/12	TBLS	L-4A	A2	12.1	32.7	80	6320	42.2
16163-2 (N)	12-16.5/14	TBLS	L-4A	A2	12.1	32.7	90	6780	42.2
16171-2 (N)	14-17.5/16	TBLS	L-4A	A2	13.7	36.3	100	8260	47.2
16174-2 (N)	15-19.5/14	TBLS	L-4A	A2	15.3	40.1	70	10060	47.2

Tire Features & Benefits

- Severe service skid-steer tire with non-directional design for packed soil, or hard surface applications.
- Reinforced sidewall with curb and rib guard that provides extra protection against rim and sidewall damage.
- Reinforced for superior tread stability and greater penetration resistance.
- Available in steel or nylon belts.

Severe Service Skid Steer - L5



(L-5)

Catalog No.	Size/Ply	Type	Pattern	Speed Symbol	Section Width (in.)	Overall Diameter (in.)	Inflation Pressure (psi)	Max Load (lbs)	Tread Depth (32nds)
16190-2	32X11-16.5	TL	L-5	A2	12.1	32.7	60	5340	48.5
16195-2	34X12.5-16.5	TL	L-5	A2	12.1	34.3	65	5600	52.0

- Severe service skid-steer tire with non-directional design for packed soil, or hard surface applications.
- Reinforced sidewall with curb and rib guard that provides extra protection against rim and sidewall damage.
- Reinforced for superior tread stability and greater penetration resistance.
- Available in steel or nylon belts.

Farm Front- Harrow-Track F-2



(F-2 model shown)

Catalog No.	Size/Ply	Type	Pattern	Speed Symbol	Section Width (in.)	Overall Diameter (in.)	Inflation Pressure (psi)	Max Load (lbs)	Tread Depth (32nds)
97100-2	4.00-12/4	TT	F-2	A8	4.4	21.2	52	495	15.1
97105-2	5.00-12/4	TT	F-2	A8	5.1	22.4	52	605	15.1
97120-2	5.00-15/4	TT	F-2	A8	5.1	26.1	44	715	16.4
97125-2	7.5L-15/6	TT	F-2	A8	8.2	29.4	44	1430	18.9
97130-2	9.5L-15/8	TT	F-2	A8	9.5	30.8	48	1870	30.2
97135-2	11L-15/8	TT	F-2	A8	11.0	32.0	44	2090	34.6
97140-2	5.50-16/4	TT	F-2	A8	5.9	28.1	40	860	13.9
97145-2	6.00-16/6	TT	F-2	A8	6.3	29.1	52	1140	18.9
97150-2	6.50-16/6	TT	F-2	A8	6.8	30.0	48	1230	18.3
97155-2	7.50-16/8	TT	F-2	A8	8.0	31.8	56	1710	24.6
97158-2	7.50-20/8	TT	F-2	A8	8.0	35.8	54	2250	26.5
97160-2	10.00-16/8	TT	F-2	A8	10.8	35.2	44	2340	32.8
97165-2	11.00-16/8	TT	F-2	A8	12.4	38.1	40	2600	30.2
97170-2	7.50-18/6	TT	F-2	A8	8.0	33.8	44	1610	26.5
97175-2	4.00-19/4	TT	F-2	A8	4.4	28.2	52	715	15.1

Farm Front- Harrow Track 4 Rib F-2



(F-2A model shown)

Catalog No.	Size/Ply	Type	Pattern	Speed Symbol	Section Width (in.)	Overall Diameter (in.)	Inflation Pressure (psi)	Max Load (lbs)	Tread Depth (32nds)
97700-2	10.00-16/10	TT	F-2A	A8	10.8	35.2	52	2600	26.5
97705-2	10.00-16/10	TBLS	F-2A	A8	10.8	35.2	52	2600	26.5
97708-2	11.00-16-10	TT	F-2A	A8	12.4	38.1	52	3080	29.0
97710-2	11.00-16-12	TT	F-2A	A8	12.4	38.1	60	3420	29.0
97715-2	11.00-16-10	TBLS	F-2A	A8	12.4	38.1	52	3080	29.0
97718-2	11.00-16-12	TBLS	F-2A	A8	12.4	38.1	60	3420	29.0

Tire Features & Benefits

- Wide foot print and more surface contact allows for even better steering control and resistance to side slip.
- Designed to resist stubble punctures.
- Self cleaning tread design enhanced steering performance.

Farm Front- Harrow Track I-1



I-1 Model



I-1E Model

Catalog No.	Size/Ply	Type	Pattern	Speed Symbol	Section Width (in.)	Overall Diameter (in.)	Inflation Pressure (psi)	Max Load (lbs)	Tread Depth (32nds)
97180-2	8.5L-14/6	TT	I-1	B	8.5	28.4	36	1870	7.6
97185-2	9.5L-14/8	TT	I-1	B	9.5	29.2	44	2400	8.2
97190-2	11L-14/6	TT	I-1	B	11.0	29.6	28	2040	8.2
97195-2	5.90-15/4	TT	I-1	B	6.1	26.2	36	1140	7.6
97200-2	6.70-15/6	TT	I-1	B	6.7	27.7	44	1610	7.6
97205-2	7.60-15/8	TT	I-1	B	7.6	28.9	52	2090	7.6
97206-2	7.60-15/8	TBLS	I-1	B	7.6	28.9	52	2090	7.6
97210-2	9.5L-15/8	TT	I-1	B	9.5	30.2	44	2470	8.2
97212-2	9.5L-15/8	TBLS	I-1	B	9.5	30.2	44	2470	8.2
97211-2	9.5L-15/8	TT	I-1E	B	9.8	28.8	44	2470	7.6
97214-2	9.5L-15/8	TBLS	I-1E	B	9.8	28.8	44	2470	7.6
97232-2	9.5L-15/12	TBLS	I-1E	B	9.8	28.8	44	2470	7.6
97215-2	10.00-15/8	TBLS	I-1	B	10.8	33.6	40	3200	10.7
97220-2	11L-15/8	TT	I-1	B	11.0	30.6	36	2540	8.2
97225-2	11L-15/8	TBLS	I-1	B	11.0	30.6	36	2540	8.2
97219-2	11L-15/8	TT	I-1E	B	10.9	29.4	36	2540	7.6
97228-2	11L-15/8	TBLS	I-1E	B	10.9	29.4	36	2540	7.6
97231-2	11L-15/12	TBLS	I-1E	B	10.9	29.4	36	2540	7.6
97230-2	12.5L-15/10	TT	I-1	B	12.5	32.4	44	3000	8.8
97235-2	27X9.50-15/8	TBLS	I-1	B	9.0	27.0	60	1870	12.0
97240-2	6.00-16/6	TT	I-1	B	6.3	28.0	44	1520	8.2
97245-2	11L-16/8	TT	I-1	B	11.0	31.6	36	2680	8.2
97250-2	12.5L-16/10	TT	I-1	B	12.5	33.4	44	3520	8.8
97260-2	31X13.50-15/10	TBLS	HF-1	B	13.8	30.8	55	2790	12.6
97265-2	5.70-15/6	TT	I-1	B	5.9	25.7	48	1490	8.2
97231-2	11L-15/12	TL	I-1	B	11.0	30.6	52	3200	8.2
97232-2	9.5L-15/12	TL	I-1	B	9.5	30.2	64	3150	8.2

Tire Features & Benefits

- Outstanding flotation use
- Easy steering from the heavy grooved ribs.
- Extra wide design.
- Non-highway service/ low speed applications.
- Also available in two economy (I-1E) sizes.

Farm Rear- Agri-Trac R-1+



(R-1KA model shown)

Tire Features & Benefits

- Bar angle provides superior traction in the field and good wear during road transportation.
- Variety of sizes for use with tractors, combines, and irrigation systems.
- Heavy duty design for excellent ride, snag resistance and long wear.

Catalog No.	Size/Ply	Type	Pattern	Speed Symbol	Section Width (in.)	Overall Diameter (in.)	Inflation Pressure (psi)	Max Load (lbs)	Tread Depth (32nds)	Tread Pattern Pitch
97012-2	14.9-24/4	TT	R-1	A6/*A8	15.0	49.8	14/*12	2665/*2200	37.8	17.0
97002-2	8.3-24/8	TT	R-1	A6	8.3	39.2	46	2115	35.3	19.0
97003-2	9.5-20/8	TT	R-1	A6	9.4	37.4	41	2105	37.8	17.0
97004-2	9.5-24/8	TT	R-1	A6	9.4	41.3	41	2445	37.8	19.0
96000-2	11.2-24/6	TT	R-1S	A6/*A8	11.2	43.5	26/*26	2300/*2090	44.1	24.0
96010-2	12.4-24/6	TT	R-1S	A6/*A8	12.4	45.7	24/*24	2645/*2400	45.4	24.0
96015-2	14.9-24/8	TT	R-1S	A6/*A8	15.0	49.8	26/*26	3880/*3520	47.9	24.0
96020-2	14.9-28/8	TT	R-1S	A6/*A8	15.0	53.7	26/*26	4145/*3740	47.9	26.0
96030-2	18.4-38/10	TT	R-1S	A6/*A8	18.3	69.1	26/*26	6975/*6400	51.7	30.0
97000-2	11.2-24/4	TT	R-1KA	A6/*A8	11.2	43.5	19/*18	1860/*1655	42.8	17.0
97001-2	11.2-24/8	TT	R-1KA	A6	11.2	43.5	35	2700	42.8	17.0
97005-2	12.4-24/4	TT	R-1KA	A6/*A8	12.4	45.7	16/*16	2085/*1870	41.6	17.0
97006-2	12.4-24/8	TT	R-1KA	A6/*A8	12.4	49.6	33/*32	3120/*2830	41.6	19.0
97010-2	14.9-24/6	TT	R-1KA	A6/*A8	15.0	49.8	20/*20	3330/*3000	45.4	17.0
97011-2	14.9-24/8	TT	R-1KA	A6/*A8	15.0	49.8	26/*26	3880/*3520	45.4	17.0
97015-2	16.9-24/8	TT	R-1KA	A6/*A8	16.9	52.6	24/*24	4500/*4080	49.9	17.0
97020-2	18.4-26/6	TT	R-1KA	A6/*A8	18.3	57.1	16/*16	4385/*3960	49.9	18.0
97025-2	11.2-28/4	TT	R-1KA	A6/*A8	11.2	47.4	19/*18	1980/*1760	39.1	19.0
97030-2	12.4-28/4	TT	R-1KA	A6/*A8	12.4	49.6	16/*16	2215/*1980	41.6	19.0
97035-2	13.6-28/6	TT	R-1KA	A6/*A8	13.6	51.6	23/*22	3155/*2830	46.6	19.0
97040-2	14.9-28/6	TT	R-1KA	A6/*A8	15.0	53.7	20/*20	3550/*3200	47.9	19.0
97045-2	16.9-28/6	TT	R-1KA	A6/*A8	16.9	56.5	19/*18	4055/*3640	49.1	19.0
97050-2	16.9-30/6	TT	R-1KA	A6/*A8	16.9	58.5	19/*18	4190/*3740	49.1	20.0
97055-2	18.4-30/6	TT	R-1KA	A6/*A8	18.3	61.0	16/*16	4675/*4190	49.9	19.0
97058-2	18.4-30/10	TT	R-1KA	A6/*A8	18.3	61.0	26/*26	6205/*5520	49.9	19.0
97057-2	24.5-32/10	TT	R-1KA	A6/*A8	24.6	71.1	20/*20	8710/*7850	54.2	21.0
97060-2	16.9-34/6	TT	R-1KA	A6/*A8	16.9	62.4	19/*18	4440/*3960	49.1	20.0
97065-2	23.1-26/10	TT	R-1KA	A6/*A8	23.2	63.2	20/*20	7155/*6400	52.9	19.0
97066-2	18.4-34/8	TT	R-1KA	A6/*A8	18.3	65.2	20/*20	5655/*5080	49.9	20.0
97067-2	18.4-34/10	TT	R-1KA	A6	18.3	65.2	26	6590	49.9	20.0
97070-2	13.6-38/8	TT	R-1KA	A6	13.6	61.6	29	4210	46.6	23.0
97075-2	15.5-38/8	TT	R-1KA	A6	15.6	61.8	26	4540	46.6	22.0
97080-2	16.9-38/8	TT	R-1KA	A6/*A8	16.9	66.3	24/*24	5555/*4940	49.1	22.0
97080G-2	16.9-38/8	TT	R-1	A6/*A8	16.9	66.3	24/*24	5555/*4940	44.1	21.0
97085-2	18.4-38/8	TT	R-1KA	A6/*A8	18.3	69.1	20/*20	5985/*5360	49.9	21.0
97086-2	18.4-38/10	TT	R-1KA	A6/*A8	18.3	69.1	26/*26	6975/*6400	49.9	21.0
97090-2	20.8-38/8	TT	R-1KA	A6/*A8	20.9	72.2	19/*18	6810/*6150	52.9	21.0
97095-2	30.5L-32/16	Tubeless	R-1C	A8	30.5	71.7	26	11000	56.7	20.0
97096-2	30.5L-32/16	TT	R-1C	A8	30.5	71.7	26	11000	56.7	20.0



GTCNA
GTC NORTH AMERICA

SAMSON

FARM BACKHOE SKID STEER

Distributed By:

