

Betriebsdruckwerte NS & Interlock G2 Pressarmaturen



NS (NICHT SCHÄLEN)			BAR
DKOSNS	M30	20S	400
	M36	25S	400
	M42	30S	250
	M52	38S	250
CESNS	M30	20S	400
	M36	25S	400
	M42	30S	250
	M52	38S	250
SFLNS	Ø 38,1 mm	12	344
	Ø 44,5 mm	16	344
	Ø 50,8 mm	20	275
	Ø 60,3 mm	24	206
	Ø 71,4 mm	32	206
SFSNS	Alle	Alle	413
SFSCNS	Alle	Alle	413
DKRNS	3/4"	12	320
	1"	16	250
	1-1/4"	20	200
	1-1/2"	24	160
	2"	32	130
AGRNS	3/4"	12	320
	1"	16	250
	1-1/4"	20	200
	1-1/2"	24	160
	2"	32	130
DAVNS	1-3/16"	19	400
	1-7/16"	23	350
	1-11/16"	27	250
	2"	32	200
DCVNS	1-3/16"	19	400
	1-7/16"	23	350
	1-11/16"	27	250
	2"	32	200
DKJNS	1-1/16"	17	275
	1-5/16"	21	275
	1-5/8"	26	206
	1-7/8"	30	206
	2-1/2"	40	206
AGJNS	1-1/16"	17	275
	1-5/16"	21	275
	1-5/8"	26	206
	1-7/8"	30	206
AGNNS	3/4"	12	275
	1"	16	275
	1-1/4"	20	206
	1-1/2"	24	172

INTERLOCK G2			BAR
DKOSH	M24	16S	400
	M30	20S	400
	M36	25S	400
	M42	30S	250
	M52	38S	250
CESH	M24	16S	400
	M30	20S	400
	M36	25S	400
	M42	30S	250
	M52	38S	250
SFLH	Ø 30,2 mm	8	344
	Ø 38,1 mm	12	344
	Ø 44,5 mm	16	344
	Ø 50,8 mm	20	275
	Ø 60,3 mm	24	206
	Ø 71,4 mm	32	206
SFSH	Alle	Alle	413
SFSCH	Alle	Alle	413
DKRH	3/4"	12	320
	1"	16	250
	1-1/4"	20	200
	1-1/2"	24	160
AGRH	3/4"	12	320
	1"	16	250
	1-1/4"	20	200
	1-1/2"	24	160
DAVH	1-3/16"	19	400
	1-7/16"	23	350
	1-11/16"	27	250
	2"	32	200
DKJH	1-1/16"	17	275
	1-5/16"	21	275
	1-5/8"	26	206
AGJH	1-1/16"	17	275
	1-5/16"	21	275
	1-5/8"	26	206
	1-7/8"	30	206
AGNH	3/4"	12	275
	1"	16	275
	1-1/4"	20	206

Stand 08-2024