CARRYALL 550

Club Car®

CARRYALL
ALWAYS TOUGH, ALWAYS READY

Maneuver over the most difficult terrain with the Carryall 550 utility vehicle, featuring 6 inches of ground clearance (the most in its class), a heavy duty brush guard, aircraft-grade aluminum frame, and rough terrain tires.

CARRYALL 550

TOUGH ENOUGH FOR ANY TASK

Max Speed
19 mph

Max Vehicle Capacity
900 lbs

Horsepower
14 hp (gas)
3.7 hp (electric)
7.4 hp (Li-ion)

Built to be rugged and versatile, the Carryall 550 UTV is a perfect solution for industrial and commercial jobs.

OPTIONS & ACCESSORIES

Ask your Club Car sales representative for details.

VersAttach™

5-Panel Rear View Mirror

Stakeside Bed

USB Port

Curtis Cab

Canopy/Windshield

Strobe Light

Rear Receiver Hitch

Available Body Colors

White | Beige | Dark Gray | Dark Green | Black | Classic Blue | Bright Blue | Titanium | Red

Colors may vary by product

CARRYALL 550

	GASOLINE	ELECTRIC	LITHIUM ION
ENGINE	Kohler EFI, 4-cycle Gas	48-volt DC	48-volt 3-phase AC
HORSEPOWER	14.5 hp (10.8 kW) rated @ 3600 RPM per SAE J1940	3.7 hp (2.7 kW) rated; peak 20 hp(14.9 kW)	7.4 hp (5.5 kW) rated @ 2863 rpm; Peak 21.4 hp (16 kW)
BATTERIES	12-volt 500 CCA 105 min reserve	Eight 6-volt flooded lead acid	Std: Vanguard 7.0kWh Lithium Opt: Vanguard 4.0kWh Lithium
CHARGER	N/A	On-board DeltaQ QuiQ (1 kW high frequency)	Std: DeltaQ IC650 - 650W high frequency Opt: DeltaQ IC900 - 900W high frequency
STEERING	Self-adjusting rack and pinion	Self-adjusting rack and pinion	Self-adjusting rack and pinion
FRONT SUSPENSION	Independent leaf spring with dual hydraulic shocks	Independent leaf spring with dual hydraulic shocks	Independent leaf spring with dual hydraulic shocks
BRAKES	4-wheel mechanical drum	4-wheel mechanical drum	4-wheel mechanical drum
PARK BRAKE	Foot operated, multi-lock	Foot operated, multi-lock	Foot operated, multi-lock
BODY AND FINISH	ArmorFlex® with automotive paint/clearcoat, aluminum finish	ArmorFlex® with automotive paint/clearcoat, aluminum finish	ArmorFlex® with automotive paint/clearcoat, aluminum finish
TIRES	22x10-10, 4-ply, extra traction	22x10-10, 4-ply, extra traction	22x10-10, 4-ply, extra traction
BED L x W x H	44.2 x 47.5 x 10.5 in (112 x 121 x 27 cm)	44.2 x 47.5 x 10.5 in (112 x 121 x 27 cm)	44.2 x 47.5 x 10.5 in (112.2 x 120.6 x 26.6 cm)
BED CAPACITY	500 lbs (227 kg)	500 lbs (227 kg)	500 lbs (227 kg)
TOTAL PAYLOAD CAPACITY	900 lbs (408 kg)	900 lbs (408 kg)	900 lbs (408 kg)
TOWING CAPACITY	900 lbs (408 kg)	900 lbs (408 kg)	900 lbs (408 kg)
WHEELBASE	78.1 in (198 cm)	78.1 in (198 cm)	78.1 in (198 cm)
GROUND CLEARANCE	6.0 in (15.2 cm)	6.0 in (15.2 cm)	6.0 in (15.2 cm)
FUEL TANK CAPACITY	5.5 gal (20.8 L)	N/A	N/A
CURB WEIGHT	942 lb (427.2 kg)	1402 lb (635.9 kg)	1102 lb (499.9 kg)
SPEED RANGE	15–17 mph (24–27 km/h)	5–17 mph (8–27 km/h)	5–19 mph (8–31 kph)
LIMITED WARRANTY	3 yr/3000 hr limited powertrain/frame 2 yr limited remaining vehicle	4 yr limited battery 3 yr limited powertrain/frame 2 yr limited remaining vehicle	5 yr limited battery warranty 3 yr limited powertrain/frame 2 yr limited remaining vehicle