Club Car
UNSURPASSED DURABILITY,
WORRY-FREE PERFORMANCE
CARRYALL 4X4 SERIES
4x4
IntelliTrak
Club Car
CARRYALL 700
CARRYALL
ALWAYS TOUGH, ALWAYS READY
EXPLORE
CARRYALL

CARRYALL 1500 AWD

ALL-AROUND HIGH-PERFORMANCE MACHINE

Max Speed
25 mph

Max Vehicle Capacity
1450 lbs

Horsepower
20 hp (gasoline)
20 hp (diesel)

CARRYALL 1700 AWD

POWERFUL HAULING FOR YOUR WHOLE TEAM

Max Speed
25 mph

Max Vehicle Capacity
1600 lbs

Horsepower
20 hp (gasoline)
20 hp (diesel)

The Club Car Advantage

IntelliTrak AWD System

Our Patented 4-Wheel drive system senses the terrain and automatically shifts power where it's needed most, no user input required.

All Aluminum Chassis

Rust and corrosion resistant, long lasting and durable, our lightweight chassis are made with aircraft grade aluminum to increase the strength and lifespan of your vehicle.

In-Frame Air Intake

Our in-frame air intake design prevents contaminants from entering your engine by sifting out dirt and debris before reaching the dual stage Donaldson cyclonic air filter.

READY FOR A HARD DAY'S WORK

Maximize your performance and productivity in any demanding work environment. Carryall's heavy-duty construction and versatile accessory options can haul your people and materials on any terrain, in any weather condition.

FOPS Certified, Automotive Style, Steel Cab Option

OPTIONS & ACCESSORIES

Ask your Club Car sales representative for details.

REINFORCED TUBE BUMPER

HEAVY-DUTY BRUSHGUARD



BELLY PAN SKID PLATE

STEEL CARGO BOX

WEATHER RESISTANT CANOPY

WINDSHIELD
(SOLID AND FOLD-DOWN AVAILABLE)

HIGH CAPACITY SUSPENSION

CV BOOT GUARD

HIGH VISIBILITY STROBE LIGHT

HEAVY-DUTY SKID PLATE

Plus many more options available!

Club Car®

	CARRYALL 1500 AWD		CARRYALL 1700 AWD	
	GASOLINE	DIESEL	GASOLINE	DIESEL
ENGINE	Kawasaki 4-cycle, industrial grade	Kubota D722, industrial grade	Kawasaki 4-cycle, industrial grade	Kubota D722, industrial grade
HORSEPOWER	20.1 hp (15 kW) rated @ 3400 RPM per SAE J1349	20 hp (15 kW) rated @ 3600 RPM per SAE J1995	20.1 hp (15 kW) rated @ 3400 RPM per SAE J1349	20 hp (15 kW) rated @ 3600 RPM per SAE J1995
BATTERIES	12-volt 500 CCA 105 min reserve	12-volt 500 CCA 105 min reserve	12-volt 500 CCA 105 min reserve	12-volt 500 CCA 105 min reserve
STEERING	Rack and pinion with tilt steering	Rack and pinion with tilt steering	Rack and pinion with tilt steering	Rack and pinion with tilt steering
FRONT SUSPENSION	Independent double A-arms with coil-over shocks	Independent double A-arms with coil-over shocks	Independent double A-arms with coil-over shocks	Independent double A-arms with coil-over shocks
REAR SUSPENSION	Semi-independent, 4-link solid axle	Semi-independent, 4-link solid axle	Semi-independent, 4-link solid axle	Semi-independent, 4-link solid axle
BRAKES	Twin piston front, single piston rear hydraulic disc	Twin piston front, single piston rear hydraulic disc	Twin piston front, single piston rear hydraulic disc	Twin piston front, single piston rear hydraulic disc
PARK BRAKE	Mechanical disc	Mechanical disc	Mechanical disc	Mechanical disc
TIRES	Standard All-terrain, 25 x 11-12, 4-ply Optional Mud, 25 x 11-12, 6-ply	Standard All-terrain, 25 x 11-12, 4-ply Optional Mud, 25 x 11-12, 6-ply	Standard All-terrain, 25 x 11-12, 4-ply Optional Mud, 25 x 11-12, 6-ply	Standard All-terrain, 25 x 11-12, 4-ply Optional Mud, 25 x 11-12, 6-ply
BED L x W x H	48.8 x 49.8 x 10.9 in (124 x 127 x 28 cm)	48.8 x 49.8 x 10.9 in (124 x 127 x 28 cm)	48.8 x 49.8 x 10.9 in (124 x 127 x 28 cm)	48.8 x 49.8 x 10.9 in (124 x 127 x 28 cm)
WHEELBASE	82 in (208 cm)	82 in (208 cm)	114 in (290 cm)	114 in (290 cm)
GROUND CLEARANCE	8.2 in (21 cm)	8.2 in (21 cm)	8.2 in (21 cm)	8.2 in (21 cm)
FUEL TANK CAPACITY	6.5 gal (24.6 L)	6.5 gal (24.6 L)	6.5 gal (24.6 L)	6.5 gal (24.6 L)
CURB WEIGHT	1430 lb (649 kg)	1550 lb (703 kg)	1630 lb (739 kg)	1750 lb (794 kg)
BED CAPACITY	Standard 800 lb (363 kg); With HD Suspension 1050 lb (476 kg)	Standard 800 lb (363 kg); With HD Suspension 1050 lb (476 kg)	800 lb (363 kg)	800 lb (363 kg)
PAYLOAD CAPACITY	Standard 1200 lb (544 kg); With HD Suspension 1450 lb (658 kg)	Standard 1200 lb (544 kg); With HD Suspension 1450 lb (658 kg)	1600 lb (726 kg)	1600 lb (726 kg)
TOWING CAPACITY	2000 lb (907 kg)	2000 lb (907 kg)	2000 lb (907 kg)	2000 lb (907 kg)
OVERALL HEIGHT	80.3 in (204 cm)	80.3 in (204 cm)	80.3 in (204 cm)	80.3 in (204 cm)
OVERALL LENGTH	124.6 in (317 cm)	124.6 in (317 cm)	154 in (391 cm)	154 in (391 cm)
OVERALL WIDTH	58.5 in (149 cm)	58.5 in (149 cm)	58.5 in (149 cm)	58.5 in (149 cm)
SPEED RANGE	25 mph (40.2 km/h)	25 mph (40.2 km/h)	25 mph (40.2 km/h)	25 mph (40.2 km/h)
LIMITED WARRANTY	1 yr/1000 hr limited vehicle warranty 2 yr/2000 hr limited powertrain warranty	1 yr/1000 hr limited vehicle warranty 2 yr/2000 hr limited powertrain warranty	1 yr/1000 hr limited vehicle warranty 2 yr/2000 hr limited powertrain warranty	1 yr/1000 hr limited vehicle warranty 2 yr/2000 hr limited powertrain warranty

Colors may vary by product

Dark Gray | Red | Dark Green

(EN - COMM0048 - US) ©2024 100724

1.800.CLUBCAR | 1.706.863.3000 | carryall.com