

QUICK REFERENCE GUIDE

Compression connectors and accessories



- Aluminum cable lugs
- Copper cable lugs
- Mechanical connectors
- Grounding system - Compression connectors
- Tools and dies



Table of contents

Aluminum cable lugs	4
Copper cable lugs	5
Mechanical connectors	7
Grounding system - Compression connectors	9
Tools and dies	16

Aluminum cable lugs



					Tools							
				TBM6PCR-LI TBM6UNICR-LI TBM62PCR-LI TBM62C-LI	TBM5 TBM5S	TBM6,TBM6S Two dies are needed, upper and lower	TBM8 TBM8S	TBM14M TBM14MC TBM14CR-LI *TBM15I *TBM15CR-LI				
Code cable Al	Bolt size (in.)	One-hole - long barrel	Two-holes - long barrel	Dies					Colour code			
8 AWG	1/4	60102-TB	—	6TON24SS	13454	13475/13477	13461	15522SS	Blue			
6 AWG	1/4	60107-TB	—	6TON29SS		13472/13476		15527SS	Grey			
4 AWG	1/4	60112-TB	—	6TON37SS	13455	13474/13477	13462	15513SS	Green			
	5/16	60113-TB	—									
2 AWG	3/8	60114-TB	—	6TON42SS	13455	13475/13477	13462	15508SS	Pink			
	1/4	60116-TB	—									
	5/16	60117-TB	—									
	3/8	60118-TB	—									
	1/2	—	—	—	—	—	—	—	—			
1 AWG	3/8	60124	—	6TON45SS	13457	13474/13477	13464	15526SS	Gold			
	5/16	60129	—	—		—		—				
1/0 AWG	3/8	60130	60230	6TON50SS	13457	13474/13477	13464	15530SS	Tan			
	1/2	60132	—	—		—		—				
2/0 AWG	3/8	60136	—	6TON54SS	13457	13475/13477	13464	15511SS	Olive			
	1/2	60138	60238	—		—		—				
3/0 AWG	3/8	60142	60242	6TON60SS	13457	13473/13476	13464	15532SS	Ruby			
	1/2	60144	60244	—		—		—				
4/0 AWG	3/8	60148	60248	6TON66SS	13458	13473/13476	13465	15534SS	White			
	1/2	60150	60250	—		—		—				
250 kcmil	3/8	—	60254	6TON71SS	13458	13472/13476	13466	15514SS	Red			
	1/2	60156	60256	—		—		—				
300 kcmil	3/8	60160	60260	6TON76SS	13458	13472/13476	13467	15512SS	Blue			
	1/2	60162	60262	—		—		—				
350 kcmil	3/8	—	60265	6TON87SS	13458	13478/13478	13468	15506SS	Brown			
	1/2	60165	60267	—		—		—				
400 kcmil	3/8	—	60268	6TON94SS	13458	—	—	—	Green			
	5/8	60168	60269	—				—	—			
500 kcmil	3/8	—	—	—	13458	—	—	15505SS	Pink			
	1/2	60171	60271					—	—	—		
600 kcmil	5/8	60172	60273	—	13458	—	—	15515SS	Black			
	3/8	—	60274					—	—	—		
750 kcmil	1/2	—	60275	—	13458	—	—	15504SS	Yellow			
	1/2	—	—							—	—	—
	1/2	—	60278							—	—	—
	1/2	—	—							—	—	—
	5/8	60178	—	—	—	—	—	—	—			

* Always use the 15500-TB adapter with the TBM15CRLI tool.

Copper cable lugs



Tools									
				TBM5 TBM5S	TBM6,TBM6S Two dies are needed, upper and lower	TBM8 TBM8S	TBM6PCR-LI TBM6UNICR-LI TBM62PCR-LI TBM62CR-LI	TBM14M TBM14MC TBM14CR-LI *TBM15CR-LI *TBM15I	
Code Copper	Bolt size (in.)	One-hole	Two-holes	One-hole - long barrel	Dies				Colour code
8 AWG	#10	54104	54204	54929BE	13475/13477	13461	6TON21SS	15520SS	Red 21
	1/4	54130	542040410	54930BE					
	5/16	54131	—	54930BE05					
	3/8	54132	256-30695-251	54930BE06					
6 AWG	1/2	—	—	—	13454	13461	6TON24SS	15522SS	Blue 24
	#10	54134	256-30695-1183	54904BE					
	1/4	54105	54205	54905BE					
	5/16	54135	—	54905BE05					
4 AWG	3/8	54136	256-30695-253	54905BE06	13472/13476	13461	6TON29SS	15527SS	Grey 29
	1/2	256-30695-422	—	—					
	#10	54138	—	54908BE					
	1/4	54106	54206	54906BE					
2 AWG	5/16	54139	256-30695-1184	—	13474/13477	13462	6TON33SS	15528SS	Brown 33
	3/8	54140	256-30695-255	—					
	1/2	256-30695-264	—	—					
	1/4	54107	54207	54910BE04					
1 AWG	5/16	54142TB	—	54910BE05	13475/13477	13462	6TON37SS	15513SS	Green 37
	3/8	54143TB	256-30695-257	54910BE					
	1/2	54145TB	256-30695-1049	54915BE					
	1/4	54108	256-30695-329	54947BE04					
1/0 AWG	5/16	54147	54255	54947BE	13475/13477	13462	6TON42SS	15508SS	Pink 42
	3/8	54148	256-30695-1236	54947BE06					
	1/2	54150	—	54947BE08					
	1/4	54152-TB	—	—					
2/0 AWG	5/16	54153TB	54255	54949BE	13474/13477	13463	6TON45SS	15526SS	Black 45
	3/8	54109	54209	54909BE					
	1/2	54155TB	256-30695-886	54950BE					
	5/16	54158	—	—					
3/0 AWG	3/8	54110	54210	54910BE	13475/13477	13463	6TON50SS	15530SS	Orange 50
	1/2	54160	54260	54951BE					
	5/16	54163-TB	—	—					
	3/8	54111	54211	54965BE06					
4/0 AWG	1/2	54165TB	54265	54965BE	13473/13476	13465	6TON54SS	15511SS	Purple 54
	5/16	54168	—	—					
	3/8	54112	54212	54970BE06					
	1/2	54170	54270	256-30695-1253					
250 kcmil	3/8	54174	54213	—	13472/13476	13466	6TON62SS	15510SS	Yellow 62
300 kcmil	1/2	54113	54275	54913BE					
	1/2	54114	54280	54914BE					
	5/8	54181	54280-1028	—					
350 kcmil	1/2	54115	54282	54915BE	13468/13468	13468	6TON71SS	15514SS	Red 71H
400 kcmil	5/8	54183	54282-1028	—					
	1/2	54116	54283-0828	54916BE					
	5/8	54185	54283-1028	54917BE					
500 kcmil	1/2	54118	54286	54918BE	13468/13468	13468	6TON76SS	15512SS	Blue 76H
600 kcmil	5/8	54187	54286-1028	54919BE					
	1/2	—	54289	54921BE					
	5/8	54120	54289-1028	54920BE					
700 kcmil	5/8	54122-TB	—	—	13468/13468	13468	6TON87SS	15506SS	Brown 87H
750 kcmil	1/2	—	54223	54922BE					
	5/8	54123TB	54223-1028	54923BE					
800 kcmil	1/2	—	54224	—					
900 kcmil	5/8	54124-TB	54224-1028	—					
	1/2	256-30695-843	54226	—					
1000 kcmil	5/8	54126	54226-1028	54926BE					
1000 kcmil	1/2	—	54228	—					
	5/8	54128	256-30695-844	54928BE					

* Always use the 15500-TB adapter with the TBM15CRLI tool.

Compression lugs and splices for copper cables

Lugs		Compression splices		Tools				
						TBM6PCR-LI TBM6UNICR-LI TBM62PCR-LI TBM62CR-LI		TBM14M TBM14MC TBM14CR-LI *TBM15CR-LI *TBM15LI
Code Copper	Bolt size (in.)	Two-holes - long barrel	Standard	Long	Thick-walled heat shrink tubing of HS type	Dies		Colour code
8 AWG	#10	—	54504	54804	HS16-12	6TON21SS	15520SS	Red 21
	1/4	54851BE						
	5/16	—						
	3/8	256-30695-1157						
6 AWG	1/2	—	54505	54805	HS16-12	6TON24SS	15522SS	Blue 24
	#10	—						
	1/4	54852BE						
	5/16	—						
4 AWG	3/8	256-30695-1158	54506	54806	HS12-6	6TON29SS	15527SS	Grey 29
	1/2	256-30695-868						
	#10	—						
	1/4	54854BE						
2 AWG	5/16	—	54507	54807	HS12-6	6TON33SS	15528SS	Brown 33
	3/8	256-30695-1159						
	1/2	256-30695-733						
	1/4	54855BE						
1 AWG	5/16	54856BE	54508	54808	HS12-6L HS6-1	6TON37SS	15513SS	Green 37
	3/8	54810BE						
	1/2	54811BE						
	1/4	54812BE						
1/0 AWG	5/16	54860BE	54509	54809	HS6-1L HS6-1-4	6TON42SS	15508SS	Pink 42
	3/8	256-30695-1162						
	1/2	256-30695-593						
	5/16	—						
2/0 AWG	3/8	256-30695-1116	54510	54810	HS6-1L HS6-1-4	6TON45SS	15526SS	Black 45
	1/2	54862BE						
	5/16	—						
	3/8	54816BE						
3/0 AWG	1/2	54864BE	54511	54811	HS6-1L HS6-1-4	6TON50SS	15530SS	Orange 50
	5/16	—						
	3/8	54818BE						
	1/2	54866BE						
4/0 AWG	3/8	54818BE	54512	54812	HS6-1L HS6-1-4	6TON54SS	15511SS	Purple 54
	1/2	54866BE						
	5/16	—						
	3/8	—						
250 kcmil	1/2	54868BE	54513	54813	HS4-30L HS4-30-4	6TON62SS	15510SS	Yellow 62
	5/8	—						
	1/2	54870BE						
	5/8	—						
300 kcmil	1/2	54872BE	54514	54814	HS4-30L HS4-30-4	6TON66SS	15534SS	White 66H
	5/8	—						
	1/2	54874BE						
	5/8	—						
350 kcmil	1/2	54876BE	54515	54815	HS4-30L HS4-30-4	6TON71SS	15514SS	Red 71H
	5/8	—						
	1/2	54874BE						
	5/8	—						
400 kcmil	1/2	54876BE	54516	54816	HS4-30L HS4-30-4	6TON76SS	15512SS	Blue 76H
	5/8	—						
	1/2	54878BE						
	5/8	—						
500 kcmil	1/2	54878BE	54518	54818	HS4-30L HS4-30-4	6TON87SS	15506SS	Brown 87H
	5/8	—						
	1/2	54878BE						
	5/8	—						
600 kcmil	1/2	54879BE	54520	54820	HS40-400L HS40-400-4	—	15536SS	Green 94H
	5/8	—						
	1/2	54879BE						
	5/8	—						
700 kcmil	1/2	54880BE	54522TB	—	HS40-400L HS40-400-4	—	15505SS	Pink 99H
	5/8	—						
	1/2	54880BE						
	5/8	—						
750 kcmil	1/2	—	54523-TB	54823	HS40-400L HS40-400-4	—	15515SS	Black 106H
	5/8	—						
	1/2	—						
	5/8	—						
800 kcmil	1/2	—	—	—	—	—	—	—
	5/8	—						
	1/2	—						
	5/8	—						
900 kcmil	1/2	58826BE	—	—	—	—	15504SS	Yellow 115H
	5/8	—						
	1/2	—						
	5/8	—						
1000 kcmil	1/2	54882BE	54528	54828	HS500-1000	—	15603	125H
	5/8	—						
	1/2	—						
	5/8	—						




* Always use the 15500-TB adapter with the TBM15CRLI tool.

Mechanical connectors - Compression wire joints for copper conductors

		Tools					
		TBM8 TBM8S		TBM5 TBM5S	TBM6 TBM6S		
Circular mil area							
Min.	Max.	Dies		Upper	Lower	Colour code	Cat. no.
19.59	27.29	13461	13454	13475	13477	Blue	54610
31.14	43.40			13472	13476	Grey	54615
49.53	65.56			13474	13477	Brown	54620
66.04	87.13	13462	13455	13474	13477	Green	54625-TB
83.48	99.99			13475	13477	Pink	54630
99.06	124.22			13474	13477	Black	54635
125.22	166.12			13474	13477	Orange	54640
166.96	193.63	13463	13456	13475	13477	Purple	54645-TB
189.19	244.02			13473	13476	Yellow	54650

AWG Size	Circular Mil Area
#14	4.107
#12	6.530
#10	10.380
#8	16.510
#6	26.250
#4	41.740
#3	52.633
#2	66.370
#1	83.690
#1/0	105.500
#2/0	133.100
#3/0	167.800
#4/0	211.600

Types of installations

Pigtail

Two-way connector


Three-way connector

Mechanical connectors

Mechanical connectors for 600V 90°C - Certified by CSA - Type AMT

	Wire range	No. of ports	Length (in.)	Width (in.)	Height (in.)	Bolt size	Cat. no.
	6 Str. to 3/0 Str.	2	1.89	1.58	1.86	3/16	AMTS3062


Diagrams



Mechanical connectors for 600V 90°C - Certified by CSA - Type AMT

	Wire range	No. of ports	Length (in.)	Width (in.)	Height (in.)	Bolt size	Cat. no.
	6 Str. to 250 Kcmil	1	3.96	1.19	2.17	5/16	AMTSR250

Diagram




PVC Insulated street and highway lighting mechanical connectors - BY Series

	Wire range	No. of ports	Cat. no.
	#14 AWG to 2/0 Str.	3	BY320

Mechanical insulation piercing connectors / copper-to-copper / copper-to-aluminum / aluminum-to-aluminum - Type IPC

	Conductor range Al / Cu		Length (in.)	Width (in.)	Height (in.)	Voltage applications	Cat. no.
	Main	Tap					
	1/0 AWG to 8 AWG 50 to 6 Kcmil	2AWG to 8 AWG 35 to 6 Kcmil	1-17/32	2-9/16	2	600 V	IPC1102
	350Kcmil to 4/0AWG 185 to 95 Kcmil	4/0AWG to 1/0 AWG 95 to 6 Kcmil	2-5/8	2-3/4	3	300 V	IPC3541

Diagram



Grounding system - Compression connectors

Compression ground tap connectors IEEE - Figure 6



Application		Manual hydraulic crimp Tool (TBM14M)	Hydraulic tools (13100A) *(TBM15I)	Battery tools (TBM14CR-LI) *(TBM15CR-LI)	Cat. no.
Main	Tap				
1/0 Str.- 250 kcmil to 1/2-5/8 in. rod	#4 Sol.- #2 Str.	Die #15G86A with (1) compression			54855
	1/0 Str. - 2/0 Str.				54860
	3/0 Str.- 250 kcmil				54865CK
#6 Sol.-#2 Str.	#6 Sol.-#2 Str.	Die #15501A with (1) compression			54875
250 kcmil – 500 kcmil to 5/8-3/4 in. rod	#4 Sol.-#2 Str.	Die #15G126R with (1) compression			54885
	1/0 Str.-2/0 Str.				54890
	3/0 Str.-250 kcmil				54895
	350 kcmil-500 kcmil	Die #15G121R with (3) compressions			54900

* Always use the 15500-TB adapter with the TBM15CRLI tool.

* Always make a crimping connection using a grounding rod and the 15508 die with 14 and 15-ton tools

Compression ground rod tap connectors IEEE - Figure 8

*Ground rod (in.)	Cable range	Manual hydraulic crimp tool (TBM14M)	Hydraulic tools (13100A) *(TBM15I)	Battery tools (TBM14CR-LI) *(TBM15CR-LI)	Cat. no.
1/2	2 AWG – 2/0 AWG	Die #15G121R with (2) compressions			GR12-202
5/8					GR58-202
3/4					GR34-202
1					GR1-202
1/2	3/0 AWG – 250 kcmil				GR12-40250
5/8					GR58-40250
3/4					GR34-40250
1					GR1-40250
5/8	300–500 kcmil				GR58-300500
3/4					GR34-300500
1					GR1-300500*

* Always use the 15500-TB adapter with the TBM15CRLI tool.

* Always make a crimping connection using a grounding rod and the 15508 die with 14 and 15-ton tools

Grid tap connectors IEEE - Type C



Application		Crimp tool (TBM14M)	Hydraulic tools (13100A) *(TBM15I)	Battery tools (TBM14CR-LI) *(TBM15CR-LI)	Cat. no.
Main	Tap				
#6 Sol.- #2 Str.	#6 Sol. - #2 Str.	Die #HBKC with (1) compression			CTP22
#1 Str.- 2/0 Str.	#6 Sol. - #2 Str.				CTP202
#1 Str.- 2/0 Str.	#1 Str. - 2/0 Str.				CTP2020
3/0 Str. - 250 kcmil	#6 Sol. - 2/0 AWG	Die #15G86R with (1) compression			CTP25020
3/0 Str. - 250 kcmil	3/0 Str.- 250 kcmil				CTP250250
300 - 500 kcmil	#6 Sol. - 2/0 AWG	Die #15G121R with (2) compressions			CTP50020
300 - 500 kcmil	3/0 Str. - 250 kcmil				CTP500250
300 - 500 kcmil	300 - 500 kcmil				CTP500500

* Always use the 15500-TB adapter with the TBM15CRLI tool.

Grounding system - Compression connectors

Compression grid and ground rod connectors IEEE - Figure 6

	Cable to cable		Element A to ground rod (in.)	*Element B to rebar (in.)	Manual hydraulic tool : TBM14M , Hydraulic tools : 13100A , *TBM15I , Battery tools : TBM14CR-LI , *TBM15CR-LI		Cat. no.
	Element A	Element B			Element A	Element B	
	#6 Sol. - #2 Str.	#6 Sol. - #2 Str.	—	—	Die #15501A with (1) compression	Die #15501A with (1) compression	54855L
	#1 Str. - 250 kcmil	#6 Sol. - #2 Str.	1/2 – 5/8	#3 rebar 3/8, thru 1/2 in. #4 rebar	Die #15G86R with (1) compression	Die #15G86R with (1) compression	54865L
	#2 Str. - 250 kcmil	#2 Str. - 250 kcmil				Die #15G86R with (1) compression	54875L
	250 kcmil - 500 kcmil	#6 Sol. - #2 Str.	5/8 – 3/4	#5 rebar 5/8, thru 3/4 in. #6 rebar	Die #15501A with (1) compression	Die #15G126R with (1) compression	54885L
		#2 Str. - 250 kcmil			Die #15G86R with (1) compression		54895L
		250 kcmil - 500 kcmil			Die #15G121R with (3) compressions	Die #15G121R with (3) compressions	54900L

* Always use the 15500-TB adapter with the TBM15CR-LI tool.

* Always make a crimping connection using a grounding rod and the 15508 die with 14 and 15-ton tools

Compression ground rod to grid connectors IEEE - Figures 6 to 8

	Ground rod in. (mm)	Cable range	Manual hydraulic tool : TBM14M Hydraulic tools : 13100A , *TBM15I Battery tools : TBM14CR-LI , * TBM15CR-LI		Cat. no.
			Element A	Element B	
	1/2 (12.7)	2 AWG–250 kcmil	Die 15G121R with (2) compressions	Die 15G121R	54855LR12*
		250 kcmil–500 kcmil		Die 15G126R with (1) compression	54885LR12*
	5/8 (16.0)	2 AWG–250 kcmil		Die 15G86R with (1) compression	54865LR58*
		250 kcmil–500 kcmil		Die 15G126R with (1) compression	54895LR58*
	3/4 (19.1)	2 AWG–250 kcmil		Die 15G86R with (1) compression	54875LR34*
		250 kcmil–500 kcmil		Die 15G126R with (1) compression	54900LR34*
	1 (25.4)	2 AWG–250 kcmil		Die 15G86R with (1) compression	54910LR100
		250 kcmil–500 kcmil		Die 15G126R with (1) compression	54920LR100

* Always use the 15500-TB adapter with the TBM15CR-LI tool.

* Always make a crimping connection using a grounding rod and the 15508 die with 14 and 15-ton tools

Structural Grounding Studs -
Type TBGS

	Ground rod in. (mm)	Cat. no.
	1/2 (12.7)	54855LR12*
		54885LR12*
	5/8 (16.0)	54865LR58*
		54895LR58*
	3/4 (19.1)	54875LR34*
		54900LR34*
	1 (25.4)	54910LR100
		54920LR100

Hex compression intimately bonds directly to copper-clad ground rod IEEE -
Figure 8

Application		Manual hydraulic tool : TBM14M , Hydraulic tools : 13100A , TBM15I , Battery tools : TBM14CR-LI , TBM15CR-LI	
Cable range	Copper-coated grounding rod (in.)		Cat. no.
One cable: 3/0 to #6 Two cables: #2 to #6	2 AWG– 250 kcmil	Die #15506SS with (2) compressions	GR58-406

* Always use the 15500-TB adapter with the TBM15CR-LI tool.

Grounding system - Compression connectors

Copper compression tap connectors - Type H



Application		Mechanical tool and dies (OD58)	Hydraulic tool and dies (JB12B)	Hydraulic tool and dies (TBM15)	Battery tool TBM15CR-LI	Cat. no.
Main A	Tap B					
ACSR : 4,6 AWG str. : 6 AWG	Sol. : 4,6,8 AWG str. : 8 AWG	BY49 , BY45, BY31	HBKT	HBKT	HBKT	CF44-1
ACSR: 2, 4 AWG str. : 4 AWG	Sol. : 2,4 AWG str. : 4 AWG	BY47	—			CF22-1
Str. : 1/0,1,2 AWG	Sol. : 2,4 ,6 AWG str. : 4 AWG	—	HO	HO, 15501-A	HO, 15501-A	CF102-1
Str. : 1/0,1,2 AWG	Str. : 1,2,1/0 AWG	—	HO			CF1010-1
Str. : 1/0,2/0 AWG	Str. : 1,2, 1/0,2/0 AWG	—	HBKT,HBKC	HBKT,HBKC	HBKT,HBKC	CF202-1
Str. : 1/0,2/0 AWG	Str. : 1,2, 1/0,2/0 AWG	—	HBKT,HBKC			CF2020-1
Str. : 2/0,3/0,4/0 AWG	Sol. : 2,4 AWG TOR : 4 AWG	—	HD,15502	HD,15502	HD,15502	CF402-1
Str. : 2/0,3/0,4/0 AWG	Str. : 1,2,1/0 AWG	—	HD,15502			CF4010-1
Str. : 2/0,3/0,4/0 AWG	Str. : 2/0,3/0,4/0 AWG	—	HD,15502			CF4040-1

Tower ground clamps - Type GTC



Conductor range		Channel thickness (in.)	Cat. no.
Max.	Min.		
2/0 str.	4 sol.		GTC13
250 Kcmil	2/0 str.		GTC14
2/0 str.	4 sol.	1/4	GTC23
250 Kcmil	2/0 str.		GTC24

Ground rod clamps - Type JAB



Wire range		Nominal rod dia. (in.)	Cat. no.
Max.	Min.		
2 AWG	10 AWG	1/2	*JAB12
1/0 AWG	8 AWG	5/8	JAB58H
1/0 AWG	8 AWG	3/4	JAB34H
3/0 AWG	8 AWG	3/4 and 5/8	JAB34C

* CSA not applicable.

Wide range tower ground clamp - Type CTG



Wire range		Depth (in.)	Cat. no.
Max.	Min.		
250 Kcmil	2 sol.	1.13	CTG250

Grounding system - Compression connectors

C-Taps



		Hydraulic and battery tools (TBM6H) (TBM6PCR-LI) (TBM6PCR-LI) (TBM62CR-LI) (TBM62PCR-LI) (TBM62UNICRLI)							Battery tools (TBM12PCR-LI) (TBM14CR-LI) *(TBM15CR-LI)		Thick-walled heat-shrinkable tube of HS type	Cat. no.	
		Manual tools (TBM5/5S)	Manual tools (TBM6/6S)	Manual tools (TBM8/5S)	Battery tool (BPLT62BSCR)								
Application									Colour code				
Main	Branch	Dies											
6 AWG	10,12 AWG	TBM45S TBM45BB TBM41E	13454	13472/ 13476	13461	6TON29SS	TBM6229	15527-CK	Grey	HS12-6	54715		
8 AWG 4 or 5 AWG	8,10, 12 AWG					6TON33SS	TBM6233	15528SS	Brown			HS6-1	
6 AWG	6 , 8 AWG					6TON37SS	TBM6237	15513-CK	Green				54720
3 AWG	6,8,10 and 12***AWG					6TON42SS	TBM6242	15508SS	Pink				
4 or 5 AWG	6, 5 AWG	—	13455	13474/ 13477	13462	6TON45SS	TBM6245	15526SS	Black	54730			
2 AWG	6,8,,10 and AWG	—											
3 AWG	5 AWG	—											
4 AWG	3 AWG	—											
1 AWG	4,5,6,8,10 and 12 AWG	—	13455	13474/ 13477	13462	6TON50SS	TBM6250	15530SS	Orange	HS4-30	54735		
2 AWG	4,5 AWG	—											
3 AWG	3,4 AWG	—											
1/0 AWG	4,5,6,8,10 and 12 AWG	—											
1 AWG	3 ,4 AWG	—	13456	13473/ 13478	13463	6TON54SS	TBM6254	15511SS	Purple	54740	54745		
2 AWG	2,3 AWG	—											
2/0 AWG	3,4,5,6,8,10 and 12 AWG	—											
1/0 AWG	2,3 AWG	—											
1 AWG	1,3 AWG	—	13456	13473/ 13478	13463	6TON62SS	TBM6262	15510-CK	Yellow	54750	54750		
3/0 AWG	2,3,4,5, 6,8,10 and 12 AWG	—											
2/0 AWG	1,2 AWG	—											
1/0 AWG	1/0,1 AWG	—											

Type H and C



Aluminum Compression H-Tap
63110
63118
63125
63140

Grounding system - Compression connectors

C-Taps

Application		Manual and hydraulic tools TBM14M	Battery tools TBM12PCR-LI TBM14CR-LI *TBM15CR-LI	Hydraulic and battery tools TBM6H TBM6PCR-LI TBM62CR-LI TBM62PCR-LI TBM6UNICRLI	Hydraulic tools TBM12	Hydraulic tools 13100A	Hydraulic tools *TBM15I	No. of crimps	Die code	Colour code	Cat. no.
Main	Branch	Dies									
1 AWG	1 AWG	—	—	—	—	—	—			—	
1/0 AWG	1/0 - 2 AWG	15512SS	15512SS	6TON76SS	TBM12D-4	15512SS	*15512SS	1	76	Blue	54755
2/0 AWG	2/0 - 4 AWG								76H		
3/0 AWG	1/0 - 6 AWG								76		
4/0 AWG	1 - 8 AWG										
2/0 AWG	2/0 - 1 AWG	15506SS	15506SS	6TON87SS	TBM12D-3	15512SS	*15506SS	2	87H	Brown	54760
3/0 AWG	3/0 - 3 AWG								87H		
4/0 AWG	4/0 - 4 AWG								87H		
250 AWG	1/0 - 8 AWG								87H		
2/0 AWG	2/0 - 1 AWG	15505SS	15505SS	—	TBM12D-2	15505SS	*15505SS	2	99H	Pink	54765
3/0 AWG	3/0 - 2 AWG								99H		
4/0 AWG	4/0 - 4 AWG								99H		
250 AWG	3/0 - 6 AWG								99H		
300 AWG	2/0 - 8 AWG	15515SS	15515-CK	—	TBM12D-2	15515SS	*15515SS	2	106H	Black	54770
4/0 AWG	4/0 - 2/0 AWG								106H		
250 AWG	250 - 1 AWG								106H		
300 AWG	4/0 - 4 AWG								106H		
350AWG	3/0 - 6 AWG	15504SS	15504SS	—	TBM12D-1	15504SS	*15504SS	2	115H	Yellow	54775
250 AWG	250 AWG								115H		
300 AWG	300 - 1/0 AWG								115H		
350AWG	350 - 1/0 AWG								115H		
400 AWG	300 - 2 AWG								115H		
450 AWG	250 - 4 AWG								115H		
500 AWG	250 - 6 AWG								115H		

Interlocking insulating covers for compression taps - Type H and C

	For H-taps		For C-taps		Cat. no.
	H-taps aluminum	H-taps copper	Type C	Colour code	
	—	—	54755	Blue	HTC40
	—	—	54760	Brown	
63148		CHT50010 5	54765	Pink	HTC500
63160		CHT50040-4	54770	Black	
		CHT75010-3 CHT750350-2	54775	Yellow	

Grounding system - Compression connectors

Clamps - Type GUV

	Conductor range (Cu)		Nominal rod size (in.)		IPS pipe size (in.)		Cat. no.
	Max.	Min.	Max.	Min.	Max.	Min.	
	250kcmil	2/0 AWG	1	7/8	3/4	1/2	GUV7825
	2/0 AWG	4 AWG	1-1/2	1-3/8	1-1/4		GUV13821
	4 AWG	8 AWG					
	250kcmil	2/0 AWG	1-7/8	1-5/8	1-1/2		GUV15825
	250kcmil	2/0 AWG	2-3/8	2	2		GUV2025
	2/0 AWG	4 AWG					GUV2021
	250kcmil	2/0 AWG	3-1/2	3	3		GUV3025
	2/0 AWG	4 AWG					GUV3021
	2/0 AWG	4 AWG	3/4	5/8	3/8		GUV5821
	4 AWG	8 AWG					

Waterpipe ground clamps

	Conductor range (Cu)		Water pipe size (in.)		Cat. no.
	Max.	Min.	Max.	Min.	
	4/0 AWG	4 AWG	1	1/2	3902BU
			2	1 1/4	3903BU
			3 1/2	2 1/2	3904BU
			5	4	3905BU
			6	—	3906BU
			8	—	3907BU

Copper Lay-In Lug - Type DB

	Conductor range (Cu)		Sizes of studs		Cat. no.
	Max.	Min.	(in.)		
	4 AWG	14 AWG	0.22		CULL4-14
	4 AWG	14 AWG	0.22	CULL4-14TP (Tinned connectors)	

High Strength Split-Bolt Connector - Type H

	Main cable and branch cable of the same gauge		Cat. no.
	10 Str.-12 Sol.	9H	
	8 Str.-10 Sol.	8H	
	6 Sol.-8 Sol.	6H	
	4 Sol.-8 Sol.	4H	
	3 Sol.-8 Sol.	3H	
	2 Sol.-6 Sol.	2H	
	2 Str.-6 Sol.	1H	
	1/0 Str.-4 Sol.	10H	
	2/0 Str.-2 Sol.	20H	
	250 kcmil-1 Str.	40H	
	350 kcmil-250 kcmil	350M	
	500 kcmil-400 kcmil	500M	
	750 kcmil-600 kcmil	750M	
	1000 kcmil-800 kcmil	1000M	

Split-bolt connectors for connections Cu to Cu - Type H

	Main cable and branch cable of the same gauge		Cat. no.
	1 Str. to 8 Sol.	1HPS	
	6 Str. to 12 Sol.	6HPS	

Mechanical connectors for conductors - Al and Cu - Type ADR

	Conductor range		Bolt size	Cat. no.
	max.	min.		
	6 Str.	14 AWG	1/4	ADR6
	2 Str.	14 AWG		ADR2
	1/0 Str.	14 AWG		ADR11
	2/0 Str.	14 AWG		ADR21
	250 kcmil	6 Str.	5/16	ADR25
	300 kcmil	6 Str.		ADR30
	350 kcmil	6 Str.		ADR35
	500 Kcmil	4 Str.	3/8	ADR50
	600 kcmil	2 Str.		ADR60
	800 kcmil	300 kcmil		ADR80
	1000 kcmil	500 kcmil		ADR99

Mechanical connectors for conductors - Al and Cu - Type ADR

	Conductor range		Bolt size	Cat. no.
	max.	min.		
	1/0 Str.	14 AWG	1/4	ADR11-21
	2/0 Str.	14 AWG		ADR21-21
	250 Kcmil	6 Str.	3/8	ADR25-21
	350 Kcmil	6 Str.	1/2	ADR35-21
	600 Kcmil	2 Str.		ADR60-21
	800 Kcmil	300 Kcmil	5/8	ADR80-21
	1000 Kcmil	500 Kcmil		ADR99-21

Grounding system - Compression connectors

Service post connectors, short stud application, copper to copper - Type DS



Conductor range stranded AWG (mm²)		Single conductor	Double conductor
max.	min.	Cat. no.	Cat. no.
8 AWG/6 mm²	12 AWG/4 mm²	SP0SS	SP0DS
7 AWG/10 mm²	10 AWG/6 mm²	SP1SS	SP1DS
5 AWG/16 mm²	10 AWG/6 mm²	SP2SS	SP2DS
3 AWG/25 mm²	10 AWG/6 mm²	SP3SS	SP3DS
1 AWG/35 mm²	8 AWG/6 mm²	SP4SS	SP4DS
1/0 AWG/50 mm²	2 AWG/35 mm²	SP5SS	SP5DS
2/0 AWG/70 mm²	2 AWG/35 mm²	SP6SS	SP6DS
4/0 AWG/95 mm²	1 AWG/35 mm²	SP8SS	SP8DS
350 AWG/150 mm²	1/0 AWG/70 mm²	SP9SS	SP9DS
500 AWG/240 mm²	3/0 AWG/95 mm²	SP10SS	SP10DS

Service post connectors, long stud application, copper to copper - Type SP



Conductor range stranded AWG (mm²)		Single conductor	Double conductor
max.	min.	Cat. no.	Cat. no.
8 AWG/6 mm²	12 AWG/4 mm²	SP0SL	SP0DL
7 AWG/10 mm²	10 AWG/6 mm²	SP1SL	SP1DL
5 AWG/16 mm²	10 AWG/6 mm²	SP2SL	SP2DL
3 AWG/25 mm²	10 AWG/6 mm²	SP3SL	SP3DL
1 AWG/35 mm²	8 AWG/6 mm²	SP4SL	SP4DL
1/0 AWG/50 mm²	2 AWG/35 mm²	SP5SL	SP5DL
2/0 AWG/70 mm²	2 AWG/35 mm²	SP6SL	SP6DL
4/0 AWG/95 mm²	1 AWG/35 mm²	SP8SL	SP8DL
350 AWG/150 mm²	1/0 AWG/70 mm²	SP9SL	SP9DL
500 AWG/240 mm²	3/0 AWG/95 mm²	SP10SL	SP10DL

Copper single conductor, one-hole mount - Type BTC



Conductor range		Bolt size	Cat. no.
max.	min.		
10 AWG	14 AWG	5/32	BTC1014*
6 Str.	14 AWG	13/64	BTC0614
2 Str.	8 Str.	17/64	BTC0208
1/0 Str.	2 Str.		BTC1102
3/0 Str.	4 Str.	13/32	BTC3104
4/0 Str.	2 Str.	11/32	BTC4102
350 kcmil	1/0 Str.	13/32	BTC3511
500 kcmil	1/0 Str.		BTC5011
1000 kcmil	600 kcmil	17/32	BTC9960

* CSA not applicable.

Flexible braids



Nominal range (A)	Circular mils	Descriptions	Cat. no.
190 -1000 A	76,800	12-inch flat flexible braid with a 7/16-inch bolt hole	FBD12-1
190 - 1000 A		18-inch flat flexible braid with a 7/16-inch bolt hole	FBD18-1
400 - 2000 A	153,600	12-inch flat flexible braid with a 7/16-inch bolt hole	FB2D12
400 - 2000 A		18-inch flat flexible braid with a 7/16-inch bolt hole	FB2D18

EZ-CK SS DIEKIT



Die Cat. no.	Copper	Aluminum	Colour code
15528SS	2 AWG	—	Brown
15513SS	1 AWG	4 AWG	Green
15508SS	1/0 AWG	2 AWG	Pink
15526SS	2/0 AWG	1 AWG (Gold)	Black
15530SS	3/0 AWG	1/0 AWG (Tan)	Orange
15511SS	4/0 AWG	2/0 AWG (Olive)	Purple
15510SS	250 kcmil	—	Yellow
15534SS	300 kcmil	4/0 AWG	White
15514SS	350 kcmil	250 kcmil	Red
15506SS	500 kcmil	350 kcmil	Brown
15515SS	750 kcmil	650 kcmil	Black
15G121R	250-500 kcmil • #2-250 kcmil	—	—
15G86R	#2-250 kcmil	—	—
15501A	#6 - #2 AWG	—	—
15G126R	250-500 kcmil	—	—

Tools and dies

The ABB compression method is used with harmonized tools and dies to form the connector and conductor into a homogeneous mass, ensuring an optimal connection between the two.


The ABB installation method for compression connectors on power cables allows for highly reliable electrical wiring. This method enables electricians to perform simple and quick installations. The advantage, of course, is a high-quality connection at a low installation cost.

A complete range for a solid and homogeneous connection

ABB offers a complete range of CEI & UL/CSA certified compression lugs in metric dimensions (Color-Keyed and Spec-Kon) as well as imperial/American Wire Gauge (AWG) sizes (Color-Keyed). All systems use compression tools with corresponding dies to form the connector and wire, providing an optimal electrical connection between the lug and the conductor.



TBM45S crimp tool



Creates diamond-style crimp

- Wide range of #8 to #2 for copper lugs and #10 to #6 for aluminum lugs
- Each die has die code embossing
- Shure Stake mechanism ensures a properly completed crimp each time
- Colour-coded die wheel rotates into position for proper die nest adjustment
- Also installs up to green colour-coded C-Taps and MD2 series motor disconnects
- Requires two crimps per connector



Cat no.	Description	Pkg. qty.
TBM45S	Crimp tool with Shure Stake mechanism for #8–#2 copper and #10–#6 aluminum lugs	1



Crimp-Assist™ foot provides stability when work surface leverage is needed to crimp larger connectors.


Cat no.	Conductor size					
	#10 Red	#8 Red	#6 Blue	#4 Grey	#2 Brown	#1 Green
Copper connectors						
One hole, short	–	54104	54134	54138	54107	–
One hole, short	–	54130	54105	54106	54142	–
One hole, short	–	54131	54135	54139	54143	–
One hole, short	–	54132	54136	54140	54145	–
One hole, short	–	54104	54205	54206	54207	–
Splice, short	–	54504	54505	54506	54507	–
One hole, long	–	54930BE	54905BE	54906BE	54942BE	–
Two hole, long	–	54850BE	54852BE	54854BE	54856BE	–
Splice, long	–	54804	54805	54806	54807	–
Cable joints	–	–	54610	54615	54620	–
Narrow tongue	–	–	–	55112	55116	–
C-taps	–	54705	54710	54715	54720	54725
Motor disconnects	–	MD8 series	MD6 series	MD4 series	MD2 series	–
Aluminum connectors						
Bi-pins	–	61905A	61910A	–	–	–
Equipment lugs	–	61102	61107	–	–	–

TBM6 and TBM6S* crimp tools



- Wide range of #8 thru 500 kcmil for copper lugs, splices and taps and #10 thru 350 kcmil for aluminum lugs and splices
- Also install 63105 through 63140 orange, green and blue H-Taps
- Shure Stake mechanism ensures a properly completed crimp each time (only in TBM6S)
- Complete with plastic carrying case and wire brush
- No dies included

Die type



Creates diamond-style crimp



Cat no.	Colour code	Al	Cu	Upper die Cat. no.	Lower die Cat. no.	Pkg. qty.
TBM6 or TBM6S*	Red	10	8	13475	13477	1
	Blue	8	6	13475	13477	1
	Grey	6	4	13472	13476	1
	Brown	–	2	13474	13477	1
	Green	4	1	13474	13477	1
	Pink	2	1/0	13475	13477	1
	Black	–	2/0	13474	13477	1
	Orange	–	3/0	13474	13477	1
	Violet	–	4/0	13475	13477	1
	Yellow	–	250	13473	13476	1
	Or	1	–	13474	13477	1
	Tan	1/0	–	13474	13477	1
	Olive	2/0	–	13475	13477	1
	Ruby	3/0	–	13473	13476	1
	White	4/0	–	13473	13476	1
	Red	250	350	13472	13476	1
	Blue	300	400	13472	13476	1
	Brown	–	500	13478	13478	1

* TBM6S includes shure steak mechanism; TBM6 does not.

Carrying cases for TBM6 and TBM6S

Cat no.	Description	Pkg. qty.
295-31365M	Steel carrying case for TBM5, TBM5S, TBM6 and TBM6S	1
295-31365	Plastic carrying case for TBM5, TBM5S, TBM6 and TBM6S	1

OD series manual compression tool



Die type



Dies for:
OD58
OD581
OD583

Fixed 5/8 dies on:

- OD58 wooden handles
- OD581 fiberglass handles
- OD583 curved wooden handles

O,D,T,K etc. dies

Fixed O and D dies.
ODF1 straight
fiberglass handles

Suitable for Burndy MD6
removable dies.

Fixed O and D dies.
ODB wooden handles

Suitable for Burndy MD6
removable dies.

Fixed O and D dies.
ODB1 fiberglass handles

Suitable for Burndy MD6
removable dies.

Fixed O and D dies.
ODB3 curved wooden
handles

Suitable for Burndy MD6
removable dies.

Insulating head cover :
• ODB
• ODH1



- Integral self-gauging system in tool head assures proper adjustment before each crimp
- Improved design reduces force to crimp by as much as 20%
- Teflon® over bronze bearings greatly reduces wear at linkage and pins; far superior to steel bearing surfaces
- All standard insert dies available for OD58 tool ("O" and "D", 840, etc.), 5/8 in. fixed die in nose
- ODF tool has fixed "O" and "D" dies
- ODB tool has fixed "O" and "D" dies; accepts standard insert dies designed for MD6 tool
- Distribution of weight over tool length gives better balance, results in easier handling and positioning
- Optional fiberglass handles for greater strength, lighter weight, better insulating properties and lower moisture absorption rate
- ODF and ODB tools with insulated heads available as an option
- Lever action tool with hot stick handles of Glastrux Fiberglass, rated and tested for 100kV/ft./5 minutes
- Lever action results in minimum applied force to crimp

Removable dies – TBM6H hydraulic press and OD-type tools

Cat no.	Description or colour code	Cat no.	Description or colour code
OJB	O	BY37	840 (EEI 11A)
DBL	D	BY55	Wire cutter (2/0 max.)
BY39	510 Hex (Unbent)	BY63	Orange (Nicopress)
BY41	635 Hex (Unbent)	BY65	Purple
BY43	747 Hex (Unbent)	BY15C*	7/32 Red
BY45	T	BY17C*	1/4 Blue
BY47	K	BY19C*	5/16 Grey
BY49	B	BY21C*	3/8 Brown
BY51	J	BY23C*	1/2 Pink
BY53	P	BY24C*	1/2-1 Gold
BY13	3/16	BY25C*	9/16 Tan/orange
BY15*	7/32 (EEI-1 index 236)	BY27C*	11/16 Yellow
BY17	1/4	BY31C*	5/8-1 Olive/Purple
BY19	5/16 (index 161.242)	BY32C*	Ruby
BY21	3/8	BY35C*	781 White
BY23	1/2 (index 163)	BY37C*	840 Red
BY25	9/16	BY28C*	17/32 Black
BY27	11/16	BY53C*	P Green
BY29	19/32		Canvas bag
BY31	5/8-1 (index 165)	BG-1-BB	for OD58 tool
BY33	737		Insulating cover
BY35	781	ODH1	for tool head

TBM8 and TBM8S* crimp tools



- Install coded copper lugs and connectors #8 through 500 kcmil
- Install aluminum lugs and connectors #10 through 350 kcmil
- Shure Stake mechanism ensures positive compression (only in TBM8S)
- Included dies are colour-coded and provide die-code embossing for easy installation and inspection
- Install all coded copper compression joints and a selection of small C-Taps
- Complete with installing dies and wire brush in plastic carrying case

Die type



Creates diamond-style crimp



Cat no.	Colour code	Al	Cu	Lower die Cat. no.	Pkg. qty.
TBM8 or TBM8S*	Red	10	8	13461	1
	Blue	8	6	13461	1
	Grey	6	4	13461	1
	Brown	–	2	13461	1
	Green	4	1	13462	1
	Pink	2	1/0	13462	1
	Black	–	2/0	13462	1
	Orange	–	3/0	13462	1
	Violet	–	4/0	13463	1
	Yellow	–	250	13463	1
	Or	1	–	13464	1
	Tan	1/0	–	13464	1
	Olive	2/0	–	13464	1
	Ruby	3/0	–	13464	1
	White	4/0	300	13465	1
	Red	250	350	13466	1
	Blue	300	400	13467	1
	Brown	350	500	13468	1

* TBM8S includes shure steak mechanism; TBM8 does not.

TBM840 crimp tool



- Wide range of #8 to 4/0 for copper connectors and splices
- Installs lugs and splices series 54000 and 58000
- 8-position colour-coded rotatable die
- Comfort hand grip
- Die index embossed for permanent inspectability
- Overall length: 233/4 in.
- Handle length: 161/2 in.
- Weight: 8.8 lb



Cat no.	Description	Pkg. qty.
TBM840	Crimp tool for #8 to 4/0 copper lugs with rotating colour-coded die wheel	1

Wire range (AWG or kcmil)		
Copper	Al / Cu	Colour code
#8	#10	Red
#6	#8	Blue
#4	#6	Grey
#2	-	Brown
#1	#4	Green
1/2	#2	Pink
2/0	-	Black
3/0	-	Orange
4/0	--	Violet

TBM14M 14-ton manual hydraulic crimp tool



Die type



Creates hex-style crimp

- Features fiberglass handles for insulation and ease of use in tight spaces
- Two-stage pump provides rapid advance for fast installation
- Uses standard ABB Color-Keyed 15500 series dies

Specifications

- Installing range:
 - Up to 900 kcmil copper lugs and splices
 - Up to 750 kcmil aluminum lugs and splices
 - CHT814-10 to CHT2502-6 copper H-taps
 - 63105 to 63148 aluminum H-taps
 - 54755 to 54775 C-taps
- Output force: 14 tons
- Length: 24 in.
- Weight without dies: 15.4 lb



Conductor range					
Copper code (AWG or kcmil)	Flex/24	Al/Cu (AWG or kcmil)	Colour code die	Die Cat. no.	Die code
8	37/24	#10	Red	15520XSS	21X
6	61/24	#8	Blue	15522XSS	24X
4	91/24	#6	Grey	15527XSS	29X
2	125/24	-	Brown	15528XSS	33X
1	150/24	#4	Green	15513XSS	37X
1/0	225/24	#2	Pink	15508XSS	42X
2/0	275/24	-	Black	15526XSS	45X
3/0	325/24	-	Orange	15530XSS	50X
4/0	450/24	-	Violet	15511XSS	54X
250	550/24	-	Yellow	15110XSS	62X
-	-	#1	Or	-	-
-	-	1/0	Tan	-	-
-	-	2/0	Olive	-	-
-	-	3/0	Ruby	-	-
300	-	4/0	White	15534XSS	66X
350	775/24 (Short)	250	Red	15514XSS	71X
400	775/24 (Long)	300	Blue	15512XSS	76X
-	925/24*	-	-	15517XSS	80X
-	-	-	-	-	-
500	-	350	Brown	15506XSS	87X
600	1100/24	400	Green	15536XSS	84X
-	1325/24**	-	Pink	-	-
700	-	500	Pink	-	-
750	-	650	Black	-	-
800	-	-	Orange	-	-
-	-	700	Violet	-	-
900	195/24	750	Yellow	-	-
1000	-	800	-	-	-
1250	-	1000	-	-	-
1500	-	-	-	-	-

TBM6PCR-LI – Li 6-ton open crimp tool



Die type



- Designed for one-handed control ram advancement and retraction
- Open yoke design with rotating head allows for maximum crimping flexibility
- Protective rubber insulated boot on head
- Rapid advance feature decreases crimp time
- Approx. 350 crimps per full battery charge (based on 3/0 AWG cable)

Specifications

- Capacity: Cu #8–600 kcmil, Al #8–400 kcmil
- Output force: 6 tons
- Dimensions (L x W x H): 13 in. x 2.5 in. x 12 in.
- Battery: 14.4 V DC
- Weight with battery: 8.75 lb




Conductor range				TBM6PCR-LI / TBM6H	
Copper code (AWG or kcmil)	Flex/24	Al/Cu (AWG or kcmil)	Colour code die	Die Cat. no.	Die code
#8	37/24	#10	Red	6TON21SS	21
#6	61/24	#8	Blue	6TON24SS	24
#4	91/24	#6	Grey	6TON29SS	29
#2	125/24	–	Brown	6TON33SS	33
#1	150/24	#4	Green	6TON37SS	37
1/0	225/24	#2	Pink	6TON42SS	42
2/0	275/24	–	Black	6TON45SS	45
3/0	325/24	–	Orange	6TON50SS	50H
4/0	450/24	–	Violet	6TON54SS	54H
250	550/24	–	Yellow	6TON62SS	62H
–	–	#1	Or	6TON45SS	45
–	–	1/0	Tan	6TON50SS	50H
–	–	2/0	Olive	6TON54SS	54H
–	–	3/0	Ruby	6TON60SS	60H
300	–	4/0	White	6TON66SS	66H
350	775/24 (Short)	250	Red	6TON71SS	71H
400	775/24 (Long)	300	Blue	6TON76SS	76H
–	925/24*	–	–	6TON80SS	80H
–	–	–	–	–	–
500	–	350	Brown	6TON87SS	87H
600	1100/24	400	Green	6TON94SS	94H

TBM6PCR-LI – Li 6-ton closed crimp tool



Die type



- Designed for one-handed control ram advancement and retraction
 - Rotating head allows maximum flexibility for crimping
 - Rapid advance feature decreases crimp time
 - Approx. 350 crimps per full battery charge (based on 3/0 AWG cable)
- Specifications**
- Capacity: Cu #8–600 kcmil, Al #10–400 kcmil
 - Output force: 6 tons
 - Dimensions (L x W x H): 13 in. x 2.5 in. x 12 in.
 - Battery: 14.4 VDC
 - Weight with battery: 8.5 lb

Conductor range				TBM62PCR-LI	
Copper code (AWG or kcmil)	Flex/24	Al/Cu (AWG or kcmil)	Colour code die	Hex-Flex die Cat. no.	Hex-Flex die code
8	37/24	#10	Red	6TON21XSS	21X
6	61/24	#8	Blue	6TON24XSS	24X
4	91/24	#6	Grey	6TON29XSS	29X
2	125/24	–	Brown	6TON33XSS	33X
1	150/24	#4	Green	6TON37XSS	37X
1/0	225/24	#2	Pink	6TON42XSS	42X
2/0	275/24	–	Black	6TON45XSS	45X
3/0	325/24	–	Orange	6TON50XSS	50X
4/0	450/24	–	Violet	6TON54XSS	54X
250	550/24	–	Yellow	6TON62XSS	62X

TBM12PCR-LI – Li inline 12-ton open crimp tool



- Designed for one-handed control ram advancement and retraction
- Rotating head allows maximum flexibility for crimping and a protective rubber boot on “C” head
- Rapid advance feature decreases crimp time
- Approx. 150 crimps per full battery charge (based on 3/0 AWG cable)

Specifications

- Capacity: Cu #8–750 kcmil, Al #8–750 kcmil
- Output force: 12-ton
- Dimensions (L x W x H): 16.5 in. x 3.3 in. x 12.6 in.
- Battery: 14.4 V DC
- Weight with battery: 16.8 lb

Conductor range					TBM12PCR-LI	
Copper code (AWG or kcmil)	Flex/24	Al/Cu (AWG or kcmil)	Colour code die	Die Cat. no.	Die code	
8	37/24	#10	Red	15520SS	21	
6	61/24	#8	Blue	15522SS	24	
4	91/24	#6	Grey	15527SS	29	
2	125/24	–	Brown	15528SS	33	
1	150/24	#4	Green	15513SS	37	
1/0	225/24	#2	Pink	15508SS	42	
2/0	275/24	–	Black	15526SS	45	
3/0	325/24	–	Orange	15530SS	50	
4/0	450/24	–	Violet	15511SS	54	
250	550/24	–	Yellow	15510SS	62	
–	–	#1	Or	15526SS	45	
–	–	1/0	Tan	15530SS	50	
–	–	2/0	Olive	15511SS	54	
–	–	3/0	Ruby	15532SS	60	
300	–	4/0	White	15534SS	66	
350	775/24 (Short)	250	Red	15514SS	71	
400	775/24 (Long)	300	Blue	15512SS	76	
–	925/24*	–	–	15517SS	80H	
–	–	–	–	–	–	
500	–	350	Brown	15506SS	87H	
600	1100/24	400	Green	15536SS	94H	
–	1325/24**	–	Pink	–	–	
700	–	500	Pink	15505SS	99H	
750	–	650	Black	15515SS	106H	
800	–	–	Orange	15540SS	107H	
–	–	700	Violet	–	–	
900	195/24	750	Yellow	15504SS	115H	

TBM14CR-LI – Li 14-ton open crimp tool



Die type



- Rotating head allows maximum flexibility for crimping
- Protective rubber boot on “C” head
- Rapid advance feature decreases crimp time
- Approx. 150 crimps per full battery charge (based on 3/0 AWG cable)

Specifications

- Installing range :
 - Up to 900 kcmil copper lugs and splices
 - Up to 750 kcmil aluminum lugs and splices
- Capacity: Cu #8–900 kcmil, Al #10–750 kcmil
- Output force: 14 tons
- Dimensions (L x W x H): 19 in. x 3.5 in. x 10.5 in.
- Battery: 14.4 V DC
- Weight with battery: 20 lb



Conductor range					TBM14CR-LI
Copper code (AWG or kcmil)	Flex/24	Al/Cu (AWG or kcmil)	Colour code die	Die Cat. no.	Die code
8	37/24	#10	Red	15520XSS	21X
6	61/24	#8	Blue	15522XSS	24X
4	91/24	#6	Grey	15527XSS	29X
2	125/24	–	Brown	15528XSS	33X
1	150/24	#4	Green	15513XSS	37X
1/0	225/24	#2	Pink	15508XSS	42X
2/0	275/24	–	Black	15526XSS	45X
3/0	325/24	–	Orange	15530XSS	50X
4/0	450/24	–	Violet	15511XSS	54X
250	550/24	–	Yellow	15110XSS	62X
–	–	#1	Or	–	–
–	–	1/0	Tan	–	–
–	–	2/0	Olive	–	–
–	–	3/0	Ruby	–	–
300	–	4/0	White	15534XSS	66X
350	775/24 (Short)	250	Red	15514XSS	71X
400	775/24 (Long)	300	Blue	15512XSS	76X
–	925/24*	–	–	15517XSS	80X
–	–	–	–	–	–
500	–	350	Brown	15506XSS	87X
600	1100/24	400	Green	15536XSS	84X
–	1325/24**	–	Pink	–	–
700	–	500	Pink	–	–
750	–	650	Black	–	–
800	–	–	Orange	–	–
–	–	700	Violet	–	–
900	195/24	750	Yellow	–	–

TBM14CR-LI – Battpac™ TBM15CR-LI hermetically sealed 15-ton battery-powered compression tool



Die type



- Rotating head allows maximum flexibility for crimping
- Protective rubber boot on head
- Rapid advance feature decreases crimp time
- Approx. 150 crimps per full battery charge (based on 3/0 AWG cable)

Specifications

- Installing range:
 - Up to 900 kcmil copper lugs and splices
 - Up to 750 kcmil aluminum lugs and splices
- Capacity: Cu #8–900 kcmil, Al #10–750 kcmil
- Output force: 14 tons
- Dimensions (L x W x H): 19 in. x 3.5 in. x 10.5 in.
- Battery: 14.4 V DC
- Weight with battery: 24 lb



Conductor range					TBM15CR-LI	
Copper code (AWG or kcmil)	Flex/24	Al/Cu (AWG or kcmil)	Colour code die	Die Cat. no.	Die code	
8	37/24	#10	Red	15520SS	21	
6	61/24	#8	Blue	15522SS	24	
4	91/24	#6	Grey	15527SS	29	
2	125/24	–	Brown	15528SS	33	
1	150/24	#4	Green	15513SS	37	
1/0	225/24	#2	Pink	15508SS	42	
2/0	275/24	–	Black	15526SS	45	
3/0	325/24	–	Orange	15530SS	50H	
4/0	450/24	–	Violet	15511SS	54H	
250	550/24	–	Yellow	15510SS	62H	
–	–	#1	Or	15526SS	45	
–	–	1/0	Tan	15530SS	50H	
–	–	2/0	Olive	15511SS	54H	
–	–	3/0	Ruby	15532SS	60H	
300	–	4/0	White	15534SS	66H	
350	775/24 (Short)	250	Red	15514SS	71H	
400	775/24 (Long)	300	Blue	15512SS	76H	
–	925/24*	–	–	15517SS	80H	
–	–	–	–	–	–	
500	–	350	Brown	15506SS	87H	
600	1100/24	400	Green	15536SS	94H	
–	1325/24**	–	Pink	–	–	
700	–	500	Pink	15505SS	99H	
750	–	650	Black	15515SS	106H	
800	–	–	Orange	–	–	
–	–	700	Violet	–	–	
900	195/24	750	Yellow	15504SS	115H	



Our **Lumen** Branches

ATLANTIC

DARTMOUTH

121, Ilsley Avenue, unit 119
B3B 1S4
902 468-7996

MONCTON

1070, St-George Blvd., unit 1A
E1E 4K7
506 382-1396

ONTARIO

OTTAWA EAST

1000, Belfast Road
K1G 4A2
613 789-7500

OTTAWA WEST

1050, Baxter Road, unit 2
K2C 3P1
613 828-2930

QUÉBEC

ALMA

485, rue Claire-Fontaine
G8B 6H1
418 668-8336

AMOS

821, av. de l'Industrie
J9T 4L6
819 732-6436

ANJOU

9901, boul. Louis-H.-Lafontaine
H1J 2Z5
514 493-4127

BAIE-COMEAU

13, rue Babin
G4Z 3A5
418 296-9320

BLAINVILLE

50, rue Jean-Paul-Cayer, suite 104
J7C 0N9
450 434-3221

CANDIAC

116, rue Paul-Gauguin
J5R 6X2
450 632-1320

CHICOUTIMI

693, rue des Actionnaires
G7J 5B2
418 693-1343

DRUMMONDVILLE

600, boul. Lemire
J2C 7W9
819 477-5933

GATINEAU

250-B, rue Deveault
J8Z 1S6
819 771-7411

GRANBY

610, rue Simonds Sud
J2J 1E1
450 776-6333

JOLIETTE

40, boul. de l'Industrie
J6E 8T9
450 759-8160

LACHENAIE

1117, rue de l'Express
J6W 0A2
450 471-4561

LAVAL

2854, boul. Industriel
H7L 3S2
450 629-4561

LAVAL (COUNTER)

4950, rue Louis-B. Mayer
H7P 0H7
450 688-9249

LÉVIS

880, rue Archimède
G6V 7M5
418 833-1344

LONGUEUIL

630, rue Giffard
J4G 1T8
450 679-3460

MONTRÉAL (DE LA SAVANE)

4750, rue de la Savane
H4P 1T7
514 341-7713

MONTRÉAL (HOCHELAGA)

3044, rue de Rouen
H1W 3Z5
514 521-7711

POINTE-CLAIRE

117A, boul. Hymus
H9R 1E5
514 426-9460

QUÉBEC

4715, av. des Replats
G2J 1B8
418 627-5943

RIMOUSKI

501, rue de l'Expansion
G5M 1S9
418 723-0969

RIVIÈRE-DU-LOUP

324-1 rue Témiscouata
G5R 2Y8
418 867-8515

ROUYN-NORANDA

841, av. Lord
J9X 7G3
819 797-0013

SAINT-EUSTACHE

120, rue Dubois
J7P 4W9
450 472-6160

SAINT-GEORGES

875, 98^e rue
G5Y 8G2
418 220-1344

SAINT-HUBERT

1959, rue F-X Sabourin
J3Z 0B3
450 656-1964

SAINT-JEAN

910, boul. Industriel
J3B 8J4
450 346-1320

SAINT-JÉRÔME

401, rue J-F Kennedy
J7Y 4B5
450 436-3225

SAINTE-FOY

2565, av. Watt, local 1
G1P 3T2
418 656-4247

SEPT-ÎLES

155, rue Napoléon
G4R 3M1
418 962-7773

SHERBROOKE

4350, rue Ouimet
J1L 2A8
819 566-0966

SOREL-TRACY

3200, boul. St-Louis
J3R 5P8
450 742-3771

TROIS-RIVIÈRES

2465, boul. des Récollets
G8Z 4G1
819 374-5013

VAL-D'OR

1225, rue des Foreurs
J9P 6X9
819 825-6555

VAUDREUIL

3665, boul. Cité des Jeunes
J7V 3Z2
450 510-7487

VICTORIAVILLE

415, boul. Labbé Nord
G6P 9J4
819 758-6205

We reserve the right to make technical changes or modify the contents of this document without prior notice. With regard to purchase orders, the agreed particulars shall prevail. ABB Installation Products Inc. does not accept any responsibility whatsoever for potential errors or possible lack of information in this document.

We reserve all rights in this document and in the subject matter and illustrations contained therein. Any reproduction or utilization of its contents – in whole or in parts – is forbidden without prior written consent of ABB Installation Products Inc. Copyright© 2023 ABB Installation Products Inc. All rights reserved

ABB Electrification Canada Inc.

Electrification Business

700 Thomas avenue,
Saint-Jean-sur-Richelieu, QC J2X 2M9

tnb.ca.abb.com