

Lumen

A Sonepar Company

ATLANTIC

Special deals
**November -
December
2021**



Valid for Electrical Contractors
ESA and ECA members only



LED Lamps



A19 - 9.8W, 2700K, 800LM
Replaces 60W, incandescent

Non-dimmable
LAMLEDA199W27KND

Dimmable
LAMLEDA199W27KDIM



GU10 - 7W, 3000K, 500LM
35° beam - **Dimmable**
Replaces 50W, halogen
LAMLEDGU107W3KFL



PAR20 - 7W, 3000K, 500LM
40° beam - **Dimmable**
Replaces 50W, halogen
LAMLEDPAR207W3KFL



MR16 - 7W, 3000K, 500LM
35° beam - **Dimmable**
Replaces 50W, halogen
LAMLEDMR167W3KFL



Signify



LED Recessed Fixture

4 in - 11W, 120V, 3000K, 700LM, dimmable, white.
Sold as pack of 4.

Replaces up to 65W, incandescent
PILADISC4R30K

READY-LITE

LUMACELL



Plastic Pictogram LED Exit Sign

4.2W, self-powered

REDCMPSSPRL
LUMCMPSSPL



Plastic Emergency LED Lighting Fixture Battery Unit

6V, 27W, 2 x 4W

REDCMPBRL
LUMCMPBL



LED Wall Pack

120/277V, 3000K, dimmable driver 0/10V, type 2
distribution, gray finish, 10 year limited warranty.
Wall mounting post and photocell included.

72W, 8100LM - *Replaces 150W, HPS*
LUMKITSSENTINELLE72W2

135W, 17655LM - *Replaces 400W, HPS*
LUMKITSSENTINELLE135W2



Plastic Pictogram LED Exit Combo Unit

2 x 1W, self-powered

REDCMPCL
LUMCMPCL



Emergency LED Lighting


6-12V

Single - 1 X 3W
REDCMR1RL
LUMCMR1L

Double - 2 X 3W
REDCMR2RL
LUMCMR2L

Day-Brite**CFI**

by @ignify

**Fluorescent Strip****48 in - 2 x F32T8 (lamps not included)**

120V/277V

CFIT232UNV12EB

347V

CFIT23234712EB

Day-Brite**CFI**

by @ignify

**LED Surface Fixture****48 in - 120/277V, 4 000K, 4 000LM**

Non-dimmable, acrylic frosted lens.

Replaces 2 x 32W, T8

CFIFSSSEZ440L840UNV

Day-Brite**CFI**

by @ignify

**LED Surface Fixture****48 in - 120/277V, 4 000LM, adjustable color**

3 000/3 500/4 000K, wraparound lens and occupancy sensor.

Replace 2 X 32W, T8

CFINWL440L8CSTUNVDIMOC

Day-Brite**CFI**

by @ignify

**LED Panel for Suspended Ceiling**

Adjustable power 120/347V and adjustable CCT 3 500/4 000/5 000K, dimmable.

1 x 4

CF11SBP3040L8CS4UN3DIM

2 x 2

CF12SBP3040L8CS2UN3DIM

2 x 4

CF12SBP3550L8CS4UN3DIM

Day-Brite**CFI**

by @ignify

**LED High Bay Fixture**

120/347V, adjustable CCT (4 000/5 000K), open hook, 6 ft cord, dimmable 0/10V, polycarbonate lens.

14 000LM

CF1HCY14L8CSTUN3DIM

21 000LM

CF1HCY21L8CSTUN3DIM

28 000LM

CF1HCY28L8CSTUN3DIM

33 000LM

CF1HCY33L8CSTUN3DIM

Day-Brite**CFI**

by @ignify

**LED Surface Fixture****96 in - Dimmable 0/10V, 8 000LM,**

acrylic frosted lens.

Replaces 4 x 32W, T8

120/277V

3 500K # CF1FSS880L835UNVDIM

4 000K

CF1FSS880L840UNVDIM

347V

3 500K # CF1FSS880L835347DIM

4 000K # CF1FSS880L840347DIM

PHILIPS**Magnetic HID Ballast Kit**

120/277/347V

Ballast HPS

70W, S62

PHI71A79A1001D

100W, S54

PHI71A80A1001D

150W, S55

PHI71A81A2001D

250W, S50

PHI71A82A1001D

400W, S51

PHI71A84A3001D

**Ballast MH**

175W, M57/M107/H39

PHI71A55A0001D

250W, M58/H37

PHI71A57A0001D

400W, M59/H33

PHI71A60A1001D

PHILIPS**High Pressure Sodium Lamp**

Mogul Base

70W

PHIC70S62ALTO

100W

PHIC100S54ALTO

150W

PHIC150S55ALTO

250W

PHIC250S50ALTO

400W

PHIC400S51ALTO

**PHILIPS****Metal Halide Lamp**

Mogul Base

175W

PHIMH175U

250W

PHIMH250U

400W

PHIMH400U

**STANPRO****LED Wall Pack**

120/277V, frosted polycarbonate lens, photocell included, bronze finish.

Replaces up to 70W, HID

15W, 1 725LM, 3 000K

STAWCILS1W30KBR

20W, 4 000K (2 522LM) /

4 500K (2 926LM) / 5 000K (2 637LM)

STAWCILS2W3CBB

**LED Wall Pack**

120/347V, 3 000/4 000/5 000K, bronze finish, photocell included, prismatic glass lens, dimmable 0/10V.

25/30/40W

STAWSPSPS40Q3C

60/80/100W

STAWSPSPS100Q3C

120W

STAWPSNS120Q3C

**LED High Bay Fixture**

4 000K, dimmable, with 10 ft cord and open hook, clear polycarbonate lens.

120/277V, 23 000LM

STAL1RSHLS2W40K

347V, 23 000LM

STAL1RSHLS2H40K

120/277V, 33 000LM

STAL1RSHLS3W40K

347V, 33 000LM

STAL1RSHLS3H40K



LED Projector

20W, 120V, 4 000K, 1 770LM, photocell included.
Replaces 150W, PAR38 incandescent

Bronze # LITOVFLLED2RH40K120PEDB
White # LITOVFLLED2RH40K120PEWH



LED Projector

With motion sensor
2 x 10W, 120V, 4 000K, 1 569LM
Replaces 2 x 60W PAR38, halogen

Bronze # LITOLF2RH40K120MOBZ
White # LITOLF2RH40K120MOWH



LED Recessed Fixture

4 in - 3 000/4 000/5 000K, 700 to 780LM,
adjustable gimbal, matte white.

Replaces up to 65W, incandescent
LITWF4ADJLED30K40K50KMW



High Bay LED Fixture

120/277V, 4 000K, medium distribution, 6 ft cord,
dimmable 0/10V, anti-glare lens, V hook and 36 in
chain included.

22-1/2 x 11-1/2 in - 24 000LM
4 000K # LITCPHB24LMSEFGCLMDMV4K
5 000K # LITCPHB24LMSEFGCLMDMV5K

22-1/2 x 11-1/2 in - 30 000LM
4 000K # LITCPHB30LMSEFGCLMDMV4K
5 000K # LITCPHB30LMSEFGCLMDMV5K



LED Wall Pack

120/277V, bronze finish
54W, adjustable output 1 450 to 6 950LM
Replaces 70W to 250W, MH

4 000K # LITTWX2LEDALO40KMVDDB
5 000K # LITTWX2LEDALO50KMVDDB

108W, adjustable output 2 900 to 13 850LM
Replaces 100W to 400W, MH

4 000K # LITTWX3LEDALO40KMVDDB
5 000K # LITTWX3LEDALO50KMVDDB



LED Ceiling Mount Fixture

120/277V, 4 000K, bronze

35W, 4 500LM
Replaces up to 150W, HID
LITCNYPEDP140KMVDDB

52W, 6 600LM
Replaces up to 175W, HID
LITCNYPEDP240KMVDDB



Suitable
for wet
location

LED Recessed Fixture

4 in - 120V, adjustable output (700/1 000/1 200LM),
adjustable CCT (2 700/3 000/3 500/4 000/5 000K)
or warm dim (2 850/1 900K), white baffle reflector,
regressed lens, renovation type junction box,
fixture height is under 3 in.

JUNKITJPDZ4RENO



LED Recessed Fixture

120V, 5 CCT 2 700 to 5 000K, dimmable, regressed
lens and deflector designed to reduce glare, white.

4 in - 9W, 670LM
Replaces 65W, incandescent
JUNWF4REGSWW590CRMW

6 in - 13W, 950LM
Replaces 75W, incandescent
JUNWF6REGSWW590CRMW



LED Recessed Fixture

120V, 5 CCT 2 700K to 5 000K, 670LM, white

4 in - 9W, 670LM
Replaces up to 65W, incandescent
JUNWF4SWW590CRIMW

6 in - 13W, 950LM
Replaces 75W, incandescent
JUNWF6SWW590CRIMW



Temporary Lighting Stringlight

For 10 x 150W lamps (maximum), 100 ft
14/3 SJTW (lamps not included).

STASL100FTDSC10SKT14AWG



LED Panel for Suspended Ceiling

120/347V, 3 500/4 000/5 000K, dimmable 0/10V.

1x4 - 20/30/40W
STAL3PNB1LPSQ3C

2x2 - 20/30/40W
STAL3PNB2LPSQ3C

2x4 - 30/40/50W
STAL3PNB4LPSQ3C



LED Projector

120V, 4 000K, arm mount, black

30W, 3 191LM
Replaces 100W, HID
STAF30W40KKNBKCHOICESTD

50W, 5 397LM
Replaces 175W, HID
STAF50W40KKNBKCHOICESTD



3-Port Plug
30A, 125/250V, 4 wires
HUBHBL2711



3-Port Connector
30A, 125/250V, 4 wires
HUBHBL2713



Valise Plug
15A, 125V, 2P, 3 wires
HUBHBL5965VY



Valise Connector Body
15A, 125V, 2P, 3 wires
HUBHBL5969VY



Transparent Cover
2-3/4" depth,
horizontal/vertical.
HUBMM420CCN



Generator Junction Box
Male plug, 30A, 3P, 4 wires
HUB58405



24-Hour Mechanical Time Switch
40A
125V, 2HP
INTT10170
208/277V, 5HP
INTT10470



Digital 24-Hour Timer
4A, 120V, single pole and 3-way
Programmable on 7 days
Wallplate not included
INTEJ600



LED Electronic Photocontrol
6A, 120V, fixture HID or LED,
button type, 1 650W à 277VAC
INTEK4036S

SIEMENS

NEW IN STOCK!
White panel available



Loadcenter SNC Series

- Equivalent to the EQL series
- Main lug panel
- 3 conductors
- 1-phase, 120/240V
- Compatible with Q series circuit breakers

Also available in 12, 16 and 40 circuits

Features


- Invertible
- Bonding screw
- Visible neutrals
- INSTA-WIRE™
- Durable hook-rails
- Integrated neutral bus
- Available in white

Amp rating	No. of spaces	No. of circuits	Height (in)	Product code
125A	24	48	24	# SIESNC2448L1125W
200A	30	48	30	# SIESNC3048L1200W
200A	40	60	36	# SIESNC4060L1200W



Pre-Assembled Heating Cable
120V, self-regulating, with 6 ft lead cable and lighted plug.

- 6 ft # RAYFG16P
- 12 ft # RAYFG112P
- 18 ft # RAYFG118P
- 24 ft # RAYFG124P
- 36 ft # RAYFG136P
- 50 ft # RAYFG150P
- 75 ft # RAYFG175P
- 100 ft # RAYFG1100P



RIM-DT Ice Melting System
Includes cable, connection kit and channel panel.
120V # RAYF6205AL231
208/240V # RAYF6205AL232

Liquid-Tight Conduit Fitting

Straight




Non-insulated

3/8 in
THO5231
1/2 in
THO5232
3/4 in
THO5233

Insulated

3/8 in
THO5331
1/2 in
THO5332
3/4 in
THO5333

90° Angle



Non-insulated

3/8 in
THO5251
1/2 in
THO5252
3/4 in
THO5253


Insulated

3/8 in
THO5351
1/2 in
THO5352
3/4 in
THO5353



Liquid-Tight Flexible Metallic Conduit

3/8 in x 100 ft
THOLTGCS01BC100
1/2 in x 100 ft
THOLTGCS02BC100
3/4 in x 100 ft
THOLTGCS03BC100



Spring Nut

3/8 in
SUPA1003/8EGC
1/2 in
SUPA1001/2EGC



Threaded Hanger Rod

3/8 in x 10 ft
VISTF3/8
1/2 in x 10 ft
VISTF1/2

Pre-Galvanized Channels



Full scale

10 ft
SUPA120010PGC
20 ft
SUPA120020PGC



Half slot

10 ft
SUPA1200HS10PGC
20 ft
SUPA1200HS20PGC



Decora Dimmer

120V, 300W LED and CFL, 600W incandescent/halogen, 60Hz, single pole and 3-way. On/Off rocker switch. Wallplate not included.
LEVDSL061LZ



Illumatech Slide Dimmer

150W LED and CFL, 600W, incandescent compatible with LED bulb, CFL, incandescent, single pole and 3-way. Wallplate not included.
LEVIPL0610Z



LED Ceiling Occupancy Sensor Lampholder

8.7W, 120VAC, 60Hz, white. Ideal for closets, storage areas, attics and basements. Suitable for indoor use only.
LEV9864LED

Gift Ideas

KLEIN TOOLS



**Tradesman Pro™
Electrician Backpack**
39 pockets for maximum tool storage.
KLE55421BP14



**Non-Contact Voltage Tester
with Laser Distance Meter**
Detects AC voltage 12 to 1000V with visual and audible indicators. 66 ft (20m) laser that measures in meters, inches with decimals, inches with fractions, feet with decimals or feet with fractions.
KLENCVT6

DYNAMIC
SECURITE INTERNATIONALE



BOSS® THERM™ Heated Vest
Base layer with 3 adjustable settings. Heating elements located on the chest and back. Includes battery operated remote control. Quick rechargeable 5V power bank provides 8+ hours of warmth on a single charge. Machine washable. One size fits all.
DYN300HV100

BUY Lineman's Pliers GET A FREE

Multi-Bit Screwdriver / Nut Driver, 11-in-1



Lineman's Pliers
9 in - Fish tape pull / crimping.
Pliers cut ACSR, screws, nails, etc.
KLEKITPINCETOURNEVIS



Pro Impact Power Bit Set
26 pieces
KLE32799

BRADY



BMP21-Plus Label Printer
Automatic label formatting for wires, 104 symbols for electricity, security and data transmission.
2-year warranty.
BRABMP21PLUS

Milwaukee

**LIMITED
QUANTITY**



PACKOUT™ Tool Box
Impact resistant polymers and metal reinforced corners for ultimate durability in harsh jobsite conditions. Featuring an IP65 rated weather seal.

- A 75 lb capacity
MIL48228424
- B 100 lb capacity
MIL48228425
- C 250 lb capacity, with
9" all-terrain wheels
MIL48228426



Keychain Measuring Tape
6 ft (2 m)
MIL48225506

Garant



Telescopic Snow Brush
Stretches up to 45" for quick, scratch-free snow removal, ultra-robust polycarbonate scraper.
GARG45SBMST



**SHOCKWAVE™ Impact
Duty Driver Bit Set**
32 pieces
MIL48324004

Energizer



Rugged LED Headlight
70LM, 4 light modes: white (high/low), red for night, green for contrast, hands-free lighting with independent controls, pivots up to 90°.
ENETUFHD31PE

Milwaukee



**M18™ FUEL™
2-Tool Combo Kit (2997-22)**
Includes: hammer drill, hex impact driver,
M12/M18™ multi-voltage charger, two XC
5.0AH batteries and carrying case.

**COMPLETE THIS KIT WITH A
FREE GIFT**



SAWZALL® SAW
M18 FUEL™ SAWZALL®
Reciprocating saw
MILKIT2997222821

OR



GRINDER
M18 FUEL™ 4-1/2 in/5 in
Paddle switch no-lock.
MILKIT2997222880

BRADY

⚠ DANGER
ARC FLASH & SHOCK HAZARD
Appropriate personal protection
equipment required

Arc Flash & Shock Hazard Sign
2 x 4 in - Industrial-grade adhesive sticks
permanently to a wide variety of surfaces.
Pack of 10 # BRA101520

Westinghouse



Dual Fuel Generator
Gas/propane - 7500W open frame. Push button
electric start. Fuel selector switch allows to easily
switch from gas to propane without shutting off
the unit. Battery charging port (charger included).
Other models available.
WESWGEN7500DF

AMPROBE



Light Meter
Autoranging, measures in Lux or foot candles (FC),
front panel switchable. Measuring range to 200 000
Lux or 20 000 foot candles (FC). Data hold to freeze
reading on the digital display.
AMPLM120

FLUKE



Laser Distance Meter
Instantly measure up to 131 ft, with 1-button
point-and-click. Quickly calculate area (ft²/m²).
FLU417D

TINGLEY



Orion™ Winter Over-Shoes Boot
Nylon upper, polyurethane midsole and TPR outsole.
Anti-fatigue overshoe with heavy-duty performance.

Small # TIN7500GSM
Medium # TIN7500GMD
Large # TIN7500GLG
X-Large # TIN7500GXL
2X-Large # TIN7500G2XL

PIONEER



**Storm Master Pullover
Head Cover**
100% spun acrylic, black.
One size # PIOV4010170



3-in-1 Neck Warmer
Micro-fleece, converts from neck
warmer to hat or face mask, black.
One size # PIOV4030470-O/S



K1 Mid-Sole Ice Cleat
Adds traction in icy and snowy work conditions. Ideal
for workers regularly going from outdoor to indoor
environments (just rotate them). One size fits all.
Regular # PIOV97701500S
Low profile # PIOV97702500S

ATLANTIC - Effective from November 1st to December 31st 2021

f o in o

lumen

7



**OVER 200
COMMERCIAL TRANSFORMERS**
in stock at Lumen

We're setting back the time on **Sunday, November 7th 2021**. Don't forget to:



INSTALL

BRKSC9120BLA
BRK9120BA



CLEAN

CRC74085



CHECK

CRC72105



CHANGE

DURPC1604BK



Download the Lumen app!



Place your orders directly
online at lumen.ca or via
the Lumen app.



Two branches to better serve Atlantic Canada!

DARTMOUTH

121, Ilsley Avenue, unit 119, Dartmouth (NS), B3B 1S4

Tel.: 902 468-7996 / **Fax:** 902 468-7997

Toll free: 1 844 516-0158

MONCTON

1070, St-George Blvd., unit 1A, Moncton (NB), E1E 4K7

Tel.: 506 382-1396 / **Fax:** 506 382-9376

Toll free: 1 844 311-1396

Lumen
A Sonepar Company

Prices are subject to change without notice. All images are for illustrative purposes only. Air Miles program is reserved to the Electrical Contractor ESA or ECA members only. We are currently experiencing an exceptionally high demand for many popular products. As a result, some products advertised in this flyer may not be available. Please check your local branch for availability or visit lumen.ca. We are currently working on replenishing supplies as quickly as possible and apologize for any inconvenience this may cause.

