


BELDEN CLASSICS


COMPOSITE ACCESS CONTROL CABLE (CUL, 300V)

- 4C-18 (grey), 3PR-22 (orange), 2C-22 (white), 4C-22 (blue)
- Each cable PVC insulated with overall foil shield
- PVC jackets, no overall jacket
- Cable jackets color coded by application
- Temperature range: **Part #50-558AFS**, 0°C to 75°C
- Lock power, card reader, door contact and REX applications




PAIRED - HIGH CONDUCTIVITY SPEAKER CABLE (CUL, FT4, 300V)

- 16 AWG and 18 AWG available
- Stranded tinned copper conductors, twisted pair
- PVC insulation
- Chrome PVC jacket
- Temperature range: **Part #50-8471 (16 AWG)**, -20°C to 80°C,
Part #50-8461-4 (18 AWG), -20°C to 80°C



PAIRED - AUDIO, CONTROL, INSTRUMENTATION CABLE (CUL, 300V)

- 18 AWG stranded tinned copper conductors, twisted pairs
- PE insulation
- Overall foil shield
- Stranded tinned copper drain wire
- Chrome PVC jacket
- Temperature range: **Part #50-8760**, -20°C to 60°C
Part #50-8760-4 (FT4 rated, PVC insulated), -30°C to 90°C




PAIRED - AUDIO, CONTROL, INSTRUMENTATION CABLE (CUL, FT4, 300V)

- 18 AWG stranded tinned copper conductors, 2 twisted pairs
- PVC insulation
- Chrome PVC jacket
- Temperature range: **Part #50-9156**, -20°C to 80°C



PAIRED - SINGLE PAIR CABLE (CUL, 300V)

- 22 AWG stranded tinned copper conductors, twisted pair
- Polyethylene insulation
- Overall foil shield
- Stranded tinned copper drain wire
- Chrome PVC jacket
- Temperature range: **Part #50-8761**, -20°C to 60°C
Part #50-8761-4 (FT4 rated), -20°C to 60°C



PAIRED - SHIELDED TWISTED PAIR CABLE (CUL, 300V)

- 22 AWG stranded tinned copper conductors, 2 twisted pairs
- Polypropylene insulation
- Individual foil shields
- Stranded tinned copper drain wire
- Chrome PVC jacket
- Temperature range: **Part #50-8723**, -20°C to 75°C
Part #50-8723-4 (FT4 rated), -40°C to 60°C




BELDEN CLASSICS

BELDEN


MULTI-PAIRED - SHIELDED TWISTED PAIR CABLE (CUL, 300V)

- 22 AWG stranded tinned copper conductors, 3 twisted pairs
- Polypropylene insulation
- Individual foil shields
- Stranded tinned copper drain wire
- Chrome PVC jacket
- Temperature range: **Part #50-8777**, -20°C to 80°C
Part #50-8777-4 (FT4 rated), -30°C to 90°C



MULTI-CONDUCTOR - AUDIO, CONTROL, INSTRUMENTATION CABLE (CUL, 300V)


- 18 AWG stranded tinned copper conductors, 3 conductors cabled
- Polyethylene insulation
- Overall foil shield
- Stranded tinned copper drain wire
- Chrome PVC jacket
- Temperature range: **Part #50-8770**, -20°C to 60°C
Part #50-8770-4 (FT4 rated), -30°C to 90°C



COAXIAL RG 58A/U (CUL, 300V)

- 20 AWG solid bare copper conductor
- Polyethylene insulation
- Tinned copper braid shield (95% coverage)
- Black PVC jacket
- Temperature range: **Part #50-8240**, -40°C to 75°C


In addition to Belden Classics, we offer special digital and HD video coaxial cables used for broadcasting applications.



COAXIAL RG 6/U (18 AWG), RG 59/U (20 AWG) (CUL, 300V)

- Solid bare copper conductor
- Gas-injected foam HDPE insulation
- Foil (100% coverage), tinned copper braid shield (95% coverage)
- Black PVC jacket
- Temperature range: **Part #50-1694A (Coaxial RG 6/U FT4)**, -30°C to 75°C
Part #50-1505A (Coaxial RG 59/U FT4), -30°C to 75°C

**Other jacket colours available upon request
Refer to C.E. Code for additional information*



Visit our website at Texcan.com and social media [@TexcanCanada](https://www.facebook.com/TexcanCanada)

VANCOUVER

1-800-665-1025
10449 120th St. Surrey, BC

MAJOR PROJECTS GROUP

1-888-818-9473
10449 120th St. Surrey, BC

EDMONTON

1-800-252-7545
11330 189 St. NW. Edmonton, AB

CALGARY

1-855-717-3900
190-11600 Stonehill Dr. NE Calgary, AB

SASKATOON

1-855-385-3800
3403 Faithfull Ave. Saskatoon, SK

WINNIPEG

1-800-665-2491
25 Meridian Dr. Winnipeg, MB

When others can't, TEXCAN

WIRE & CABLE SPECIALISTS SINCE 1978