


Phoenix Selection Guide

Terminal Blocks

UK 5 N - Feed-through terminal block



UK5N Terminal Block



FBI 10- 6 - Fixed bridge



D-UK 4/10 - End cover



E/NS 35 N - End bracket



UCT-TM 6 -Terminal Marking

PH03004362	UK5N Feed-through terminal block, nom. voltage: 800 V, nominal current: 32 A, number of connections: 2, connection method: Screw connection, mounting type: NS 35/7,5, NS 35/15, NS 32, color: gray
PH00203250	FBI 10- 6 - Fixed bridge for UK5N, pitch: 6.2 mm, number of positions: 10, color: silver-colored
PH03003020	D-UK 4/10 - End cover for UK5N, color: gray
PH00800886	E/NS 35 N - End bracket/clamp, width: 9.5 mm, color: gray
PH00828736	UCT-TM 6 - Marker for terminal blocks, Sheet, white, unmarked, mounting type: latching, for terminal block width: 6.2 mm, Number of individual labels: 60, text field height: 10.5 mm, text field width: 5.6 mm

UT 4 - Feed-through terminal block



UT4 Terminal block



UT4 PE - Protective conductor terminal block




D-UT 2.5/10 - End cover



E/NS 35 N - End bracket

PH03044102	UT4 Feed-through terminal block, nom. voltage: 1000 V, nominal current: 32 A, number of connections: 2, connection method: Screw connection, mounting type: NS 35/7,5, NS 35/15, color: gray
PH03044128	UT4 PE - Protective conductor terminal block, number of connections: 2, connection method: Screw connection, mounting type: NS 35/7,5, NS 35/15, color: green-yellow
PH03047028	D-UT 2.5/10 - End cover for UT4, color: gray
PH00800886	E/NS 35 N - End bracket/clamp, width: 9.5 mm, color: gray

PT 2.5 - Feed-through terminal block



PT 2.5 Terminal Block



PT 2.5-PE - Protective conductor terminal block



FBS 10-5 - Plug-in bridge




D-ST 2.5 - End cover



E/NS 35 N - End bracket

PH03209510	PT 2.5 Terminal - nom. voltage: 800 V, nominal current: 24 A, number of connections: 2, number of positions: 1, connection method: Push-in connection, mounting type: NS 35/7,5, NS 35/15, color: gray
PH03209536	PT 2.5-PE - Protective conductor terminal block, number of connections: 2, connection method: Push-in connection, mounting type: NS 35/7,5, NS 35/15, color: green-yellow
PH03030213	FBS 10-5 - Plug-in bridge PT2.5 & PT2.5 Quattro, pitch: 5.2 mm, number of positions: 10, nominal current: 24 A, length: 23 mm, color: red
PH03030417	D-ST 2.5 - End cover for PT2.5, color: gray
PH00800886	E/NS 35 N - End bracket/clamp, width: 9.5 mm, color: gray

PT 2.5 QUATTRO - Feed-through terminal block



PT2.5 QUATTRO Terminal block



FBS 10-5 - Plug-in bridge




D-ST 2,5-QUATTRO - End cover



E/NS 35 N - End bracket

PH03209578	PT2.5 QUATTRO - Feed-through terminal block, nom. voltage: 800 V, nominal current: 24 A, number of connections: 4, connection method: Push-in connection, mounting type: NS 35/7,5, NS 35/15, color: gray
PH03030213	FBS 10-5 - Plug-in bridge PT2.5 & PT2.5 Quattro, pitch: 5.2 mm, number of positions: 10, nominal current: 24 A, length: 23 mm, color: red
PH03030514	D-ST 2,5-QUATTRO - End cover for PT2.5 Quattro, depth: 29.1 mm, width: 2.2 mm, height: 72.2 mm, color: gray
PH00800886	E/NS 35 N - End bracket/clamp, width: 9.5 mm, color: gray



DIN Rail - For all DIN Mountable Products

PH00801733	DIN rail perforated - 35mm/7.5mm /2000mm, acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver
------------	---

Power Supplies

PH01394764	PS-EE-2G/1AC/24DC/60W/SC - Primary-switched power supply unit ESSENTIAL POWER, Screw connection, DIN rail mounting, input: 1-phase, output: 24 V DC / 2.5 A, adjustable from 24-28 V DC
------------	--



PH01234302	PS-EE-2G/1AC/24DC/120W/SC - Primary-switched power supply unit ESSENTIAL POWER, Screw connection, DIN rail mounting, input: 1-phase, output: 24 V DC / 5 A, adjustable from 24-28 V DC
------------	---



Unmanaged Ethernet Switches


PH01085039	FL SWITCH 1005N - Narrow Ethernet switch, Five (5) RJ45 ports with 10/100 Mbps on all ports, auto-detecting, auto-crossing, and QoS
------------	---



PH01085256	FL SWITCH 1008N - Narrow Ethernet switch, Eight (8) RJ45 ports with 10/100 Mbps on all ports, auto-detecting, auto-crossing, and QoS
------------	--



Ferrules



PH03200014	Ferrule, Al 0.5 – 8 WH, 1.1 mm diameter, Length contact range: 8 mm, sleeve length: 14 mm, color: white
PH03200043	Ferrule, Al 1.5 - 8 BK, 1.8 mm diameter, Length contact range: 8 mm, sleeve length: 14 mm, color: black
PH03200522	Ferrule, Al 2.5 – 8 BU, 2.3 mm diameter, Length contact range: 8 mm, sleeve length: 14 mm, color: blue