

BONDING, GASKETING AND SEALING



404™

- ✓ An instant adhesive designed for general maintenance and repair on a wide variety of materials.
- ✓ Excellent for bonding rubber where very fast fixturing is required.
- ✓ Temperature range: -54°C (-65°F) to 82°C (180°F).
- ✓ Fixture time: 30 seconds.
- ✓ **CFIA &/or Health Canada Listed.**
MIL-A-46050C, Type II, /Class II.



ITEM #	IDH #	DESCRIPTION	FORMAT
46551	135465	LOCTITE® 404™ Industrial Adhesive — Clear	.33 oz. bottle

495™

- ✓ General-purpose, low viscosity instant adhesive. Offers fast bonding on a wide range of materials, including plastics, rubbers and metals.
- ✓ Temperature range: -54°C (-65°F) to 121°C (250°F).
- ✓ Fast bonding (5-20 secs fixture time).
- ✓ Gap fill: 0.006 in.



ITEM #	IDH #	DESCRIPTION	FORMAT
49504	234072	LOCTITE® 495™ Instant Adhesive — Clear	3 gram tube
49550	135467		1 oz. bottle

SI 596™

HIGH TEMPERATURE

- ✓ Forms a tough, flexible, waterproof, oil-resistant silicone rubber bond.
- ✓ Resists aging, weathering and thermal cycling without hardening, shrinking or cracking.
- ✓ Used as a sealant and adhesive for assembly and repair of industrial furnaces, ovens, boilers, exhaust stacks, high temperature ducting, and heating elements in electrical appliances.
- ✓ Heat resistant up to 316°C (600°F).
- ✓ **CFIA &/or Health Canada Listed.**



ITEM #	IDH #	DESCRIPTION	FORMAT
59630	135507	LOCTITE® SI 596™ Red High Temp RTV Silicone Adhesive Sealant — Red	80 ml tube
59675	198817		300 ml cartridge
40465	743520		190 ml power can

401™

- ✓ Surface insensitive instant adhesive.
- ✓ Very high strength on close-fitting parts.
- ✓ Perfect for all quick repairs and all types of small emergency repairs.
- ✓ Low viscosity.
- ✓ Temperature range: -54°C (-65°F) to 121°C (250°F).
- ✓ Bonds a wide range of similar or dissimilar substrates (metals, rubber, wood, cardboard, ceramics as well as most plastics).



ITEM #	IDH #	DESCRIPTION	FORMAT
40104	233641	LOCTITE® 401™ Surface Insensitive Instant Adhesive — Clear	3 gram tube
40140	135429		20 gram bottle

SI 587™

HIGH PERFORMANCE

- ✓ A silicone paste used for formed-in-place gasketing and sealing applications in plant maintenance and OEMs.
- ✓ Excellent resistance to automotive engine oils and adheres to a wide range of substrates.
- ✓ Used in applications up to 260°C (500°F).
- ✓ **CFIA &/or Health Canada Listed.**



ITEM #	IDH #	DESCRIPTION	FORMAT
58730	135504	LOCTITE® SI 587™ Blue High Performance RTV Silicone Gasket Maker — Blue	70 ml tube
58775	234590		300 ml cartridge
40462	743517		190 ml power can

EA E-OONS™

- ✓ A 2-part, fast fixturing, thixotropic gel epoxy.
- ✓ Cures at room temperature to form a translucent, rigid and machinable bondline.
- ✓ Suitable for use on vertical surfaces.
- ✓ Low odour. Non-sag.
- ✓ **CFIA &/or Health Canada Listed.**



ITEM #	IDH #	DESCRIPTION	FORMAT
29294	233962	LOCTITE® EA E-OONS™ Epoxy — Yellow/Translucent	50 ml dual cartridge
98472	720228		50 m gun
98455	720230		nozzles - 10/pk

BONDING, GASKETING AND SEALING

AA 330™

NO-MIX ADHESIVE

- ✓ A no-mix, clear/amber, general-purpose structural bonder ideal for bonding metal, wood, ferrite, ceramic and plastic materials.
- ✓ Max temperature: 121°C (250°F).
- ✓ **Typical applications:** metal labels, spec. tags, vibration analysis buttons, magnets.



ITEM #	IDH #	DESCRIPTION	FORMAT
1690727	1690727	LOCTITE® AA 330™	Adhesive Kit (25 ml syringe)
1691005	1691005	No-Mix	Industrial Pac (250 ml tube)
1689700	1689700	Adhesive	250 ml tube*
1689437	1689437	— Amber	300 ml cartridge*

* Requires LOCTITE® Activator 7387™

380™

- ✓ A low viscosity, rubber-toughened, 1-part, room temperature cure, instant adhesive. Designed for close fitting parts and bonding metal, rubber and selected plastics.
- ✓ Excellent peel, impact, and shear strengths.
- ✓ Toughened.
- ✓ Low viscosity.
- ✓ **CFIA &/or Health Canada Listed.**



ITEM #	IDH #	DESCRIPTION	FORMAT
38004	232834	LOCTITE® 380™ Toughened – Black	3 gram tube
38050	135423		1 oz. bottle
38061	135424		1 lb bottle

MS 5570™ WH

- ✓ A strong bonding adhesive based on Flextec® Technology, with elastic properties for bonding and sealing dissimilar substrates, as well as exterior seam sealing.
- ✓ High initial tack and fast setting.
- ✓ Primerless flexible sealing adhesion.
- ✓ Max temperature: 93°C (200°F).
- ✓ U.V. Resistant.



ITEM #	IDH #	DESCRIPTION	FORMAT
1565679	1565679	TEROSON® MS 5570™ Adhesive – White	300 ml cartridge

SI 5900™

BEST IN CLASS

- ✓ Heavy bodied, silicone-based gasketing product suitable for various substrates. Excellent resistance to oil and joint movement.
- ✓ Adheres to metal, plastic, glass and ceramic materials.
- ✓ **Typical applications:** stamped sheet metal covers (timing covers, and oil sumps).
- ✓ **CFIA &/or Health Canada Listed.**



ITEM #	IDH #	DESCRIPTION	FORMAT
20166	212184	LOCTITE® SI 5900™ Heavy Body RTV Silicone Flange Sealant	300 ml cartridge
40478	743912	LOCTITE® SI 5900™ Instant Gasket — Black	90 ml power can
30509	270637		5 oz. cartridge
40479	743913		190 ml power can

HY 4070™

NEW INNOVATION

- ✓ Ultra-Fast universal repair instant adhesive/acrylic.
- ✓ Hybrid technology.
- ✓ Fixture time as fast as 20 seconds.
- ✓ Excellent gap-fill ability, up to 5 mm.
- ✓ Non-drip gel.
- ✓ Rapid bond strength on many materials such as metal, plastics, rubber, wood, paper, & leather.



ITEM #	IDH #	DESCRIPTION	FORMAT
2264448	2264448	LOCTITE® HY 4070™ Ultra-Fast, Universal Repair Adhesive — Clear/Amber	11 gram kit (4 nozzles, syringe, & plunger)

HY 4060™ GY

NEW INNOVATION

- ✓ The go-to adhesive. Durable, structural repair Instant adhesive/epoxy.
- ✓ Hybrid technology.
- ✓ Fast, 5-minute cure speed.
- ✓ High gap filling capability.
- ✓ Machinable, sandable, drillable, paintable.
- ✓ Excellent bond strength on many material such as metal, plastics, rubber, wood, paper, and leather.



ITEM #	IDH #	DESCRIPTION	FORMAT
2267079	2267079	LOCTITE® HY 4060™ GY Structural Instant Adhesive Hybrid — Grey	25 gram dual syringe