

SURFACE PROTECTION CONCRETE REPAIR, GROUTING, & ANTI-SLIP COATINGS

FC FAST CURE WEARING COMPOUND

- ✓ A 2-part, thixotropic, compound epoxy, non-sag paste that works in less than half the time of conventional curing epoxies.
- ✓ Use to rebuild, repair and protect processing equipment from hard sliding abrasion.
- ✓ Rebuilding and protecting chutes, pumps, elbows, cyclones and other handling equipment under in dry service temperatures of -30°C to +105°C (-22°F to +221°F).



ITEM #	IDH #	DESCRIPTION	FORMAT
1860113	1860113	LOCTITE® FC Fast Cure Wearing Compound — Blue	25 lb. kit

PC 7218™

- ✓ A 2-part, ceramic-filled, trowelable, epoxy-based surface coating designed to protect parts from coarse particle abrasion or erosion on metals (with or without chemical attack).
- ✓ Designed for parts such as cyclones/separator bodies, dust collectors/exhausters, pump liners/impellers, fan blades and housings, chutes/hoppers and elbows/transition points.



ITEM #	IDH #	DESCRIPTION	FORMAT
1323940	1323940	LOCTITE® PC 7218™ Wearing Compound — Grey	25 lb. kit

PC 7226™

- ✓ A 2-part, carbide-filled, trowelable, non-sagging, epoxy-based surface coating for protecting processing equipment from fine particle abrasion (with or without chemical attack).
- ✓ It is suitable for overhead and vertical surfaces. Typical applications include dredge pump liners, flumes and troughs, pump impellers, vibrating feeders, and chutes/hoppers.



ITEM #	IDH #	DESCRIPTION	FORMAT
98383	209824	LOCTITE® PC 7226™ Pneu Wear — Grey	3 lb. kit

PC 6315 BK™

- ✓ Known as Big Foot™ Zero V.O.C.
- ✓ A 2-part, solvent-free epoxy which creates an extremely durable anti-slip coating that withstands heavy vehicular traffic on concrete, wood and metal surfaces in odour-sensitive areas, under typical dry service temperatures of -29°C to +60°C (-20°F to +140°F).
- ✓ Typical applications: heavy duty anti-slip finish where a solvent-free material is required.



ITEM #	IDH #	DESCRIPTION	FORMAT
1624641	1624641	LOCTITE® PC 6315™ BK Zero V.O.C — Black	1 gal kit

PIPE REPAIR KIT

- ✓ A urethane impregnated fiberglass tape, activated by water, for reliable, temporary repairs of metal, plastic, and composite pipes. Includes LOCTITE® EA 3463™ epoxy stick, LOCTITE® PC 5070™ urethane impregnated fiberglass tape, and gloves.
- ✓ Cures in 30 minutes.
- ✓ CFIA &/or Health Canada Listed.



ITEM #	IDH #	DESCRIPTION	FORMAT
96321	209818	LOCTITE® 209818 Pipe Repair Kit	2" x 6' tape
96322	269078		4" x 12' tape

EA 3463™

- ✓ A versatile, dual component, easy to use, steel-filled epoxy repair putty.
- ✓ 10-minute repair epoxy.
- ✓ This product stops leaks in pipes and tanks, fills oversized bolt holes, smoothes welds, and repairs non-structural defects in castings or holes in tanks.
- ✓ Temperature range of: -30°C to +121°C (-22°F to +250°F).



ITEM #	IDH #	DESCRIPTION	FORMAT
98853	826034	LOCTITE® EA 3463™ Metal Magic Steel™ — Grey	4 oz. stick

SURFACE PROTECTION CONCRETE REPAIR, GROUTING, & ANTI-SLIP COATINGS



EA 445™

- ✓ A 2-part, room temperature cure, epoxy adhesive paste used for high strength, permanent bonding of metals, ceramics, concrete, wood and most plastics. This product can withstand temperatures of up to +80°C (+180°F). Typical applications include the production, maintenance and prototype bonding of metals, ceramics, concrete, wood, glass and most plastics.



IDH #	IDH #	DESCRIPTION	FORMAT
21425	209717	LOCTITE® EA 445™ Fast Cure Epoxy Mixer Cups — Grey	can of 10-4 gram cups

PC 7227™ GY

- ✓ A 2-part, brushable, ultra smooth, ceramic-reinforced epoxy kit providing a high gloss, low friction coating.
- ✓ Typically used to provide a smooth, protective abrasion resistant coating and for repairing heat exchangers and condensers, lining tanks and chutes, resurfacing and repairing rudders and pintle housings and repairing cooling pump impellers and butterfly valves
- ✓ Kit, which is easy to mix and use.



ITEM #	IDH #	DESCRIPTION	FORMAT
98733	209826	LOCTITE® PC 7227™ GY Brushable Ceramic — Grey	2 lb. kit

PC 6231™

- ✓ A 2-part, rapid curing, polyurethane joint filler. It is a self-leveling, 100% solids, low viscosity, flexible system. For indoor, outdoor use. Applications include control joints or construction saw joints on horizontal concrete surfaces. Used for industrial floor applications receiving heavy vehicle traffic and exterior applications where minimal joint movement will occur. Repairs holes, spalls, and cracks in concrete, brick, block and masonry.



ITEM #	IDH #	DESCRIPTION	FORMAT
1291113	1291113	LOCTITE® PC 6231™ Crack Filler SL Self-Leveling — Grey	8.6 oz. coaxial cartridge
1093940	1093940	✓ Product comes with one nozzle. Note: Shake the tube well prior to use.	Manual Applicator
1100962	1100962		3/pk nozzles

PC 9410™

- ✓ A high strength, 2-part, rapid setting, liquid/paste magnesium phosphate-based concrete repair and grouting system that outperforms conventional concrete repairs.
- ✓ Typically used to patch damaged concrete on horizontal or vertical surfaces, used for indoor and outdoor applications.
- ✓ Applications with an operating range of -50°C to 1,100°C (-58°F to 2,012°F).
- ✓ **CFIA &/or Health Canada Listed.**



IDH #	IDH #	DESCRIPTION	FORMAT
95555	235573	LOCTITE® PC 9410™ Concrete Repair Material — Grey	5 gallon kit

PC 7228™

- ✓ A 2-part, white, ceramic-filled, brushable, self-levelling epoxy surface coating that creates a high gloss, low friction surface. Primarily it protects against fine particle abrasion and corrosion under dry service temperatures from -30°C to +95°C, (-22°F to +203°F).
- ✓ It also works well as a top coat over LOCTITE® wearing compounds for applications requiring surface rebuilding and lasting protection.



ITEM #	IDH #	DESCRIPTION	FORMAT
96443	209668	LOCTITE® PC 7228™ Brushable Ceramic — White	2 lb. kit

PC 7350™

- ✓ A rubber repair, 2-part, 100% solid, room temperature-curing polyurethane resin and isocyanate compound kit. Cures to a tough, resilient adhesive.
- ✓ **Typical applications:** rubber belting, repairing or rebuilding liners in mills, pumps, feeder bowls, hoppers, chutes, and repairing cast urethane screens and liners.



ITEM #	IDH #	DESCRIPTION	FORMAT
2073202	2073202	LOCTITE® PC 7350™ Conveyor Belt Repair — Black	400 ml cartridge
1372751	1372751		400 ml dual gun
243335	243335		6/pk nozzles