

High Voltage Differential Probe THDP0400 Model Datasheet



Key applications

- Floating differential measurements
- Power Semi Si, SiC, GaN Validation and Characterization
- Switching power supply design
- Industrial and automotive motor drive designs
- Power converter design and service

The Tektronix THDP0400 high voltage differential probe enables safe measurement of floating differential voltages up to ± 2000 V. It is well suited for testing IGBT, SiC, and GaN power devices, as well as applications such as motor drives and power converters.

The probe provides up to 400 MHz bandwidth with selectable attenuation settings, enabling accurate measurement of fast-switching signals in medium- to high-voltage differential applications.

The THDP0400 model includes a range of standard accessories to simplify connection to the device under test (DUT). Like all probes in the THDP series, it features the TekVPI® interface, allowing seamless connection to 4, 5, and 6 Series B MSO oscilloscopes for both manual and automated measurements.

Key features

- 400 MHz bandwidth for high-speed signal measurements
- Differential voltage range up to ± 2 kV
- Common-mode voltage up to ± 2 kV
- Selectable attenuation: 50X, 100X, 250X, 500X
- DC gain accuracy: $\pm 1\%$
- Switchable attenuation settings for measurement flexibility
- Safety certified as per UL 61010-031 and IEC 61010-031 standards
- CAT Rating: 1000 V CAT III

Specifications

All specifications are typical and apply to all models unless noted otherwise.

Probe overview

Characteristic	Description			
Bandwidth	400 MHz			
Probe range	2 kV: 500X	1 kV: 250X	400 V: 100X	200 V: 50X
Rise time	0.9 ns	0.9 ns	1 ns	1 ns
Noise (AC RMS)	265 mV	265 mV	225 mV	225 mV
Noise (AC RMS at 20 MHz)	55 mV	55 mV	45 mV	45 mV
DC balance (input referred)	±2 V	±1 V	±1 V	±500 mV
Max differential input voltage	±2000 V	±1000 V	±400 V	±200 V
DC gain accuracy	±1%			
Common mode voltage	±2000 Vpk			
CMRR	DC: 80 dB			
	100 kHz: 70 dB			
	1 MHz: 70 dB			
	10 MHz: 50 dB			
	50 MHz: 45 dB			
	100 MHz: 35 dB			
	400 MHz: 28 dB			
Input impedance	Each input to ground: 5 MΩ 5 pF			
	Differential input impedance: 10 MΩ 2.5 pF			
Cable length	2 meters			
CAT rating	1000V CAT III			
Supported oscilloscopes	4, 5, 6 Series B MSO			
Propagation delay	13 ns ±0.5 ns			

Environmental requirements

Characteristic	Operating	Non-operating
Temperature	0° C TO +50° C	-40°C TO +71°C
Humidity	80% relative humidity (% RH) at up to +31°C, decreasing linearly to 40% at +50°C. Units to be powered up at least 30 minutes prior to testing.	5% to 95% RH (Relative Humidity) at up to +40°C, noncondensing.
Altitude	Up to 3,000 meters	Up to 15,240 meters

Ordering information





Select the appropriate instrument and options for your measurement needs.

Model overview



Model	Description
THDP0400	400 MHz high voltage differential probe
THDP0400KIT	Standard accessory kit (includes items in standard accessory list)

Standard accessories

The following table lists the accessories that are shipped with the probe.



Accessory	Description	Part number
	Probe tip adapters; 4mm to 0.8mm, black (qty. 2)	013-0436-XX
	Spring tips; fine (qty. 4)	214-5586-XX
	Hook clamps; red and black (qty. 2)	344-0703-XX
	Rotating grip jaw clamps (qty. 2)	344-0704-XX

High Voltage Differential Probe THDP0400 Model Datasheet

Accessory	Description	Part number
	2-footed holder; black (qty. 2)	352-1192-XX
	Safety alligator clips; small (qty. 2)	344-0705-XX

Recommended accessories

The following table lists optional accessories.

Accessory	Description	Part number
	Transit hard case	016-2177-XX
	EMI noise suppression kit	276-0914-XX
	3D positioner with steel base, 200 mm span width and universal probe holder	352-1193-XX
	4 mm Coupler f-f (red), 30V AC / 60V DC	133-0698-XX
	BNC-male to dual 4 mm sockets, fully insulated	133-0699-XX

Tektronix is registered to ISO 9001:2015 and ISO 14001:2015.

Contact Information:

Australia 1 800 709 465
Austria* 00800 2255 4835
Balkans, Israel, South Africa and other ISE Countries +41 52 675 3777
Belgium* 00800 2255 4835
Brazil +55 (11) 3530-8901
Canada 1 800 833 9200
Central East Europe / Baltics +41 52 675 3777
Central Europe / Greece +41 52 675 3777
Denmark +45 80 88 1401
Finland +41 52 675 3777
France* 00800 2255 4835
Germany* 00800 2255 4835
Hong Kong 400 820 5835
India 000 800 650 1835
Indonesia 007 803 601 5249
Italy 00800 2255 4835
Japan 81(3) 6714 3086
Luxembourg +41 52 675 3777
Malaysia 1 800 22 55835
Mexico, Central/South America and Caribbean 52 (55) 88 69 35 25
Middle East, Asia, and North Africa +41 52 675 3777
The Netherlands* 00800 2255 4835
New Zealand 0800 800 238
Norway 800 16098
People's Republic of China 400 820 5835
Philippines 1 800 1601 0077
Poland +41 52 675 3777
Portugal 80 08 12370
Republic of Korea +82 2 565 1455
Russia / CIS +7 (495) 6647564
Singapore 800 6011 473
South Africa +41 52 675 3777
Spain* 00800 2255 4835
Sweden* 00800 2255 4835
Switzerland* 00800 2255 4835
Taiwan 886 (2) 2656 6688
Thailand 1 800 011 931
United Kingdom / Ireland* 00800 2255 4835
USA 1 800 833 9200
Vietnam 12060128

* European toll-free number. If not accessible, call: +41 52 675 3777

Find more valuable resources at [TEK.COM](https://www.tek.com)

Tektronix[®]

Copyright © Tektronix. All rights reserved. Tektronix products are covered by U.S. and foreign patents, issued and pending. Information in this publication supersedes that in all previously published material. Specification and price change privileges reserved. TEKTRONIX and TEK are registered trademarks of Tektronix, Inc. All other trade names referenced are the service marks, trademarks or registered trademarks of their respective companies.

51W-74235-0 6 April 2026