Agilent N9343C 13.6 GHz Handheld Spectrum Analyzer

If you are making measurements in the field, the Agilent N9343C handheld spectrum analyzer (HSA) makes your job easier. It's got the features you need for operating in tough field environments, and its measurement performance gives you confidence the job's been done right. The N9343C HSA let you automate routine tasks to save time and ensure consistent results. Field testing just got easier with the Agilent N9343C HSA.

Field testing just got easier



Get the features you need in a field-ready instrument:

- · Rugged and fanless design for tough field environments.
- · Clear screen viewing, day and night.
- · Built-in GPS receiver and GPS antenna.
- Dedicated applications for spectrum monitoring and interference analysis.
- Flexible remote control via USB/LAN.

Gain confidence in your measurements with benchtop performance in a handheld instrument:

- Best-in-class RF performance (-155 dBm/Hz DANL, minimum sweep time < 2 ms).
- Powerful one-button measurements, built-in tracking generator, AM/FM modulation analysis and time-gated sweep.
- High-accuracy power measurements with Agilent USB power sensors.

Innovative **task planner**: www.agilent.com/find/taskplanner slashes test setup time by 95%, delivers test automation and consistency, and makes it easy to captures test results, generate reports and share task plans with others.

Quick Fact Sheet

Key specifications

Specification	Description	
Frequency range	1 MHz to 13.6 GHz (tunable to 9 kHz	
Displayed average noise level (DANL) @ 3 GHz/ 7 GHz/13 GHz, normalized to 1 Hz, typical	-142 dBm/-142 dBm/-140 dBm, PA OFF	
	-154 dBm/-155 dBm/-155 dBm, PA ON	
RBW range	10 Hz to 3 MHz (1-3-10 steps)	
TOI @ 12 GHz, typical	+12 dBm	
Phase noise, typical	-89 dBc/Hz @ 30 kHz	
	-119 dBc/Hz @ 1 MHz	
Sweep speed	2 ms to 1000 s	
	6 μs to 200 s	
Amplitude accuracy, typical	± 0.6 dB	
Dimension	318 mm x 207 mm x 69 mm (12.5 inch x 8.15 inch x 2.7 inch)	
Weight	3.2 kg (7 lbs)	
Battery	3.5 hours, field replaceable	

Option

ltem	Description	Upgradability	MSRP
N9343C	Handheld Spectrum analyzer, 1 MHz to 13.6 GHz	N/A	\$16,978
P13	Preamplifier, 13.6 GHz	Yes, license	\$1,446
TG7	Tracking generator, 7 GHz	Yes, H/W+ license	\$2,479
SIM	Spectrum monitor with spectrogram record and playback	Yes, license	\$1,653
GPS	GPS receiver with built-in GPS antenna	Yes, license	\$615
TPN	Task planner for test automation	Yes, license	\$1,240
PWM	USB power sensor support	Yes, license	\$594
SEC	Secure erase of user data	Yes, license	\$208
TMG	Time-gated spectrum analysis	Yes, license	\$834
AMA	AM/FM modulation analysis	Yes, license	\$618

N9311X-518 directional antenna N9343C-SCC ergonomic backpack N9343C-BCG external battery charger* * Batteries not included. N9343C-BAT spare battery pack

Powerful measurement features



Built-in GPS receiver and GPS antenna (option GPS)



Measuring two-port transmission with tracking generator (option TG7)




Spectrum Monitor (option SIM)



Erase user memory for security purpose (option SEC)




Agilent U2000 Series USB power sensor support (option PWM)



AM/FM modulation analysis (option AMA)



Task planner for routine test automation (option TPN)



Time-gated spectrum analysis (option TMG)

More accessories at www.agilent.com/find/n9311X

Standard shipped items

Automotive 12V DC charger

- N9343C HSA
- · RoHS addendum
- USB cable
- Help kit CD
- · Battery Li-Ion
- · Ear phone
- Power supply AC/DC
- Quick start tutorial



N9343C-1TC

Hard transit case

Recommended service options

Additional two years of Return-to-Agilent warranty
Additional two years of Return-to-Agilent calibrations
For more information go to www.agilent.com/find/removealIdoubt

Technical data, availability and pricing subject to change without notice. © Agilent Technologies, Inc. 2011, Printed in USA, February 16, 2011 5990-7429ENDI