

Bay Area AQMD Motor Vehicle and Mobile Equipment Coating Operations Regulation 8 Rule 45 Amended: 12/3/2008 | In Effect: 1/1/2010



| Coating Category | Ibs/U.S. gal (g/L) Limit: VOC Regulatory (Less Water Less Exempts). | | |
|----------------------------|---|--|--|
| Solvent (Surface Cleaner)* | 0.21 (25) | | |
| Pretreatment Coating | 5.5 (660) | | |
| Primer / Primer Surfacer | 2.1 (250) | | |
| Primer Sealer | 2.1 (250) | | |
| Single Stage Coating | 2.8 (340) | | |
| Color Coating | 3.5 (420) | | |
| Underbody Coating | 3.6 (430) | | |
| Clear Coating | 2.1 (250) | | |
| Uniform Finish Coating | 4.5 (540) | | |
| Adhesion Promoter | 4.5 (540) | *VOC content applies to this category only | |

| Product Code & Name | Hardener/ Activator | Reducer | Mix Ratio | VOC Content |
|---|------------------------|---------|-----------|------------------------------|
| Solvent (Surface Cleaner) | | | | Limit: 0.21 lbs/gal (25 g/L) |
| SWX350 H ₂ O-SO-CLEAN [®] Wax & Grease Remover | - | - | - | 0.17 (20) |
| SX1009 2.9 VOC Bug and Tar Remover* | * | * | * | 2.89 (345) |
| *Allowed only as bug and tar remover under low usage limit. See 8-45-308.5 for details. | | | | |

| Product Code & Name | Hardener/Activator | Reducer | Additives | Mix Ratio | Applied VOC Less Water Less Exempt |
|--|-----------------------------|-----------------------------|-------------------|------------------|---------------------------------------|
| Pre-Treatment Coatings | | | | Lim | it: 5.5 lbs/gal (660 g/L) |
| SX1071 ECOBASE [®] 5.5 Etch Prime | SX1072 | - | - | 1:1 | 5.48 (657) |
| SXA1031 Etch Primer - Gray | - | - | - | Aerosol | N/A |
| Primer Surfacer | | | | Lir | nit 2.1 lbs/gal (250 g/L) |
| MP80x 2.1 VOC Multi-Purpose Primer | MH810 | MR29x | - | 4:1:2 | 1.96 (236) |
| MP871 2.1 VOC Epoxy Primer | MP875 | MR29x | - | 2:1:1 | 2.07 (248) |
| MP243 Polyester Primer | MEKP (MX199) | - | - | 1 tube/qt | 1.64 (196) |
| Primer Sealer (apply over previously coat | ed surfaces) | | | Lim | it: 2.1 lbs/gal (250 g/L) |
| MP80X Multi-Purpose Primer | MH810 | MR29X | MC262 or MC770 | 3:1:1:1 | 2.02 (242) |
| MP871 2.1 VOC Epoxy Primer | MP875 | MR29X | - | 2:2:1 | 2.07 (248) |
| MP89x 2.1 VOC Urethane Sealers | MH810 | MR29x | - | 4:1:1 | 2.01 (241) |
| Single Stage Coating | | | | Lim | it: 2.8 lbs/gal (340 g/L) |
| MLX 2.8 VOC Acrylic Enamel | MH238 | MR29x | - | 4:1:1 | 2.76 (331) |
| MTX 2.8 VOC Single Stage | MH238 | MR29x | - | 4:1:2 | 2.80 (336) |
| Basecoat for Multi Stage Topcoat System | | | | Lim | it: 3.5 lbs/gal (420 g/L) |
| MBX OMNI® 3.5 VOC Acrylic Basecoat | - | MR29x | - | 1:1 | 3.5 (419) |
| Use MBPX blend to | spray mix recommendation w | vithout MH238 only with co | olor formulas th | nat contain M799 | |
| MBPX Omni Plus 3.5 Basecoat | - | MR29x | - | 1:1 | 3.48 (417) |
| Use MBPX blend to sp | oray mix recommendations wi | ith MH238 with all historic | color formulas | that contain M7 | 36 |
| MBPX Omni Plus 3.5 Basecoat | MH238 | MR29x | - | 10:1:10 | 3.48 (417) |
| MBPX Omni Plus 3.5 Basecoat | MH238 | MR29x | - | 10:1:5 | 3.48 (417) |



Bay Area AQMD Motor Vehicle and Mobile Equipment Coating Operations Regulation 8 Rule 45 Amended: 12/3/2008 | In Effect: 1/1/2010



| Product Code & Name | Hardener/Activator | Reducer | Additives | Mix Ratio | Applied VOC Less Water Less Exempt |
|--|---------------------------|--------------|-----------|-----------|---------------------------------------|
| Clear Coating | | | | Limi | t: 2.1 lbs/gal (250 g/L) |
| MC262 Omni 2.1 VOC 4+1 Urethane Clear | MH266, MH267 | - | - | 4:1 | 2.08 (249) |
| MC730 2.1 VOC Production Clear | MH737, MH738, MH739 | MR295, MR296 | - | 4:1:0.5 | 2.08 (249) |
| MC760 2.1 VOC Universal Clear | MH267, MH268 | MR295, MR296 | - | 4:1:1 | 2.08 (249) |
| MC2910 2.1 VOC EUROPLUS [®] Multi- Panel Clearcoat | MH2918, MH2919 | - | - | 2:1 | 1.95 (234) |
| MC2980 2.1 VOC Europlus Clear | MH2981, MH2982, MH2983 | - | - | 2:1 | 2.08 (249) |

| Additional Products (listing not intended to be all inclusive) | | | | |
|--|---|--|--|--|
| SLV4985 Universal Flattening Agent | SU4901 Clean and Scuff Sponge | SXA1044 High Build Flexible Surfacer (Aerosol) | | |
| SLV73 Fisheye Eliminator | SUA4903 Advanced Plastic Bond (Aerosol) | SXA1050 Plastic Adhesion Promoter (Aerosol) | | |
| SLV814 Universal Flexibilizer | SWX100 Waterborne Gun Cleaner | SX1047 High Build WB Flexible Surfacer | | |
| SLV840 Uniform Finish Blender | SXA840 Uniform Finish Blender (Aerosol) | SU470LV 1K Compliant Adhesion Promoter | | |
| SLV898 Retarder | SXA1030 Black Guide Coat (Aerosol) | SXA1041 Bumper Black (Aerosol) | | |

This "Bay Area AQMD Rule 8-45 (PPG OMNI)" wall chart is intended to provide INFORMATION to PPG's customers. In providing this wall chart, PPG makes no separate or additional warranties, express or implied, and assumes no liability or responsibility arising out of its use. It is the responsibility of each customer, RE-SELLER AND END USER of PPG's products to independently ascertain that their practices are legal, appropriate and constitute sound product stewardship. This "Bay Area AQMD Rule 8-45 (PPG OMNI)" wall chart does not include all currently compliant OMNI products. The representative products listed are compliant with Rule 8-45 VOC limits as of the date of this wall chart; however, subsequent changes in Rule 8-45 may change the compliance status of the listed products. It is the responsibility of the end user to review and comply with current regulations, including applicable coating category VOC limits, as of the date of product purchase and/or use. This document is not INTENDED to define or create legal rights or obligations. It is the responsibility of each customer, RE-SELLER AND END USER to comply with all applicable federal, state and local laws.