

Santa Barbara County APCD Motor Vehicle and Mobile Equipment Coating Operations Rule 339

Amended: 06/19/2008 | In Effect: 01/01/2010

| Coating Category | lbs/gal (g/L) | | Limit:VOC Regulatory (Less Water Less Exempts) | | | |
|--|------------------------|--------------------------|--|---|------------------------------------|--|
| Solvent (Surface Cleaner) | 0.21 (25)* | | * VOC content applies to this category only | | | |
| Pretreatments Coating | | 5 (660) | To be contained applied to this category only | | | |
| Primer/Primer Surfacer | | l (250) | | | | |
| Primer Sealer | | l (250) | | | | |
| Single-Stage Coating | | 3 (340) | | | | |
| Color Coating | | 5 (420) | | | | |
| Clear Coating | | I (250) | 1 | | | |
| Uniform Finish Coating | | 5 (540) | | | | |
| Adhesion Promoter | 4.5 | 5 (540) | | | | |
| Product Code & Name | | | Reducer | Mix Ratio | VOC Content | |
| Solvent (Substrate Cleaner) | | | | Limit: 0.21 | lbs/gal (25 g/L) | |
| CFX435LV - Low VOC Cleaner | | | Water | 1:1 | 0.20 (25) | |
| SWX350 H2O-SO-CLEAN® Wax and Grease Remover | | | - | - | 0.17 (20) | |
| SX1009 2.9 VOC Bug and Tar Remover* | | | _ | _ | 2.89 (346) | |
| • | | | | ا الحدد المامين | ` ' | |
| *Section B. 8 - Maximum 20gal/yr/facil | ity with a maxim | ium VOC content of | 6.5 lbs/gai allov | vea with record keeping re | , . | |
| Product Code & Name | | Hardener/ Activator | Reducer | Mix Ratio | Applied VOC Less Water Less Exempt | |
| Pretreatment Coating | | | | Limit: 5.5 | lbs/gal (660 g/L) | |
| F4945 5.5 VOC Wash Primer | | F4946 | - | 1:1 | 5.32 (637) | |
| SXA1031 Etch Primer – Gray | | - | - | Aerosol | N/A | |
| Product Code & Name | Hardener/ Activator | Additives | Reducer | Mix Ratio | Applied VOC Less Water Less Exempt | |
| Primer/Primer Surfacer | | | | Limit: 2.1 | lbs/gal (250 g/L) | |
| ESU410 2.1/2.8 Polyurethane Primer | ESU419 | ESX590 | - | 5:1+6 oz / RTS gal | 1.99 (238) | |
| ESU470 2.1 VOC Wet on Wet Epoxy Primer - Gray | ESU479 | - | ESR300 or ESR310 | 2:1:1 or 2:1:2 (reducer last) | 2.07 (248) | |
| ESU480/481/482 2.1 VOC Epoxy Primer | ESU489 | - | - | 4 : 1 | 2.09 (250) | |
| F3970/BK/WH Ultra High Solids Primer | F3971 | F3400 or F3405 | F3385, F3390 or F3395 | 3:1 + 6 oz / RTS gal + 10% optional reducer | 2.07 (248) | |
| F3998 2.1 VOC Primer Surfacer | F3999 | - | - | 2:1 | 1.99 (238) | |
| F4921/BK/WH 2.1 VOC Epoxy Primer | F4922 | - | F3385, F3390 or F3395 | 3:1:1 | 2.05 (246) | |
| F4932/BK/WH 2.1 VOC Fast Dry Urethane Surfacer | F4933 | - | F3385, F3390 or F3395 | 4:1:1 | 2.08 (249) | |
| F4935/36/37 High Solids Epoxy Primers | F4938 | - | - | 1:1 | 2.08 (249) | |
| Single-Stage Coating | | | | Limit: 2.8 | lbs/gal (340 g/L) | |
| ESSS Single Stage Polyurethane Enamel | ESH200 | ESX5XX | - | 6 : 1 :1 | 2.76 (331) | |
| FDGU Single Stage Ultra high Solids Polyurethane Enamel | F3260 | F3400, F3405 or F3410 | F3385, F3390 or F3395 | 3:1+6 oz /RTS gal + 10% reducer | 2.82 (338) | |
| FDSU Ultra HS Polyurethane Single Stage | F3260 | F3400, F3405 or F3410 | F3385, F3390 or F3395 | 3:1+6 oz /RTS gal + 10% reducer | 2.82 (338) | |



Santa Barbara County APCD

Motor Vehicle and Mobile Equipment Coating Operations Rule 339

Amended: 06/19/2008 | In Effect: 01/01/2010



| Product Code & Name | Hardener/ Activator | Additives | Reducer | Mix Ratio | Applied VOC Less Water Less Exempt | | | |
|---|-------------------------------|--------------------------|---|--|------------------------------------|--|--|--|
| Color Coating | | | | Limit: 3.5 | lbs/gal (420 g/L) | | | |
| ESSS Basecoat Polyurethane Basecoat | ESH210 | ESB800 | - | 2:1:1 | 3.04 (364) | | | |
| FBCH High Solids Polyurethane Basecoat | F3200, F3259 or F3260 | F3440, F3441 or F3442 | - | 3:1:1 | 3.47 (416) | | | |
| FBCS High Solids Basecoat - Fast | F3200 or F3260- | - | F3385 | 3 : 1 + 10% | 3.04 (364) | | | |
| FBCS High Solids Basecoat - Fast | F3200 or F3260- | - | F3330, F3340, F3350 or F3360 | 3:1+10% | 3.41 (409) | | | |
| Product Code & Name | Hardener/ Activator | Additives | Reducer | Mix Ratio | Applied VOC Less Water Less Exempt | | | |
| Clear Coating Limit: 2.1 lbs/gal (250 g/L) | | | | | | | | |
| ESC621 2.1 VOC Clearcoat | ESH200 | - | ESX711, ESX721, ESR300 or ESR310 | 4:1:1 | 2.06 (247) | | | |
| F3921 2.1 VOC Clearcoat | F3210 or F3211 | - | F3385, F3390 or F3395 | 3:1:1/2 | 2.05 (246) | | | |
| Additional Products: (listing not intended to be all inclusive) | | | | | | | | |
| FBCH500 FBCH Blending Clear | SLV73 Fisheye Eliminator | | | SUA4903 Advanced Plastic Bond SXA840 Blending Solvent | | | | |
| FDGU500 FDGU Blending Clear | SU4901 Clean and Scuff Sponge | | | SARO40 DIEHUING SOIVERIL | | | | |

Santa Barbara County APCD Rule 339 – PPG DELFLEET® Evolution and DELFLEET ESSENTIAL®

This "Santa Barbara County APCD Rule 339 (PPG *Delfleet*)" wall chart is intended to provide INFORMATION to PPG's customers. In providing this wall chart, PPG makes no separate or additional warranties, express or implied, and assumes no liability or responsibility arising out of its use. It is the responsibility of each customer, RE-SELLER AND END USER of PPG's products to independently ascertain that their practices are legal, appropriate and constitute sound product stewardship. This "Santa Barbara County APCD Rule 339 (PPG *Delfleet*)" wall chart does not include all currently compliant *Delfleet* products. The representative products listed are compliant with Santa Barbara County APCD Rule 339 VOC limits as of the date of this wall chart; however, subsequent changes in Santa Barbara County APCD Rule 339 may change the compliance status of the listed products. It is the responsibility of the end user to review and comply with current regulations, including applicable coating category VOC limits, as of the date of product purchase and/or use. This document is not INTENDED to define or create legal rights or obligations. It is the responsibility of each customer, RE-SELLER AND END USER to comply with all applicable federal, state and local laws.



PPG Industries, Inc. Commercial Coatings 19699 Progress Drive Strongsville, OH 44149 1-800-647-6050

PPG Canada Inc. 2301 Royal Windsor Drive, Unit #6 Mississauga, Ontario L5J 1K5 1-888-310-4762