

## **Feather River AQMD**

Motor Vehicle and Mobile Equipment Coating Operations
Rule 3.19
Amended: 8/1/2016 | In Effect: 8/1/2017

**ENVIROBASE®** HIGH PERFORMANCE

| Coating Category           | Ibs./U.S. gal (g/L) Limit: VOC Regulatory (Less Water Less Exempts). |                                                   |  |
|----------------------------|----------------------------------------------------------------------|---------------------------------------------------|--|
| Solvent (Surface Cleaner)* | 0.21 (25)                                                            |                                                   |  |
| Pretreatment Coating       | 5.5 (660)                                                            |                                                   |  |
| Primer / Primer Surfacer   | 2.1 (250)                                                            |                                                   |  |
| Primer Sealer              | 2.1 (250)                                                            |                                                   |  |
| Single Stage Coating       | 2.8 (340)                                                            |                                                   |  |
| Color Coating              | 3.5 (420)                                                            |                                                   |  |
| Underbody Coating          | 3.6 (430)                                                            |                                                   |  |
| Clear Coating              | 2.1 (250)                                                            |                                                   |  |
| Uniform Finish Coating     | 4.5 (540)                                                            |                                                   |  |
| Adhesion Promoter          | 4.5 (540)                                                            | *VOC content value applies to this category only. |  |

| Product Code & Name                                                | Hardener/<br>Activator | Reducer | Mix Ratio | VOC Content                  |
|--------------------------------------------------------------------|------------------------|---------|-----------|------------------------------|
| Solvent (Surface Cleaner)                                          |                        |         |           | Limit: 0.21 lbs/gal (25 g/L) |
| SWX350 H <sub>2</sub> O-SO-CLEAN <sup>®</sup> Wax & Grease Remover | -                      | -       | -         | 0.17 (20)                    |
| SX1009 2.9 VOC Bug & Tar Remover*                                  | -                      | -       | -         | 2.89 (346)                   |
| *Allowed only as bug & tar remover Rule 3.14 A.4.g                 |                        |         |           |                              |

| Product Code & Name                         | Hardener/Activator | Reducer              | Additives | Mix Ratio   | Applied VOC<br>Less Water Less Exempt |
|---------------------------------------------|--------------------|----------------------|-----------|-------------|---------------------------------------|
| Pre-Treatment Coatings                      |                    |                      |           | Limi        | t: 5.5 lbs/gal (660 g/L)              |
| SX1071 ECOBASE <sup>®</sup> 5.5 Etch Prime  | SX1072             | -                    | -         | 1:1         | 5.48 (657)                            |
| SXA1031 Etch Primer - Gray                  | -                  | -                    | -         | Aerosol     | N/A                                   |
| Primer Surfacer                             |                    |                      |           | Lim         | it 2.1 lbs/gal (250 g/L)              |
| ECP1X A-Chromatic Surfacer                  | EH391              | D8764, D8774, D8767  | -         | 4:1:1       | 2.08 (249)                            |
| ECP1X A-Chromatic Surfacer                  | EH391              | D8764, D8774, D8767  | -         | 4:1         | 2.08 (249)                            |
| ECP1X A-Chromatic Surfacer                  | EH391              | D8764, D8774, D8767  | SL93LV    | 4:1:1 + 10% | 2.09 (250)                            |
| DPLV 2.1 Epoxy Primer                       | DP401LV            | D8764, D8774, D8767  | -         | 2:1:1       | 2.09 (250)                            |
| EPW115 Waterborne Speed Prime               | -                  | T494                 | -         | 1:13%       | 0.72 (86)                             |
| Primer Sealer (apply over previously coated | d surfaces)        |                      |           | Limi        | t: 2.1 lbs/gal (250 g/L)              |
| ECS2X A-Chromatic LV Sealer                 | EH391, EH392       | D8764, D8774, D8767  | -         | 4:1:1       | 2.05 (246)                            |
| ECS8X A-Chromatic LV Sealer                 | EH391, EH392       | ECRXX, D87XX, DT18XX | -         | 4:1:1       | 2.07 (248)                            |
| Single Stage Coating                        |                    |                      |           | Limi        | t: 2.8 lbs/gal (340 g/L)              |
| ENVIROBASE® Interior System                 | T584               | T494                 | -         | 100:15:15   | 2.79 (334)                            |
| Basecoat for Multi Stage Topcoat System     |                    |                      |           | Limi        | t: 3.5 lbs/gal (420 g/L)              |
| Envirobase High Performance Basecoat        | -                  | T494                 | -         | 100:10      | 3.33 (399)                            |
| Envirobase High Performance Basecoat        | -                  | T494                 | -         | 100:20      | 3.38 (405)                            |
| Envirobase High Performance Basecoat        | -                  | T494                 | -         | 100:30      | 3.50 (420)                            |
| Envirobase High Performance Basecoat        | -                  | -                    | T492      | 100:10      | 2.78 (333)                            |
| Envirobase High Performance Basecoat        | -                  | T494                 | T492      | 100:10:10   | 3.24 (388)                            |
| Envirobase High Performance Basecoat        | -                  | T494                 | T492      | 100:20:10   | 3.28 (393)                            |
| Envirobase High Performance Basecoat        | -                  | T494                 | T492      | 100:30:10   | 3.28 (393)                            |
| Envirobase High Performance Basecoat        | T493               | T494                 | T492      | 100:5:10:10 | 3.21 (385)                            |
| Envirobase High Performance Basecoat        | T493               | T494                 | T492      | 100:5:20:10 | 3.24 (388)                            |

© 2019 PPG Industries EUVOCWAL FRAQMD EHP (8/19)



## **Feather River AQMD**

Motor Vehicle and Mobile Equipment Coating Operations Rule 3.19

ENVIROBASE®

Amended: 8/1/2016 | In Effect: 8/1/2017

| Product Code & Name                                      | Hardener/Activator           | Reducer                     | Additives | Mix Ratio      | Applied VOC<br>Less Water Less Exempt |
|----------------------------------------------------------|------------------------------|-----------------------------|-----------|----------------|---------------------------------------|
| Basecoat for Multi Stage Topcoat System                  | Continued                    |                             |           | Lim            | it: 3.5 lbs/gal (420 g/L)             |
| Envirobase High Performance Basecoat                     | T493                         | T494                        | T492      | 100:5:30:10    | 3.25 (389)                            |
| Envirobase High Performance Basecoat                     | T493                         | -                           | T492      | 100:5:10       | 2.81 (337)                            |
| Underbody Coatings (Specialty)                           |                              |                             |           | Limi           | it: 3.6 lbs/gal (430 g/L)             |
| Internal Repair System                                   | T581                         | T494                        | -         | 100:15:15      | 3.08 (369)                            |
| Internal Repair System                                   | T581                         | T494                        | -         | 100:15:20      | 3.09 (370)                            |
| Clearcoat for Multi Stage Topcoat System                 |                              |                             |           | Limi           | it: 2.1 lbs/gal (250 g/L)             |
| D8126 CERAMICLEAR®                                       | D8226                        | -                           | -         | 2:1            | 2.00 (240)                            |
| D8188 Glamour LV Clearcoat                               | D8382, D8383<br>D8384, D8385 | D8767                       | -         | 3:1:10%        | 2.05 (246)                            |
| DC4010 Velocity Premium Clear                            | DCH36X0                      | -                           | -         | 4:1            | 2.05 (246)                            |
| DC4125 Ceramiclear                                       | DCH4126                      | -                           | -         | 2:1            | 2.05 (246)                            |
| EC520 <b>En-V</b> <sup>®</sup> High Production Clearcoat | ECH5075                      | ECRXX                       | -         | 3:1:1          | 2.07 (248)                            |
| EC530 <i>En-V</i> Performance Clearcoat                  | ECH5075                      | ECRXX                       | -         | 3:1:1          | 1.94 (232)                            |
| EC550 <i>En-V</i> Ultra Gloss Clearcoat                  | ECH5075                      | ECRXX                       | -         | 3:1:1          | 2.01 (241)                            |
| EC700 ONE VISIT® Production Clear                        | ECH7070, 7080, 7090          | -                           | -         | 4:1            | 2.08 (249)                            |
| EC700 One Visit Production Clear                         | ECH7070, 7080, 7090          | D87XX                       | SL93LV    | 4:0.5:1:2%     | 2.09 (250)                            |
| EC750 One Visit Appearance Clear                         | ECH7070, 7080, 7090          | -                           | -         | 4:1            | 2.08 (249)                            |
| EC800 Ultra Fast 2.1 Clearcoat                           | ECH8075<br>ECH8075           | D8767, DT1855<br>ECA83      |           | 4:1:1<br>4:1:1 | 2.08 (249)<br>1.90 (228)              |
| ECW8186 Waterborne Clearcoat                             | EHW8224                      | T494                        | -         | 5:2:2          | 2.09 (250)                            |
| VC5250 DITZLER <sup>®</sup> Satin Clear                  | VH7250                       | DT18XX, D87XX,<br>P850-1775 | -         | 4:1:1.5        | 1.85 (222)                            |
| VC5700 Ditzler Custom Clear                              | VH7780, VH7795               | DT1855, D8767,<br>P850-1775 | -         | 2:1:1          | 2.08 (249)                            |

| Additional Products (listing not intended to be all inclusive) |                                         |                                                |  |  |
|----------------------------------------------------------------|-----------------------------------------|------------------------------------------------|--|--|
| SLV4985 Universal Flattening Agent                             | SU4901 Clean and Scuff Sponge           | SXA1044 High Build Flexible Surfacer (Aerosol) |  |  |
| SLV73 Fisheye Eliminator                                       | SUA4903 Advanced Plastic Bond (Aerosol) | SXA1050 Plastic Adhesion Promoter (Aerosol)    |  |  |
| SLV814 Universal Flexibilizer                                  | SWX100 Waterborne Gun Cleaner           | SX1047 High Build WB Flexible Surfacer         |  |  |
| SLV840 Uniform Finish Blender                                  | SXA840 Uniform Finish Blender (Aerosol) | SXA1041 Bumper Black (Aerosol)                 |  |  |
| SLV898 Retarder                                                | SXA1030 Black Guide Coat (Aerosol)      | SU470LV 1K Compliant Adhesion Promoter         |  |  |

This "Feather River AQMD Rule 3.19 PPG Envirobase High Performance" wall chart is intended to provide INFORMATION to PPG's customers. In providing this wall chart, PPG makes no separate or additional warranties, express or implied, and assumes no liability or responsibility arising out of its use. It is the responsibility of each customer, RE-SELLER AND END USER of PPG's products to independently ascertain that their practices are legal, appropriate and constitute sound product stewardship. This "Feather River AQMD Rule 3.19 PPG Envirobase High Performance" wall chart does not include all currently compliant PPG Envirobase High Performance products. The representative products listed are compliant with Feather River AQMD Rule 3.19 VOC limits as of the date of this wall chart; however, subsequent changes in Feather River AQMD Rule 3.19 may change the compliance status of the listed products. It is the responsibility of the end user to review and comply with current regulations, including applicable coating category VOC limits, as of the date of product purchase and/or use. This document is not INTENDED to define or create legal rights or obligations. It is the responsibility of each customer, RE-SELLER AND END USER to comply with all applicable federal, state and local laws.

The PPG logo, Envirobase, Ecobase, En-V, Ditzler, CeramiClear, One Visit and  $H_2$ O-So-Clean are trademarks of PPG Industries of Ohio, Inc.

© 2019 PPG Industries EUVOCWAL FRAQMD EHP (8/19)