

State of Delaware

Mobile Equipment Repair and Refinishing **Title 7 Regulation 1124 Section 11.0**Amended: 10/11/2010 | In Effect: 1/1/2012



Coating Category	Ibs/U.S. gal (g/L) Limit: VOC Regulatory (Less Water Less Exempts).		
Solvent (Surface Cleaner)*	0.21 (25)		
Pretreatment Coating	5.5 (660)		
Primer / Primer Surfacer	2.1 (250)		
Primer Sealer	2.1 (250)		
Single Stage Coating	2.8 (340)		
Color Coating	3.5 (420)		
Underbody Coating	3.6 (430)		
Clear Coating	2.1 (250)		
Adhesion Promoter	4.5 (540)	*VOC content applies to this category only	

Product Code & Name	Hardener/ Activator	Reducer	Mix Ratio	VOC Content	
Solvent (Surface Cleaner) Limit: 0.21 lbs/gal (25 g/L					
SWX350 H ₂ O-SO-CLEAN [®] Wax and Grease Remover	-	-	-	0.17 (20)	
SX1009 2.9 VOC Bug and Tar Remover*	-	-	-	2.89 (346)	
*11.3.2.1 Special cleaning solvent for use in specific and difficult clear	ning tasks associated wit	h surface preparation with	VOC content no greater than 35	i0 g/L may be used at a volume	

*11.3.2.1 Special cleaning solvent for use in specific and difficult cleaning tasks associated with surface preparation with VOC content no greater than 350 g/L may be used at a volume equal to 2.5% of the preceding year's annual coating usage up to a maximum of 40 gallons per year.

Pre-Treatment Coatings SX1071 ECOBASE® 5.5 Etch Prime SXA1031 Etch Primer - Gray Primer Surfacer	SX1072 -	-	-	1:1 Aerosol	t: 5.5 lbs/gal (660 g/L) 5.48 (657)
SXA1031 Etch Primer - Gray Primer Surfacer	-	-	-		5.48 (657)
Primer Surfacer	-	-	-	Aorocal	
				AGIOSOI	N/A
				Lim	nit 2.1 lbs/gal (250 g/L)
MP80x 2.1 VOC Multi-Purpose Primer	MH810	MR29x	-	4:1:2	1.96 (236)
MP871 2.1 VOC Epoxy Primer	MP875	MR29x	-	2:1:1	2.07 (248)
MP243 Polyester Primer	MEKP (MX199)	-	-	1 tube/qt	1.64 (196)
Primer Sealer (apply over previously coated	l surfaces)			Limi	it: 2.1 lbs/gal (250 g/L)
MP80X Multi-Purpose Primer	MH810	MR29X	MC262 or MC770	3:1:1:1	2.02 (242)
MP871 2.1 VOC Epoxy Primer	MP875	MR29X	-	2:2:1	2.07 (248)
MP89x 2.1 VOC Urethane Sealers	MH810	MR29x	-	4:1:1	2.01 (241)
Single Stage Coating				Limi	it: 2.8 lbs/gal (340 g/L)
MLX 2.8 VOC Acrylic Enamel	MH238	MR29x	-	4:1:1	2.76 (331)
MTX 2.8 VOC Single Stage	MH238	MR29x	-	4:1:2	2.80 (336)
Basecoat for Multi Stage Topcoat System				Limi	it: 3.5 lbs/gal (420 g/L)
MBX OMNI® 3.5 VOC Acrylic Basecoat	-	MR29x	-	1:1	3.5 (419)
Use MBPX blend to spray mix recommendation without MH238 only with color formulas that contain M799					
MBPX <i>Omni</i> Plus 3.5 Basecoat	•	MR29x	-	1:1	3.48 (417)
Use MBPX blend to spray mix recommendations with MH238 with all historic color formulas that contain M736					
MBPX Omni Plus 3.5 Basecoat	MH238	MR29x	-	10:1:10	3.48 (417)
MBPX Omni Plus 3.5 Basecoat	MH238	MR29x	-	10:1:5	3.48 (417)

VOC DEL OMNI (5/19)



State of Delaware

Mobile Equipment Repair and Refinishing **Title 7 Regulation 1124 Section 11.0**Amended: 10/11/2010 | In Effect: 1/1/2012



Product Code & Name	Hardener/Activator	Reducer	Additives	Mix Ratio	Applied VOC Less Water Less Exempt
Clear Coating				Limit: 2.1 lbs/gal (250 g/L)	
MC262 Omni 2.1 VOC 4+1 Urethane Clear	MH266, MH267	-	-	4:1	2.08 (249)
MC730 2.1 VOC Production Clear	MH737, MH738, MH739	MR295, MR296	-	4:1:0.5	2.08 (249)
MC760 2.1 VOC Universal Clear	MH267, MH268	MR295, MR296	-	4:1:1	2.08 (249)
MC2910 2.1 VOC EUROPLUS® Multi- Panel Clearcoat	MH2918, MH2919	-	-	2:1	1.95 (234)
MC2980 2.1 VOC Europlus Clear	MH2981, MH2982, MH2983	-	-	2:1	2.08 (249)

Additional Products (listing not intended to be all inclusive)				
SLV4985 Universal Flattening Agent	SU4901 Clean and Scuff Sponge	SXA1044 High Build Flexible Surfacer (Aerosol)		
SLV73 Fisheye Eliminator	SUA4903 Advanced Plastic Bond (Aerosol)	SXA1050 Plastic Adhesion Promoter (Aerosol)		
SLV814 Universal Flexibilizer	SWX100 Waterborne Gun Cleaner	SX1047 High Build WB Flexible Surfacer		
SLV840 Uniform Finish Blender	SXA840 Uniform Finish Blender (Aerosol)			
SLV898 Retarder	SXA1030 Black Guide Coat (Aerosol)			
SU470LV 1K Compliant Adhesion Promoter	SXA1041 Bumper Black (Aerosol)			

This "State of Delaware Title 7 Regulation 1124 Section 11.0 (PPG *OMNI*)" wall chart is intended to provide INFORMATION to PPG's customers. In providing this wall chart, PPG makes no separate or additional warranties, express or implied, and assumes no liability or responsibility arising out of its use. It is the responsibility of each customer, RE-SELLER AND END USER of PPG's products to independently ascertain that their practices are legal, appropriate and constitute sound product stewardship. This "State of Delaware Title 7 Regulation 11.0 (PPG *OMNI*)" wall chart does not include all currently compliant OMNI products. The representative products listed are compliant with Title 7 Regulation 11.24 Section 11.0 VOC limits as of the date of this wall chart; however, subsequent changes in Title 7 Regulation 1124 Section 11.0 voc implications and comply with current regulations, including applicable coating category VOC limits, as of the date of product purchase and/or use. This document is not INTENDED to define or create legal rights or obligations. It is the responsibility of each customer, RE-SELLER AND END USER to comply with all applicable federal, state and local laws.