

## Ventura County APCD Motor Vehicle and Mobile Equipment Coating Operations Rule 74.18 Amended: 11/11/2008 | In Effect: 1/1/2010



| Coating Category           | Ibs/U.S. gal (g/L) Limit: VOC Regulatory (Less Water Less Exempts). |  |  |
|----------------------------|---|--|--|
| Solvent (Surface Cleaner)* | 0.21 (25)   |  |  |
| Pretreatment Coating       | 5.5 (660)   |  |  |
| Primer / Primer Surfacer   | 2.1 (250)   |  |  |
| Primer Sealer              | 2.1 (250)   |  |  |
| Single Stage Coating       | 2.8 (340)   |  |  |
| Color Coating              | 3.5 (420)   |  |  |
| Underbody Coating          | 3.6 (430)   |  |  |
| Clear Coating              | 2.1 (250)   |  |  |
| Uniform Finish Coating     | 4.5 (540)   |  |  |
| Adhesion Promoter          | 4.5 (540)   | *VOC content applies to this category only |  |

| Product Code & Name   | Hardener/<br>Activator | Reducer              | Mix Ratio | VOC Content                  |
|---|------------------------|----------------------|-----------|------------------------------|
| Solvent (Surface Cleaner)   |                        |                      |           | Limit: 0.21 lbs/gal (25 g/L) |
| SWX350 H <sub>2</sub> O-SO-CLEAN <sup>®</sup> Wax & Grease Remover  | -                      | -                    | -         | 0.17 (20)                    |
| SX1009 2.9 VOC Bug and Tar Remover*                                 | -                      | -                    | -         | 2.89 (346)                   |
| SXA103 MULTI-PREP <sup>®</sup> Cleaner*                             | -                      | -                    | Aerosol   | 5.88 (705)                   |
| SXA330 Wax and Grease Remover*                                      | -                      | -                    | Aerosol   | 5.77 (691)                   |
| *Section C.12 Prior written approval of APCO required under low use | exemption, maximum 13  | 0 lbs/calendar year. |           |                              |

| Product Code & Name                         | Hardener/Activator         | Reducer                     | Additives           | Mix Ratio          | Applied VOC<br>Less Water Less Exempt |
|---|----------------------------|-----------------------------|---------------------|--------------------|---------------------------------------|
| Pre-Treatment Coatings                      |                            |                             |                     | Limi               | t: 5.5 lbs/gal (660 g/L)              |
| SX1071 ECOBASE <sup>®</sup> 5.5 Etch Prime  | SX1072                     | -                           | -                   | 1:1                | 5.48 (657)                            |
| SXA1031 Etch Primer - Gray                  | -                          | -                           | -                   | Aerosol            | N/A                                   |
| Primer Surfacer                             |                            |                             |                     | Lim                | it 2.1 lbs/gal (250 g/L)              |
| JP209 Gray Polyester Primer / Filler        | MEKP                       | -                           | -                   | 0.5 oz. per quart  | 0.98 (118)                            |
| JP35X 2.1 VOC Multi-Purpose Primer          | JH358                      | JR55X                       | -                   | 4:1:2              | 2.05 (246)                            |
| JP390 2.1 VOC Epoxy Primer - Gray           | JH397                      | JR55X                       | -                   | 2:1:1              | 2.07 (248)                            |
| Primer Sealer (apply over previously coated | d surfaces)                |                             |                     | Limi               | t: 2.1 lbs/gal (250 g/L)              |
| JP35X 2.1 VOC Multi-Purpose Primer          | JH358                      | JR55X                       | JC78x, or<br>JC7200 | 3:1:1:1            | 2.09 (250)                            |
| JP36X Series 2.1 VOC Urethane Sealers       | JH358                      | JR55X                       | -                   | 4:1:1              | 2.09 (250)                            |
| JP390 2.1 VOC Epoxy Primer - Gray           | JH397                      | JR55X                       | -                   | 2:1:2              | 2.07 (248)                            |
| Single Stage Coating                        |                            |                             |                     | Limi               | t: 2.8 lbs/gal (340 g/L)              |
| JTX 2.8 VOC Direct Gloss Acrylic Urethane   | JH6028                     | JR55X                       | -                   | 4:1:2              | 2.80 (335)                            |
| JLX 2.8 VOC Acrylic Enamel                  | JH6028                     | JR55X                       | -                   | 4:1:1              | 2.76 (331)                            |
| Basecoat for Multi Stage Topcoat System     |                            |                             |                     | Limi               | t: 3.5 lbs/gal (420 g/L)              |
| JBX 3.5 Acrylic Basecoat                    | -                          | JR29X                       | -                   | 1:1                | 3.48 (417)                            |
| Use JBPX blend to spra                      | ay mix recommendation with | out JH6028 only with new    | color formula       | s that contain J17 | 79                                    |
| JBPX 3.5 VOC Acrylic Urethane Basecoat      | -                          | JR55X                       | -                   | 1:1                | 3.49 (419)                            |
| Use JBPX blend to spr                       | ay mix recommendations wi  | th JH6028 with all historic | color formula       | s that contain J13 | 6                                     |
| JBPX 3.5 VOC Acrylic Urethane Basecoat      | JH6028                     | JR55X                       | -                   | 10:1:10            | 3.48 (417)                            |
| JBPX 3.5 VOC Acrylic Urethane Basecoat      | JH6028                     | JR55X                       | -                   | 10:1:5             | 3.48 (417)                            |



## Ventura County APCD Motor Vehicle and Mobile Equipment Coating Operations Rule 74.18 Amended: 11/11/2008 | In Effect: 1/1/2010



| Product Code & Name                                 | Hardener/Activator        | Reducer      | Additives | Mix Ratio | Applied VOC<br>Less Water Less Exempt |
|---|---------------------------|--------------|-----------|-----------|---------------------------------------|
| Clear Coating                                       |                           |              |           | Limi      | t: 2.1 lbs/gal (250 g/L)              |
| JC780 2.1 VOC Polyurethane Speed Clear              | JH7870, JH7880,<br>JH7890 | -            | -         | 4:1       | 2.08 (249)                            |
| JC781 2.1 VOC Polyurethane High Gloss Clear         | JH7870, JH7880,<br>JH7890 | -            | -         | 4:1       | 2.06 (247)                            |
| JC830 2.1 VOC Production Clear                      | JH8370, JH8380,<br>JH8390 | JR555, JR556 | -         | 4:1:0.5   | 2.08 (249)                            |
| JC7100 2.1 VOC HS European Multi-Panel<br>Clearcoat | JH7121, JH7131            | -            | -         | 2:1       | 1.95 (234)                            |
| JC7200 2.1 VOC European Clearcoat                   | JH72XX                    | -            | -         | 2:1       | 2.08 (249)                            |

| Additional Products (listing not intended to be all inclusive) |   |  |  |  |
|--|---|--|--|--|
| SLV4985 Universal Flattening Agent                             | SU4901 Clean and Scuff Sponge           | SXA1044 High Build Flexible Surfacer (Aerosol) |  |  |
| SLV73 Fisheye Eliminator                                       | SUA4903 Advanced Plastic Bond (Aerosol) | SXA1050 Plastic Adhesion Promoter (Aerosol)    |  |  |
| SLV814 Universal Flexibilizer                                  | SWX100 Waterborne Gun Cleaner           | SX1047 High Build WB Flexible Surfacer         |  |  |
| SLV840 Uniform Finish Blender                                  | SXA840 Uniform Finish Blender (Aerosol) | SU470LV 1K Compliant Adhesion Promoter         |  |  |
| SLV898 Retarder  | SXA1030 Black Guide Coat (Aerosol)      | SXA1041 Bumper Black (Aerosol)                 |  |  |

This "Ventura County APCD Rule 74.18 (PPG *Shop-Line*)" wall chart is intended to provide INFORMATION to PPG's customers. In providing this wall chart, PPG makes no separate or additional warranties, express or implied, and assumes no liability or responsibility arising out of its use. It is the responsibility of each customer, RE-SELLER AND END USER of PPG's products to independently ascertain that their practices are legal, appropriate and constitute sound product stewardship. This "Ventura County APCD Rule 74.18 (PPG *Shop-Line*)" wall chart does not include all currently compliant *Shop-Line* products. The representative products listed are compliant with Ventura County APCD Rule 74.18 (VPG *Shop-Line*)" wall chart, however, subsequent changes in Ventura County APCD Rule 74.18 45 may change the compliance status of the listed products. It is the responsibility of the end user to review and comply with current regulations, including applicable coating category VOC limits, as of the date of produce use. This document is not INTENDED to define or create legal rights or obligations. It is the responsibility of each customer, RE-SELLER AND END USER to comply with all applicable federal, state and local laws.

© 2019 Copyright PPG Industries, Inc. All rights reserved www.ppgrefinish.com The PPG Logo, Acryli-Clean, Echobase, H2O-So-Clean, and SHOP-LINE® are registered trademarks of PPG Industries Ohio, Inc.