

State of Maryland Control of VOC Emissions from Vehicle Refinishing COMAR 26.11.19.23



In Effect: 7/1/2013

Coating Category	Ibs/gal (g/L) Limit: VOC Regulatory (Less Water Less Exempts).				
Solvent (Surface Cleaner)*	0.21 (25)				
Pretreatment Coating	5.5 (660)				
Primer / Primer Surfacer	2.1 (250)				
Primer Sealer	2.1 (250)				
Single Stage Coating	2.8 (340)				
Color Coating	3.5 (420)				
Underbody Coating	3.6 (430)		*VOC content applies to this category only.		
Clear Coating	2.1 (250)				
Adhesion Promoter	4.5 (540)]		
Product Code & Name	Hardener/Activator	Reducer	Mix Ratio	VOC Content	
Solvent (Surface Cleaner)				Limit: 0.21 lbs/gal (25 g/L)	
SWX350 H2O-So-Clean Wax & Grease Remover	-	-	-	0.17 (20)	
SX1005 Low VOC Wax & Grease Remover	-	Water	1:1	0.21 (25)	
SX1009 2.9 VOC Bug & Tar Remover*	-	-	-	2.89 (346)	
* C (C)(b) Courses and boundary and for boundary and					

^{*} E.(5)(b) For cleaning solvents used for bug and tar removal, a person may not use or apply to a motor vehicle, mobile equipment, or associated part a bug and tar remover greater than 40 percent VOC by weight as set forth in COMAR 26.11.32.04B. (SX1009 meets that standard.)

Product Code & Name	Hardener/Activator	Reducer	Additives	Mix Ratio	Applied VOC Less Water Less Exempt
Pretreatment Coatings				Lim	it: 5.5 lbs/gal (660 g/L)
SX1071 Etch Prime	SX1072	-	-	1:1	5.48 (657)
SXA1031 Etch Primer - Gray	-	-	-	Aerosol	N/A
Primer / Primer Surfacer				Lin	nit 2.1 lbs/gal (250 g/L)
DPLV305X Acrylic Urethane Surfacer	DHLV3030	DT18XX Series	-	4:1:1	2.03 (243)
DPLV305X Acrylic Urethane Surfacer	DHLV3030	-	-	4:1	2.03 (243)
DPLV 2.1 Epoxy Primer	DP401LV	DT18XX Series	-	2:1:1	2.09 (250)
DS1002 UV Cured Primer Surfacer	-	-	-	Aerosol	N/A
ECP1X A-Chromatic Surfacer	EH391	DT18XX Series	-	4:1:1	2.09 (250)
ECP1X A-Chromatic Surfacer	EH391	DT18XX Series	-	4:1	2.08 (249)
ECP1X A-Chromatic Surfacer	EH391	DT18XX Series	EA157	4:1:1 + 10%	2.09 (250)
EPW115 Waterborne Speed Prime		T494		1:13%	.72 (86)
NCP280 2.1 VOC Primer Surfacer	NCX285			2:1	2.10 (250)
NCP280 2.1 VOC Primer Surfacer	NCX285			2:1+10% Acetone	2.1 (250)
Primer Sealer (apply over previously co	oated surfaces)			Lim	it: 2.1 lbs/gal (250 g/L)
ECS2X A-Chromatic LV Sealer	EH391	DT18XX	-	4:1:1	1.82 (246)
Single Stage Coating				Lim	it: 2.8 lbs/gal (340 g/L)
ENVIROBASE® Interior System	T584	T494	-	100:15:15	2.79 (334)

© 2014 PPG Industries VOC 26.11.19.23 DEL (7/14)



State of Maryland

Control of VOC Emissions from Vehicle Refinishing COMAR 26.11.19.23



In Effect: 7/1/2013

Product Code & Name	Hardener/Activator	Reducer	Additives	Mix Ratio	Applied VOC Less Water Less Exempt
Color Coating				Lin	nit: 3.5 lbs/gal (420 g/L)
Envirobase Waterborne Basecoat	-	T494	-	100:10	3.35 (401)
Envirobase Waterborne Basecoat	-	T494	-	100:20	3.40 (407)
Envirobase Waterborne Basecoat	-	T494	-	100:30	3.50 (419)
Envirobase Waterborne Basecoat	-	-	T492	100:10	3.36 (403)
Envirobase Waterborne Basecoat	-	T494	T492	100:10:10	3.38 (405)
Envirobase Waterborne Basecoat	-	T494	T492	100:20:10	3.40 (407)
Envirobase Waterborne Basecoat	T581	T494	-	100:10:10	3.05 (336)
Envirobase Waterborne Basecoat	T581	T494	-	100:10:20	3.09 (370)
Envirobase Waterborne Basecoat	T581	T494	-	100:10:30	3.11 (373)
Underbody Coating				Lin	nit: 3.6 lbs/gal (430 g/L)
Internal Repair System	T581	T494	-	100:15:15	3.08 (369)
Clear Coating				Lin	nit: 2.1 lbs/gal (250 g/L)
DC3010 DELTRON® High Velocity Clear	DCH36XX	-	-	2:1	2.00 (240)
DC4010 Velocity Premium Clear	DCH36XX	D8767	-	3:1:10%	2.05 (246)
DC4010 Velocity Premium Clear	DCH36XX	-	-	4:1	2.08 (249)
DCU2010 2.1 Speed Clear	DCX20XX	-	-	2:1	2.05 (246)
DC4125 Ceramiclear Clearcoat	DCH4126	-	-	4:1	2.07 (248)
EC700 OneVisit Production Clear	ECH70XX	-	-	4:1	2.08 (249)
EC700 OneVisit Production Clear	ECH70XX	D87XX	EA10	4:1:0.5 +5%	2.08 (249)
EC750 OneVisit Appearance Clear	ECH70XX	-	-	4:1	2.08 (249)
EC800 Ultra Fast 2.1 Clearcoat	ECH8075	D8767, DT1855	-	4:1:1	2.08 (249)
	ECH8075	ECA83	-	4:1:1	1.90 (228)

Additional Products (listing not intended to be all inclusive)				
DX101 Sanding Paste	SLV840 Uniform Finish Blender	SXA1030 Black Guide Coat		
DX310 EZ Cleaner	SU460LV 1K Compliant Adhesion Promoter	SXA1033 Texture Spray		
SLV4985 Universal Flattening Agent	SU4901 Clean and Scuff Sponge	SXA1041 Bumper Black		
SLV73 Fisheye Eliminator	SUA4903 Advanced Plastic Bond	SXA1050 Plastic Adhesion Promoter		
SLV814 Universal Flexibilizer	SWX100 Waterborne Gun Cleaner	SX1047 High Build Flexible Surfacer		

This "State of Maryland COMAR 26.11.19.23 (PPG Deltron)" wall chart is intended to provide INFORMATION to PPG's customers. In providing this wall chart, PPG makes no separate or additional warranties, express or implied, and assumes no liability or responsibility arising out of its use. It is the responsibility of each customer, RE-SELLER AND END USER of PPG's products to independently ascertain that their practices are legal, appropriate and constitute sound product stewardship. This "State of Maryland COMAR 26.11.19.23(PPG Deltron)" wall chart does not include all currently compliant Deltron products. The representative products listed are compliant with State of Maryland COMAR 26.11.19.23 VOC limits as of the date of this wall chart; however, subsequent changes in State of Maryland COMAR 26.11.19.23 may change the compliance status of the listed products. It is the responsibility of the end user to review and comply with current regulations, including applicable coating category VOC limits, as of the date of product purchase and/or use. This document is not INTENDED to define or create legal rights or obligations. It is the responsibility of each customer, RE-SELLER AND END USER to comply with all applicable federal, state and local laws.

The PPG logo, Deltron and Envirobase are registered trademarks of PPG Industries of Ohio, Inc.