

Antelope Valley AQMD Motor Vehicle and Mobile Equipment Coating Operations Rule 1151 Amended: 6/19/2012 | In Effect: 5/1/2013



Coating Category	Ibs/U.S. gal (g/L) Limit: VOC Regulatory (Less Water Less Exempts).		
Solvent (Surface Cleaner)*	0.21 (25)		
Pretreatment Coating	5.5 (660)		
Primer / Primer Surfacer	2.1 (250)		
Primer Sealer	2.1 (250)		
Single Stage Coating	2.8 (340)		
Color Coating	3.5 (420)		
Underbody Coating	3.6 (430)		
Clear Coating	2.1 (250)		
Uniform Finish Coating	4.5 (540)		
Adhesion Promoter	4.5 (540)	*VOC content applies to this category only	

Product Code & Name	Hardener/ Activator	Reducer	Mix Ratio	VOC Content
Solvent (Surface Cleaner)				Limit: 0.21 lbs/gal (25 g/L)
SWX350 H ₂ O-SO-CLEAN [®] Wax & Grease Remover	-	-	-	0.17 (20)
SXA103 MULTI-PREP™ Cleaner*	-	-	Aerosol	5.88 (705)
SXA330 ACRYLI-CLEAN [®] Wax & Grease Remover*	-	-	Aerosol	5.77 (691)

*RULE 2.31 113 The provisions of Sections 301 shall not apply to cleaning with aerosol products if 160 ounces or less are used per day per facility and the facility has obtained either a District permit, or a written exemption from the APCO. The products used shall comply with California Air Resources Board (ARB) regulations.

Product Code & Name	Hardener/Activator/ Modifier	Reducer	Additives	Mix Ratio	Applied VOC Less Water Less Exempt
Pre-Treatment Coatings				Limi	t: 5.5 lbs/gal (660 g/L)
SX1071 ECOBASE [®] 5.5 Etch Prime	SX1072	-	-	1:1	5.48 (657)
SXA1031 Etch Primer - Gray	-	-	-	Aerosol	N/A
Primer Surfacer				Lim	it 2.1 lbs/gal (250 g/L)
JP209 Gray Polyester Primer / Filler	MEKP	-	-	0.5 oz. per quart	0.98 (118)
JP35X 2.1 VOC Multi-Purpose Primer	JH358	JR55X	-	4:1:2	2.05 (246)
JP390 2.1 VOC Epoxy Primer - Gray	JH397	JR55X	-	2:1:1	2.07 (248)
Primer Sealer (apply over previously coated	d surfaces)			Limi	t: 2.1 lbs/gal (250 g/L)
JP35X 2.1 VOC Multi-Purpose Primer	JH358	JR55X	JC78x, or JC7200	3:1:1:1	2.09 (250)
JP36X Series 2.1 VOC Urethane Sealers	JH358	JR55X	-	4:1:1	2.09 (250)
JP390 2.1 VOC Epoxy Primer - Gray	JH397	JR55X	-	2:1:2	2.07 (248)
Single Stage Coating				Limi	t: 2.8 lbs/gal (340 g/L)
JTX 2.8 VOC Direct Gloss Acrylic Urethane	JH6028	JR55X	-	4:1:2	2.80 (335)
JLX 2.8 VOC Acrylic Enamel	JH6028	JR55X	-	4:1:1	2.76 (331)
Color Coating/Basecoat for Multi Stage Topcoat System				Limi	t: 3.5 lbs/gal (420 g/L)
JBX 3.5 Acrylic Basecoat	-	JR29X	-	1:1	3.48 (417)
Use JBPX blend to spra	ay mix recommendation with	nout JH6028 only with new	v color formula	s that contain J17	79
JBPX 3.5 VOC Acrylic Urethane Basecoat	-	JR55X	-	1:1	3.49 (419)
Use JBPX blend to spra	ay mix recommendations wi	th JH6028 with all historic	color formula	s that contain J13	6
JBPX 3.5 VOC Acrylic Urethane Basecoat	JH6028	JR55X	-	10:1:10	3.48 (417)
JBPX 3.5 VOC Acrylic Urethane Basecoat	JH6028	JR55X	-	10:1:5	3.48 (417)



Antelope Valley AQMD Motor Vehicle and Mobile Equipment Coating Operations Rule 1151 Amended: 6/19/2012 | In Effect: 5/1/2013



Product Code & Name	Hardener/Activator	Reducer	Additives	Mix Ratio	Applied VOC Less Water Less Exempt
Clear Coating				Limit: 2.1 lbs/gal (250 g/L)	
JC780 2.1 VOC Polyurethane Speed Clear	JH7870, JH7880, JH7890	-	-	4:1	2.08 (249)
JC781 2.1 VOC Polyurethane High Gloss Clear	JH7870, JH7880, JH7890	-	-	4:1	2.06 (247)
JC830 2.1 VOC Production Clear	JH8370, JH8380, JH8390	JR555, JR556	-	4:1:0.5	2.08 (249)
JC7100 2.1 VOC HS European Multi-Panel Clearcoat	JH7121, JH7131	-	-	2:1	1.95 (234)
JC7200 2.1 VOC European Clearcoat	JH72XX	-	-	2:1	2.08 (249)

Additional Products (listing not intended to be all inclusive)				
SLV4985 Universal Flattening Agent	SU4901 Clean and Scuff Sponge	SXA1044 High Build Flexible Surfacer (Aerosol)		
SLV73 Fisheye Eliminator	SUA4903 Advanced Plastic Bond (Aerosol)	SXA1050 Plastic Adhesion Promoter (Aerosol)		
SLV814 Universal Flexibilizer	SWX100 Waterborne Gun Cleaner	SX1047 High Build WB Flexible Surfacer		
SLV840 Uniform Finish Blender	SXA840 Uniform Finish Blender (Aerosol)	SU470LV 1K Compliant Adhesion Promoter		
SLV898 Retarder	SXA1030 Black Guide Coat (Aerosol)	SXA1041 Bumper Black (Aerosol)		

This Antelope Valley AQMD Rule 1151 (PPG *Shop-Line*)" wall chart is intended to provide INFORMATION to PPG's customers. In providing this wall chart, PPG makes no separate or additional warranties, express or implied, and assumes no liability or responsibility arising out of its use. It is the responsibility of each customer, RE-SELLER AND END USER of PPG's products to independently ascertain that their practices are legal, appropriate and constitute sound product stewardship. This Antelope Valley AQMD Rule 1151 (PPG *Shop-Line*)" wall chart does not include all currently compliant *Shop-Line* products. The representative products listed are compliant with Antelope Valley AQMD Rule 1151 VOC limits as of the date of this wall chart; however, subsequent changes in Antelope Valley AQMD Rule 1151 VOC limits as of the date of this wall chart; however, subsequent changes in Antelope Valley AQMD Rule 1151 may change the compliance status of the listed products. It is the responsibility of the end user to review and comply with current regulations, including applicable coating category VOC limits, as of the date of product purchase and/or use. This document is not INTENDED to define or create legal rights or obligations. It is the responsibility of each customer, RE-SELLER AND END USER to comply with all applicable federal, state and local laws.