

## Detailed Delfleet Essential Package VOC

All data contained in this chart represents package formula values. Depending on the requirements of the regulatory body, one or more of these sets of data would be requested.  
 The "VOC Regulatory - Less Water Less Exempt" represents the weight of volatiles minus water and exempt solvent weight contribution, per unit volume product minus water and exempt solvent volume contribution.  
 The "VOC Actual" entry represents the weight of the volatiles minus water and exempt weight contribution per unit volume (which includes water and exempt solvent volume contribution). (This entry is sometimes referred to as VOC, as calculated by Rule 1171, also referred to as VOC emissions.)  
 The "Pounds of Organic VoHAP per Gallon of Product" represents the weight of organic VoHAP per unit volume (including volatile volume contribution.)  
 This chart is revised periodically. To obtain the most accurate values check for updates on a regular basis.

| Product Code | Applicable Use Category(ies)  | Density | Density | VOC Regulatory - Less Water Less Exempt | VOC Regulatory - Less Water Less Exempt | VOC Actual | VOC Actual | Wt. % Volatiles | Wt. % Water | Wt. % Exempt Compounds | Vol. % Water | Vol. % Exempt Compounds | Volatile Volume % | Pounds of Organic VoHAP per Gallon of Product |
|--------------|-------------------------------|---------|---------|---|---|------------|------------|-----------------|-------------|------------------------|--------------|-------------------------|-------------------|---|
|              |                               | lbs/gal | gm/ltr  | lbs/gal                                 | gm/ltr                                  | lbs/gal    | gm/ltr     |                 |             |                        |              |                         |                   |   |
| ES301780PC   | Single-Stage Ctg              | 8.57    | 1027    | 3.05                                    | 366                                     | 2.2        | 263        | 53.2            | 0.1         | 27.5                   | 0.1          | 28                      | 59.3              | 0   |
| ES903653SF   |                               | 10.46   | 1253    | 2.77                                    | 332                                     | 2.5        | 299        | 30.1            | 0.1         | 6.1                    | 0.2          | 9.6                     | 43.8              | 0   |
| ES915500LG   | Single-Stage Ctg              | 9.16    | 1098    | 2.6                                     | 312                                     | 1.77       | 212        | 48.1            | 0.2         | 28.6                   | 0.2          | 31.8                    | 56.7              | 0   |
| ES915502LG   | Single-Stage Ctg              | 9.47    | 1135    | 2.88                                    | 345                                     | 2.08       | 249        | 47              | 0.3         | 24.7                   | 0.4          | 27.4                    | 56.4              | 0   |
| ES915512LG   | Single-Stage Ctg              | 9.16    | 1098    | 2.49                                    | 298                                     | 1.66       | 199        | 47.9            | 0.1         | 29.7                   | 0.1          | 33.2                    | 56.6              | 0   |
| ES924451LG   | Single-Stage Ctg              | 9.1     | 1090    | 2.52                                    | 302                                     | 1.68       | 201        | 48.6            | 0.1         | 30                     | 0.1          | 33.3                    | 56.9              | 0   |
| ES924780LG   | Single-Stage Ctg              | 9.06    | 1086    | 2.58                                    | 309                                     | 1.76       | 210        | 48.1            | 0.1         | 28.6                   | 0.1          | 31.8                    | 56.4              | 0   |
| ES941101BD   |                               | 8.91    | 1068    | 2.98                                    | 357                                     | 2.5        | 300        | 48.2            | 0           | 20.1                   | 0            | 16.2                    | 50.1              | 0.72  |
| ESB800       | Color Ctg (Additive)          | 9.52    | 1141    | 5.01                                    | 600                                     | 2.95       | 353        | 79.3            | 0           | 48.3                   | 0            | 41.1                    | 83.9              | 0.28  |
| ESB810       | Single-Stage Ctg              | 10.92   | 1309    | 1.01                                    | 121                                     | 0.4        | 48         | 62.3            | 0           | 58.5                   | 0            | 59.9                    | 65.7              | 0   |
| ESC600       |                               | 7.62    | 913     | 4.38                                    | 524                                     | 3.52       | 422        | 63.4            | 0.1         | 17.1                   | 0.1          | 19.5                    | 69                | 2.55  |
| ESC621       | Clear Ctg, Uniform Finish Ctg | 8.59    | 1029    | 2.42                                    | 290                                     | 1.54       | 185        | 55.9            | 0.1         | 37.9                   | 0.1          | 36.3                    | 58.3              | 0.97  |
| ESH200       | Single-Stage Ctg (Hardener)   | 9.51    | 1140    | 1.04                                    | 125                                     | 1.04       | 125        | 11              | 0           | 0                      | 0            | 0                       | 13.2              | 0   |
| ESH210       | Color Ctg (Hardener)          | 10.8    | 1294    | 0.06                                    | 7                                       | 0.02       | 2          | 75.2            | 0           | 75                     | 0            | 72.4                    | 72.5              | 0   |
| ESM101       | Color Ctg, Single-Stage Ctg   | 8.3     | 995     | 2.71                                    | 325                                     | 2.16       | 259        | 43.2            | 0.3         | 16.8                   | 0.3          | 20.1                    | 50                | 0   |
| ESM102       | Color Ctg, Single-Stage Ctg   | 8.35    | 1001    | 2.74                                    | 328                                     | 2.06       | 247        | 46.8            | 0.1         | 22                     | 0.1          | 24.6                    | 53                | 0   |
| ESM103       | Color Ctg, Single-Stage Ctg   | 8.46    | 1014    | 2.8                                     | 335                                     | 2.19       | 263        | 43              | 0.1         | 16.9                   | 0.1          | 21.4                    | 51.6              | 0   |
| ESM104       | Color Ctg, Single-Stage Ctg   | 8.36    | 1002    | 2.71                                    | 325                                     | 2.08       | 249        | 45.7            | 0.1         | 20.7                   | 0.1          | 23.2                    | 51.7              | 0   |
| ESM105       | Color Ctg, Single-Stage Ctg   | 8.66    | 1038    | 2.83                                    | 339                                     | 2.23       | 267        | 43.8            | 0.1         | 18                     | 0.1          | 21.2                    | 51.6              | 0   |
| ESM106       | Color Ctg, Single-Stage Ctg   | 8.49    | 1017    | 2.56                                    | 306                                     | 1.92       | 230        | 45.1            | 0.3         | 22.1                   | 0.3          | 24.5                    | 51                | 0   |
| ESM107       | Color Ctg, Single-Stage Ctg   | 8.33    | 998     | 3.05                                    | 366                                     | 2.45       | 293        | 46.2            | 0.3         | 16.5                   | 0.3          | 19.6                    | 53.4              | 0   |
| ESM108       | Color Ctg, Single-Stage Ctg   | 8.93    | 1070    | 2.82                                    | 338                                     | 2.48       | 297        | 37.3            | 0.1         | 9.4                    | 0.1          | 12                      | 45.7              | 0   |
| ESM109       | Color Ctg, Single-Stage Ctg   | 9.81    | 1175    | 2.76                                    | 331                                     | 2.43       | 291        | 33.1            | 0.1         | 8.3                    | 0.1          | 12.1                    | 45.4              | 0   |
| ESM110       | Color Ctg, Single-Stage Ctg   | 8.33    | 998     | 2.83                                    | 339                                     | 2.25       | 270        | 43.6            | 0.2         | 16.4                   | 0.2          | 20.3                    | 51.1              | 0   |
| ESM111       | Color Ctg, Single-Stage Ctg   | 8.8     | 1054    | 2.7                                     | 324                                     | 2.18       | 262        | 41.5            | 0.1         | 16.5                   | 0.1          | 19                      | 49.2              | 0   |
| ESM112       | Color Ctg, Single-Stage Ctg   | 9.1     | 1090    | 2.8                                     | 336                                     | 2.35       | 282        | 41.1            | 0           | 15.2                   | 0            | 16                      | 48.4              | 0   |
| ESM113       | Color Ctg, Single-Stage Ctg   | 9.09    | 1089    | 2.79                                    | 335                                     | 2.43       | 291        | 36.3            | 0.1         | 9.5                    | 0.1          | 12.9                    | 46.1              | 0   |
| ESM114       | Color Ctg, Single-Stage Ctg   | 8.36    | 1002    | 2.72                                    | 326                                     | 2.07       | 247        | 45.5            | 0.4         | 20.4                   | 0.4          | 23.7                    | 52.3              | 0   |
| ESM115       | Color Ctg, Single-Stage Ctg   | 8.28    | 992     | 2.63                                    | 316                                     | 2.01       | 241        | 45.3            | 0.3         | 20.7                   | 0.3          | 23.3                    | 51.6              | 0   |
| ESM116       | Color Ctg, Single-Stage Ctg   | 9.46    | 1134    | 2.76                                    | 331                                     | 2.33       | 279        | 36.3            | 0.3         | 11.4                   | 0.3          | 15.3                    | 47.2              | 0   |
| ESM117       | Color Ctg, Single-Stage Ctg   | 9.5     | 1138    | 2.79                                    | 335                                     | 2.33       | 280        | 36.2            | 0.3         | 11.3                   | 0.3          | 16.1                    | 48.2              | 0   |
| ESM118       | Color Ctg, Single-Stage Ctg   | 9.23    | 1106    | 2.8                                     | 335                                     | 2.31       | 277        | 37.6            | 0.3         | 12.3                   | 0.3          | 17                      | 49                | 0   |
| ESM119       | Color Ctg, Single-Stage Ctg   | 8.4     | 1007    | 2.73                                    | 327                                     | 2.1        | 251        | 44.3            | 0.4         | 18.9                   | 0.4          | 22.9                    | 52                | 0   |
| ESM120       | Color Ctg, Single-Stage Ctg   | 8.45    | 1013    | 2.76                                    | 331                                     | 2.15       | 258        | 44.1            | 0.5         | 18.2                   | 0.5          | 21.6                    | 51.6              | 0.01  |
| ESM121       | Color Ctg, Single-Stage Ctg   | 8.85    | 1060    | 2.81                                    | 337                                     | 2.28       | 273        | 40.9            | 0.2         | 14.9                   | 0.2          | 18.8                    | 50.7              | 0   |
| ESM122       | Color Ctg, Single-Stage Ctg   | 9.17    | 1099    | 2.82                                    | 338                                     | 2.27       | 272        | 41              | 0.2         | 16.1                   | 0.2          | 19.4                    | 50.9              | 0   |
| ESM123       | Color Ctg, Single-Stage Ctg   | 8.35    | 1001    | 2.73                                    | 327                                     | 2.12       | 254        | 44.1            | 0.4         | 18.3                   | 0.4          | 21.8                    | 51.1              | 0   |
| ESM124       | Color Ctg, Single-Stage Ctg   | 8.44    | 1011    | 2.76                                    | 331                                     | 2.14       | 257        | 45.1            | 0.4         | 19.3                   | 0.4          | 22.1                    | 51.9              | 0   |
| ESM125       | Color Ctg, Single-Stage Ctg   | 8.1     | 971     | 2.76                                    | 330                                     | 2.15       | 258        | 44.7            | 0.1         | 18                     | 0.1          | 21.8                    | 52                | 0.01  |

## Detailed Delfleet Essential Package VOC

All data contained in this chart represents package formula values. Depending on the requirements of the regulatory body, one or more of these sets of data would be requested.  
 The "VOC Regulatory - Less Water Less Exempt" represents the weight of volatiles minus water and exempt solvent weight contribution, per unit volume product minus water and exempt solvent volume contribution.  
 The "VOC Actual" entry represents the weight of the volatiles minus water and exempt weight contribution per unit volume (which includes water and exempt solvent volume contribution). (This entry is sometimes referred to as VOC, as calculated by Rule 1171, also referred to as VOC emissions.)  
 The "Pounds of Organic VoHAP per Gallon of Product" represents the weight of organic VoHAP per unit volume (including volatile volume contribution.)  
 This chart is revised periodically. To obtain the most accurate values check for updates on a regular basis.

| Product Code | Applicable Use Category(ies)       | Density | Density | VOC Regulatory - Less Water Less Exempt | VOC Regulatory - Less Water Less Exempt | VOC Actual | VOC Actual | Wt. % Volatiles | Wt. % Water | Wt. % Exempt Compounds | Vol. % Water | Vol. % Exempt Compounds | Volatile Volume % | Pounds of Organic VoHAP per Gallon of Product |
|--------------|------------------------------------|---------|---------|---|---|------------|------------|-----------------|-------------|------------------------|--------------|-------------------------|-------------------|---|
|              |                                    | lbs/gal | gm/ltr  | lbs/gal                                 | gm/ltr                                  | lbs/gal    | gm/ltr     |                 |             |                        |              |                         |                   |   |
| ESM126       | Color Ctg, Single-Stage Ctg        | 10.49   | 1257    | 2.56                                    | 306                                     | 2.3        | 275        | 28.4            | 0.1         | 6.4                    | 0.2          | 10                      | 40.7              | 0   |
| ESM127       | Color Ctg, Single-Stage Ctg        | 9.01    | 1080    | 2.79                                    | 334                                     | 2.32       | 278        | 38.9            | 0.3         | 12.8                   | 0.4          | 16.5                    | 48.8              | 0   |
| ESM128       | Color Ctg, Single-Stage Ctg        | 10.12   | 1213    | 2.8                                     | 336                                     | 2.5        | 299        | 31.9            | 0.1         | 7.1                    | 0.2          | 10.8                    | 44.8              | 0   |
| ESM129       | Color Ctg, Single-Stage Ctg        | 8.32    | 997     | 2.76                                    | 331                                     | 2.03       | 244        | 47.7            | 0.1         | 23.2                   | 0.1          | 26.4                    | 55.4              | 0   |
| ESM130       | Color Ctg, Single-Stage Ctg        | 8.3     | 995     | 2.75                                    | 330                                     | 2.02       | 242        | 47.7            | 0.1         | 23.3                   | 0.1          | 26.5                    | 55.3              | 0   |
| ESM132       | Color Ctg, Single-Stage Ctg        | 15.11   | 1811    | 2.65                                    | 317                                     | 2.65       | 317        | 17.5            | 0           | 0                      | 0            | 0                       | 38.3              | 0   |
| ESM133       | Color Ctg, Single-Stage Ctg        | 8.23    | 986     | 2.77                                    | 332                                     | 2.04       | 244        | 46.3            | 0.1         | 21.5                   | 0.1          | 26.4                    | 54.9              | 0   |
| ESR300       | Primer, Single-Stage Ctg (Thinner) | 8.9     | 1066    | 0                                       | 0                                       | 0          | 0          | 100             | 0.2         | 99.8                   | 0.2          | 99.2                    | 100               | 0   |
| ESR310       | Primer, Single-Stage Ctg (Thinner) | 10.05   | 1204    | 0                                       | 0                                       | 0          | 0          | 100             | 0.1         | 99.9                   | 0.1          | 99.7                    | 100               | 0   |
| ESS9075HDM   | Single-Stage Ctg                   | 8.53    | 1022    | 3.2                                     | 384                                     | 2.21       | 265        | 54.7            | 0.2         | 28.7                   | 0.2          | 30.9                    | 61.1              | 0.01  |
| ESS53800SF   | Single-Stage Ctg                   | 10.47   | 1255    | 2.57                                    | 308                                     | 2.31       | 276        | 28.6            | 0.1         | 6.5                    | 0.2          | 10.1                    | 41.9              | 0   |
| ESS54876     | Single-Stage Ctg                   | 15.06   | 1805    | 2.65                                    | 318                                     | 2.64       | 317        | 17.7            | 0           | 0.1                    | 0            | 0.2                     | 38.4              | 0   |
| ESS560156A   | Single-Stage Ctg                   | 9.2     | 1102    | 2.78                                    | 333                                     | 2.36       | 283        | 38.8            | 0.1         | 13.1                   | 0.1          | 14.9                    | 47.3              | 0   |
| ESS59000     | Single-Stage Ctg                   | 8.1     | 971     | 2.76                                    | 330                                     | 2.15       | 258        | 44.7            | 0.1         | 18                     | 0.1          | 21.8                    | 52                | 0.01  |
| ESS59000PC   | Single-Stage Ctg                   | 8.35    | 1001    | 2.99                                    | 359                                     | 2.09       | 250        | 53.6            | 0.1         | 28.4                   | 0.1          | 30.1                    | 58.7              | 0.01  |
| ESS59000SF   | Single-Stage Ctg                   | 8.1     | 971     | 2.76                                    | 330                                     | 2.15       | 258        | 44.7            | 0.1         | 18                     | 0.1          | 21.8                    | 52                | 0.01  |
| ESS5903653   | Single-Stage Ctg                   | 10.46   | 1253    | 2.77                                    | 332                                     | 2.5        | 299        | 30.1            | 0.1         | 6.1                    | 0.2          | 9.6                     | 43.8              | 0   |
| ESS5909919   | Single-Stage Ctg                   | 10.46   | 1253    | 2.57                                    | 308                                     | 2.3        | 276        | 28.6            | 0.1         | 6.5                    | 0.2          | 10.2                    | 41.9              | 0   |
| ESS5911678   | Single-Stage Ctg                   | 9.35    | 1120    | 2.68                                    | 322                                     | 1.48       | 177        | 59.6            | 0.1         | 43.7                   | 0.1          | 44.8                    | 65.4              | 0.01  |
| ESS5915499   | Single-Stage Ctg                   | 8.3     | 995     | 2.78                                    | 333                                     | 2.15       | 258        | 44.8            | 0.1         | 18.8                   | 0.1          | 22.3                    | 52.3              | 0   |
| ESS5932858   | Single-Stage Ctg                   | 8.85    | 1060    | 2.69                                    | 323                                     | 2.2        | 264        | 38.7            | 0.1         | 13.7                   | 0.1          | 18.2                    | 48.8              | 0.01  |
| ESS5942364   | Single-Stage Ctg                   | 8.31    | 996     | 2.76                                    | 331                                     | 2.04       | 245        | 47.4            | 0.1         | 22.8                   | 0.1          | 26                      | 55.2              | 0   |
| ESS5979392   | Single-Stage Ctg                   | 8.23    | 986     | 2.77                                    | 332                                     | 2.04       | 244        | 46.3            | 0.1         | 21.5                   | 0.1          | 26.4                    | 54.9              | 0   |
| EST900       | Single-Stage Ctg                   | 10.8    | 1294    | 2.72                                    | 326                                     | 2.7        | 323        | 25.5            | 0           | 0.5                    | 0            | 0.7                     | 36.2              | 0   |
| ESU400       |                                    | 8.42    | 1009    | 5.79                                    | 693                                     | 5.77       | 691        | 68.8            | 0.3         | 0                      | 0.3          | 0                       | 85                | 0.23  |
| ESU409       |                                    | 7.04    | 844     | 6.86                                    | 822                                     | 6.72       | 805        | 98              | 2.5         | 0                      | 2.1          | 0                       | 99.1              | 1.26  |
| ESU410       | Primer                             | 12.92   | 1548    | 2.05                                    | 245                                     | 1.83       | 220        | 19.6            | 0           | 5.3                    | 0            | 10.3                    | 37.2              | 0   |
| ESU419       | Primer (Hardener)                  | 9.66    | 1158    | 0                                       | 0                                       | 0          | 0          | 0               | 0           | 0                      | 0            | 0                       | 0                 | 0   |
| ESU420       |                                    | 11.94   | 1431    | 3.55                                    | 425                                     | 2.72       | 326        | 35.8            | 0.1         | 12.9                   | 0.1          | 23.2                    | 61.5              | 1.03  |
| ESU421       |                                    | 11.94   | 1431    | 3.5                                     | 420                                     | 2.69       | 322        | 35.5            | 0.1         | 12.9                   | 0.1          | 23.2                    | 61                | 1.03  |
| ESU421SF     |                                    | 11.94   | 1431    | 3.5                                     | 420                                     | 2.69       | 322        | 35.5            | 0.1         | 12.9                   | 0.1          | 23.2                    | 61                | 1.03  |
| ESU428       | Primer (Hardener)                  | 9.2     | 1102    | 2.08                                    | 250                                     | 1.47       | 176        | 51.9            | 0           | 35.9                   | 0            | 29.6                    | 51.1              | 0.55  |
| ESU430       |                                    | 10.3    | 1234    | 4.78                                    | 573                                     | 4.78       | 572        | 46.4            | 0           | 0                      | 0            | 0                       | 67.6              | 0.59  |
| ESU439       |                                    | 7.2     | 863     | 5.95                                    | 713                                     | 5.94       | 712        | 82.6            | 0.1         | 0                      | 0.1          | 0                       | 84.5              | 2.08  |
| ESU440       |                                    | 11.56   | 1385    | 3.68                                    | 441                                     | 3.12       | 373        | 35.8            | 0.1         | 8.8                    | 0.1          | 15.3                    | 58.5              | 1.83  |
| ESU449       |                                    | 10.3    | 1234    | 0                                       | 0                                       | 0          | 0          | 40.6            | 0           | 40.6                   | 0            | 37.4                    | 37.3              | 0   |
| ESU460       |                                    | 11.83   | 1418    | 4.14                                    | 496                                     | 4.14       | 496        | 35              | 0           | 0                      | 0            | 0                       | 58.5              | 1.3   |
| ESU461       |                                    | 12.35   | 1480    | 4.07                                    | 488                                     | 4.07       | 488        | 33              | 0           | 0                      | 0            | 0                       | 57.6              | 1.65  |
| ESU462       |                                    | 11.34   | 1359    | 4.15                                    | 497                                     | 4.15       | 497        | 36.6            | 0           | 0                      | 0            | 0                       | 58.7              | 1.49  |

## Detailed Delfleet Essential Package VOC

All data contained in this chart represents package formula values. Depending on the requirements of the regulatory body, one or more of these sets of data would be requested.  
 The "VOC Regulatory - Less Water Less Exempt" represents the weight of volatiles minus water and exempt solvent weight contribution, per unit volume product minus water and exempt solvent volume contribution.  
 The "VOC Actual" entry represents the weight of the volatiles minus water and exempt weight contribution per unit volume (which includes water and exempt solvent volume contribution). (This entry is sometimes referred to as VOC, as calculated by Rule 1171, also referred to as VOC emissions.)  
 The "Pounds of Organic VoHAP per Gallon of Product" represents the weight of organic VoHAP per unit volume (including volatile volume contribution.)  
 This chart is revised periodically. To obtain the most accurate values check for updates on a regular basis.

| Product Code | Applicable Use Category(ies)             | Density | Density | VOC Regulatory - Less Water Less Exempt | VOC Regulatory - Less Water Less Exempt | VOC Actual | VOC Actual | Wt. % Volatiles | Wt. % Water | Wt. % Exempt Compounds | Vol. % Water | Vol. % Exempt Compounds | Volatile Volume % | Pounds of Organic VoHAP per Gallon of Product |
|--------------|--|---------|---------|---|---|------------|------------|-----------------|-------------|------------------------|--------------|-------------------------|-------------------|---|
|              |  | lbs/gal | gm/ltr  | lbs/gal                                 | gm/ltr                                  | lbs/gal    | gm/ltr     |                 |             |                        |              |                         |                   |   |
| ESU469       |  | 7.69    | 921     | 5.14                                    | 616                                     | 5.13       | 614        | 66.9            | 0.1         | 0.2                    | 0            | 0.2                     | 72.2              | 0.08  |
| ESU470       | Primer                                   | 12.51   | 1499    | 1.72                                    | 206                                     | 1.32       | 158        | 27.6            | 0           | 17                     | 0.1          | 23.4                    | 42.6              | 0.39  |
| ESU478       | Primer (Hardener)                        | 9.03    | 1082    | 2.75                                    | 329                                     | 1.87       | 225        | 60              | 0           | 39.3                   | 0            | 31.7                    | 58.4              | 1.18  |
| ESU479       | Primer (Hardener)                        | 8.7     | 1042    | 2.77                                    | 332                                     | 2.2        | 264        | 51.8            | 0           | 26.4                   | 0            | 20.6                    | 52.3              | 1.29  |
| ESU480       | Primer, Primer Sealer                    | 12.24   | 1467    | 1.85                                    | 222                                     | 1          | 120        | 43.8            | 0.1         | 35.6                   | 0.1          | 45.8                    | 59.7              | 0.39  |
| ESU481       | Primer                                   | 12.22   | 1464    | 1.84                                    | 221                                     | 0.99       | 119        | 43.9            | 0.1         | 35.7                   | 0.1          | 46                      | 59.8              | 0.39  |
| ESU482       | Primer                                   | 12.25   | 1468    | 1.85                                    | 222                                     | 0.99       | 119        | 43.9            | 0.1         | 35.8                   | 0.1          | 46.2                    | 59.9              | 0.39  |
| ESU489       | Primer, Primer Sealer (Hardener)         | 8.27    | 991     | 2.69                                    | 322                                     | 2.43       | 291        | 42.3            | 0           | 12.9                   | 0            | 9.5                     | 42.4              | 1.54  |
| ESU489HDM    |  | 8.27    | 991     | 2.69                                    | 322                                     | 2.43       | 291        | 42.3            | 0           | 12.9                   | 0            | 9.5                     | 42.4              | 1.54  |
| ESX500       | Single-Stage Ctg (Additive)              | 9.55    | 1144    | 7.92                                    | 949                                     | 2.09       | 251        | 99.5            | 0.1         | 77.5                   | 0.1          | 73.5                    | 99.5              | 0   |
| ESX510       | Single-Stage Ctg (Additive)              | 9.55    | 1144    | 7.99                                    | 957                                     | 2.09       | 251        | 99.7            | 0.1         | 77.7                   | 0.1          | 73.7                    | 99.7              | 0   |
| ESX520       | Single-Stage Ctg (Additive)              | 9.55    | 1144    | 8.02                                    | 961                                     | 2.09       | 251        | 99.8            | 0.1         | 77.9                   | 0.1          | 73.8                    | 99.8              | 0   |
| ESX530       | Single-Stage Ctg (Additive)              | 9.56    | 1146    | 8.09                                    | 969                                     | 2.09       | 251        | 100             | 0.1         | 78                     | 0.1          | 74                      | 100               | 0   |
| ESX540       | Single-Stage Ctg (Additive)              | 9.03    | 1082    | 5.48                                    | 657                                     | 3.24       | 388        | 86.5            | 0           | 50.6                   | 0            | 40.9                    | 84.8              | 0   |
| ESX590       | Primer (Additive)                        | 8.15    | 977     | 8.01                                    | 959                                     | 7.98       | 957        | 98.3            | 0.1         | 0.2                    | 0.1          | 0.2                     | 98.4              | 0   |
| ESX711       | Uniform Finish Ctg, Clear Ctg (Additive) | 8.9     | 1066    | 0.02                                    | 2                                       | 0          | 0          | 99.7            | 0.2         | 99.6                   | 0.2          | 98.9                    | 99.7              | 0   |
| ESX721       | Uniform Finish Ctg, Clear Ctg (Additive) | 8.9     | 1066    | 0.09                                    | 11                                      | 0          | 0          | 99.9            | 0.2         | 99.7                   | 0.2          | 99                      | 99.9              | 0   |