

Texas VOC Chart Automotive Refinish Coatings Title 30 Part 01 115.421(12)



Applies to regulated regions of the Dallas-Fort Worth area (Collin, Dallas, Denton, Ellis, Johnson, Kaufman, Parker, Rockwall, and Tarrant Counties), the Houston-Galveston-Brazoria area (Brazoria, Chambers, Fort Bend, Galveston, Harris, Liberty, Montgomery, and Waller Counties), and the El Paso area (El Paso County).

In Effect: 1/1/2013

Coating Category	Ibs/U.S. gal (g/L) Limit: VOC Regulatory (Less Water Less Exempts).		
Wipe Down Solution (Surface Cleaner)*	1.4 (168)		
Pre-Treatment Wash Primer	6.5 (780)		
Primer Surfacer	4.8 (576)**		
Primer Sealer	4.6 (552)**		
Single Stage Coating	5.0 (600)		
Multi Stage Coating (2 Stage - BC/CC)	5.0 (600)		
Multi Stage Coating (3 or more Stages - BC/CC)	5.2 (624)	*VOC content value.	
Specialty Coatings	7.0 (840)	**Federal EPA Rule Limit	

Product Code & Name	Hardener/ Activator	Reducer	Mix Ratio	VOC Content
Solvent (Surface Cleaner)				Limit: 1.4 lbs/gal (168 g/L)
SWX350 H ₂ O-SO-CLEAN [®] Wax and Grease Remover	-	-	-	0.17 (20)
SX394 1.4 Low VOC Cleaner	-	-	-	1.34 (161)
TCEQ has ruled SXA type aerosol substrate cleaners used for auto refinish applications are not allowed within the regulated regions of the Dallas-Fort Worth area (Collin, Dallas, Den-				

TCEQ has ruled SXA type aerosol substrate cleaners <u>used for auto refinish applications</u> are not allowed within the regulated regions of the Dallas-Fort Worth area (Collin, Dallas, Denton, Ellis, Johnson, Kaufman, Parker, Rockwall, and Tarrant Counties), the Houston-Galveston-Brazoria area (Brazoria, Chambers, Fort Bend, Galveston, Harris, Liberty, Montgomery, and Waller Counties), and the El Paso area (El Paso County).

Product Code & Name	Hardener/Activator	Reducer	Additives	Mix Ratio	Applied VOC Less Water Less Exempt
Pre-Treatment Coatings				Lim	nit: 6.5 lbs/gal (780 g/L)
MP220 Chrome Free Etch Primer	MP222	-	-	1:1	6.04 (724)
SX1071 ECOBASE [®] 5.5 Etch Prime	SX1072	-	-	1:1	5.48 (657)
SXA1031 Etch Primer - Gray	-	-	-	Aerosol	N/A
Primer Surfacer				Lir	nit 4.8 lbs/gal (576 g/L)
SX1060 2K Rollable Surfacer	SX1061	-	-	4:1	4.18 (501)
MP182 2K Urethane Surfacer	MH165, MH166	-	-	5:1	4.20 (502)
MP182 2K Urethane Surfacer W/ MTK color	MH165, MH166	-	-	4:1:1	4.30 (515)
MP243 Polyester Primer	MEKP (MX199)	-	-	1 tube/qt	1.64 (196)
MP281 1K Light Gray Primer Surfacer	-	MS250	-	1:1	4.80 (575)
MP282 High Build 2K Primer Surfacer	MH283, MH284	MR18x	-	4:1:1	4.66 (558)
MP80x 2.1 VOC Multi-Purpose Primer	MH810	MR18x	-	4:1:1	3.82 (458)
MP80x 2.1 VOC Multi-Purpose Primer	MH810	MR29x	-	4:1:2	1.96 (236)
MP871 2.1 VOC Epoxy Primer	MP875	MR29x	-	2:1:1	2.07 (248)
Primer Sealer (apply over previously coated	surfaces)			Lim	nit: 4.6 lbs/gal (552 g/L)
MP17x Epoxy Primer	MP175	-	-	2:1	4.54 (539)
MP213 GP Sealer	-	MR18x	-	4:1	4.60 (552)
MP23x 2K Urethane Sealer	MH283, MH284	MR18x	-	4:1:1	4.54 (544)
MP80x 2.1 VOC Multi-Purpose Primer	MH810	MR18x	MC262	3:1:1:1	3.49 (418)
MP80x 2.1 VOC Multi-Purpose Primer	MH810	MR29X	MC262	3:1:1:1	2.02 (242)
MP871 2.1 VOC Epoxy Primer	MP875	MR29X	-	2:2:1	2.07 (248)
MP89x 2.1 VOC Urethane Sealers	MH810	MR29x	-	4:1:1	2.01 (241)



Texas VOC Chart Automotive Refinish Coatings Title 30 Part 01 115.421(12)



Applies to regulated regions of the Dallas-Fort Worth area (Collin, Dallas, Denton, Ellis, Johnson, Kaufman, Parker, Rockwall, and Tarrant Counties), the Houston-Galveston-Brazoria area (Brazoria, Chambers, Fort Bend, Galveston, Harris, Liberty, Montgomery, and Waller Counties), and the El Paso area (El Paso County).

In Effect: 1/1/2013

Product Code & Name	Hardener/Activator	Reducer	Additives	Mix Ratio	Applied VOC Less Water Less Exempt
Single Stage Coating				Limi	t: 5.0 lbs/gal (600 g/L)
MAE Acrylic Enamel	-	MR18x	-	4:1	5.0 (599)
MAE Acrylic Enamel Activated	MH101, MH202	MR18x	-	8:1:1	5.0 (599)
MLX 2.8 VOC Acrylic Enamel	MH238	MR29x	-	4:1:1	2.76 (331)
MTK Acrylic Urethane Single Stage	MH16x	MR18x	-	4:1:1	5.0 (599)
MTX 2.8 VOC Single Stage	MH238	MR29x	-	4:1:2	2.8 (335)
Multi-Stage Topcoat System			System VOC	Limit ^{1,2} : 5.0 / 5.2	lbs/gal (600 / 624 g/L)
Color Coating				Limit ²	²: 6.3 lbs/gal (755 g/L)
MBC Acrylic Basecoat	-	MR18x	-	1:1	6.29 (755)
MBP OMNI® Plus Acrylic Urethane Basecoat	-	MR18x	-	1:1	6.3 (755)
MBX Omni 3.5 VOC Acrylic Basecoat	-	MR29x	-	1:1	3.5 (419)
Use MBPX blend to sp	ray mix recommendation w	vithout MH238 only with c	olor formulas th	nat contain M799	
MBPX Omni Plus 3.5 Basecoat	-	MR29x	-	1:1	3.48 (417)
Use MBPX blend to spra	y mix recommendations wi	th MH238 with all historic	color formulas	that contain M73	6
MBPX Omni Plus 3.5 Basecoat	MH238	MR29x	-	10:1:10	3.48 (417)
MBPX Omni Plus 3.5 Basecoat	MH238	MR29x	-	10:1:5	3.48 (417)
Clear Coating				Limit ²	: 4.3 lbs/gal (515 g/L)
MC161 High Solids Urethane Clear	MH16x	-	-	2:1	4.18 (500)
MC250 Urethane Clearcoat	MH25x	-	-	4:1	4.14 (496)
MC260 Quick Clear	MH16x	-	-	2:1	4.29 (514)
MC262 Omni 2.1 VOC 4+1 Urethane Clear	MH266, MH267	-	-	4:1	2.08 (249)
MC270 4.2 VOC Production clear	MH27x	-	-	4:1	4.18 (501)
MC730 2.1 VOC Production Clear	MH737, MH738, MH739	MR295, MR296	-	4:1:0.5	2.08 (249)
MC760 2.1 VOC Universal Clear	MH267, MH268	MR295, MR296	-	4:1:1	2.08 (249)
MC2910 2.1 VOC EUROPLUS [®] Multi-Panel Clearcoat	MH2918, MH2919	-	-	2:1	1.95 (234)
MC2980 2.1 VOC Europlus Clear	MH2981, MH2982, MH2983	-	-	2:1	2.08 (249)

The VOC limit on Tri-Coat and Quad-Coat Multi-Stage Systems is 5.2 lbs/gal. The VOC of the BC/CC (Multi-stage) system is found by BC/CC composite calculation, where the VOC_{sys} = (VOC_{bc} + 2VOC_{cc}) / 3, as specified by current air quality regulations. Specialty coatings include, but are not limited to, the listed products 1. 2. 3.

Additional Products (listing not intended to be all inclusive)				
SLV4985 Universal Flattening Agent	SU4901 Clean and Scuff Sponge	SXA1044 High Build Flexible Surfacer (Aerosol)		
SLV73 Fisheye Eliminator	SUA4903 Advanced Plastic Bond (Aerosol)	SXA1050 Plastic Adhesion Promoter (Aerosol)		
SLV814 Universal Flexibilizer	SWX100 Waterborne Gun Cleaner	SX1047 High Build WB Flexible Surfacer		
SLV840 Uniform Finish Blender	SXA840 Uniform Finish Blender (Aerosol)	SU470LV 1K Compliant Adhesion Promoter		
SLV898 Retarder	SXA1030 Black Guide Coat (Aerosol)	SXA1041 Bumper Black (Aerosol)		

This "State of Texas Title 30, Part 01 115.421(a) (8) (B) (PPG *OMNI*)" wall chart is intended to provide INFORMATION to PPG's customers. In providing this wall chart, PPG makes no separate or additional warranties, express or implied, and assumes no liability or responsibility arising out of its use. It is the responsibility of each customer, RE-SELLER AND END USER of PPG's products to independently ascertain that their practices are legal, appropriate and constitute sound product stewardship. This "State of Texas Title 30, Part 01 115.421(a) (8) (B) (PPG *OMNI*)" wall chart does not include all currently compliant *OMNI* products. The representative products listed are compliant with State of Texas Title 30, Part 01 115.421(a) (8) (B) (PPG *OMNI*)" wall chart does not include all currently compliant *OMNI* products. It is the responsibility of the date of this wall chart; however, subsequent changes in State of Texas Title 30, Part 01 115.421(a) (8) (B) VOC limits as of the date of this wall chart; however, subsequent changes in State of Texas Title 30, Part 01 115.421(a) (8) (B) way change the compliance status of the listed products. It is the responsibility of the end user to review and comply with current regulations, including applicable coating category VOC limits, as of the date of product purchase and/or use. This document is not INTENDED to define or create legal rights or obligations. It is the responsibility of each customer, RE-SELLER AND END USER to comply with all and local lever. with all applicable federal, state and local laws.

© 2019 Copyright PPG Industries, Inc. All rights reserved www.ppgrefinish.com

The PPG Logo Acryli-Clean, Multi-Prep, Ecobase, EuroPlus, H2O-So-Clean, and Omni are registered trademarks of PPG Industries Ohio, Inc.