

Ventura County APCD Motor Vehicle and Mobile Equipment Coating Operations **Rule 74.18**





Amended: 11/11/2008 | In Effect: 01/01/2010

Coating Category	lbs/gal (g/L)		Limit:VOC Regulatory (Less Water Less Exempts)						
Solvent (Surface Cleaner)		.21 (25)*	* VOC content applies to this category only						
Pretreatments Coating	5	5.5 (660)							
Primer/Primer Surfacer	2	.1 (250)	·						
Primer Sealer	2	.1 (250)							
		.8 (340)							
Color Coating			(420) (250)						
Clear Coating	3								
Uniform Finish Coating	4	.5 (540)							
Adhesion Promoter	4	.5 (540)							
Product Code & Name			Reducer	Mix Ratio	VOC Content				
Solvent (Substrate Cleaner)			Limit: 0.2	1 lbs/gal (25 g/L)					
CFX435LV - Low VOC Cleaner		Water	1:1	0.20 (25)					
SWX350 H2O-SO-CLEAN® Wax and 0	\ r	vvalei	1.1	0.17 (20)					
SX1009 2.9 VOC Bug and Tar Remove	;ı			2.89 (346)					
	· low use evemption	maximum 120 lba/a	olondor voor	2.09 (340)					
*Section C.12 Prior written approval of APCO required under low use exemption, maximum 130 lbs/calendar year.									
Product Code & Name		Hardener/	Reducer	Mix Ratio	Applied VOC Less Water				
Floudet Code & Name		Activator	Reducei	IVIIX Natio	Less Exempt				
Pretreatment Coating			Limit: 5.5	lbs/gal (660 g/L)					
F4945 5.5 VOC Wash Primer		F4946	-	1:1	5.32 (637)				
SXA1031 Etch Primer – Gray		-	-	Aerosol	N/A				
Product Code & Name	Hardener/	Additives	Reducer	Mix Ratio	Applied VOC				
					Less Water				
	Activator				Less Exempt				
Primer/Primer Surfacer	ı	ı	ı	Limit: 2.1	Ibs/gal (250 g/L)				
ESU410 2.1/2.8 Polyurethane	ESU419	ESX590	_	5:1+6 oz / RTS gal	1.99 (238)				
Primer ESU470 2.1 VOC Wet on Wet			E00000	2:1:1or2:1:2	(/				
ES0470 2.1 VOC Wet on Wet Epoxy Primer - Gray	ESU479	-	ESR300 or ESR310	(reducer last)	2.07 (248)				
ESU480/481/482 2.1 VOC Epoxy			ESKSIU	(reducer last)					
Primer	ESU489	-	-	4:1	2.09 (250)				
		50.400	F0005 F0000	3:1 +6 oz / RTS					
F3970/BK/WH Ultra High Solids	F3971	F3400 or	F3385, F3390	gal + 10% optional	2.07 (248)				
Primer		F3405	or F3395	reducer	, ,				
F3998 2.1 VOC Primer Surfacer	F3999	-	-	2:1	1.99 (238)				
F4921/BK/WH 2.1 VOC Epoxy	F4922	_	F3385, F3390	3:1:1	2.05 (246)				
Primer	1 1022		or F3395	0.1.1	2.00 (2.10)				
F4932/BK/WH 2.1 VOC Fast Dry	F4933	-	F3385, F3390	4:1:1	2.08 (249)				
Urethane Surfacer F4935/36/37 High Solids Epoxy			or F3395		· - /				
Primers	F4938	-	-	1:1	2.08 (249)				
Single-Stage Coating				l imit· 28	lbs/gal (340 g/L)				
ESSS Single Stage Polyurethane									
Enamel	ESH200	ESX5XX	-	6 : 1 :1	2.76 (331)				
FDGU Single Stage Ultra high Solids		F3400, F3405	F3385, F3390	3:1+6 oz /RTS gal					
Polyurethane Enamel	F3260	or F3410	or F3395	+ 10% reducer	2.82 (338)				
	1			3:1+6 oz /RTS gal	2.82 (338)				
FDSU Ultra HS Polyurethane Single	F3260	F3400, F3405	F3385, F3390	3.1+002/K13 yai i	0.00 (000)				

Ventura County APCD Rule 74.18 – PPG DELFLEET® Evolution and DELFLEET ESSENTIAL®



Ventura County APCD Motor Vehicle and Mobile Equipment Coating Operations

Delfleet

ESSENTIAL

Rule 74.18
Amended: 11/11/2008 | In Effect: 01/01/2010

Product Code & Name	Hardener/ Activator	Additives	Reducer	Mix Ratio	Applied VOC Less Water Less Exempt	
Color Coating				Limit: 3.5 lbs/gal (420 g/L)		
ESSS Basecoat Polyurethane Basecoat	ESH210	ESB800	-	2:1:1	3.04 (364)	
FBCH High Solids Polyurethane Basecoat	F3200, F3259 or F3260	F3440, F3441 or F3442	-	3:1:1	3.47 (416)	
FBCS High Solids Basecoat - Fast	F3200 or F3260-	-	F3385	3 : 1 + 10%	3.04 (364)	
FBCS High Solids Basecoat - Fast	F3200 or F3260-	-	F3330, F3340, F3350 or F3360	3 : 1 + 10%	3.41 (409)	
Product Code & Name	Hardener/ Activator	Additives	Reducer	Mix Ratio	Applied VOC Less Water Less Exempt	
Clear Coating Limit: 2.1 lbs/gal (250 g/						
ESC621 2.1 VOC Clearcoat	ESH200	-	ESX711, ESX721, ESR300 or ESR310	4:1:1	2.06 (247)	
F3921 2.1 VOC Clearcoat	F3210 or F3211	-	F3385, F3390 or F3395	3 : 1 : 1/2	2.05 (246)	
Additional Products: (listing not intend	ed to be all inclus	sive)				
FBCH500 FBCH Blending Clear	SLV73 F	isheye Eliminator		SUA4903 Advanced Plastic Bond		
FDGU500 FDGU Blending Clear	SU4901	Clean and Scuff S	ponge	SXA840 Blending Solvent		

Ventura County APCD Rule 74.18 - PPG DELFLEET® Evolution and DELFLEET ESSENTIAL®

This "Ventura County APCD R74.18 (PPG Delfleet)" wall chart is intended to provide INFORMATION to PPG's customers. In providing this wall chart, PPG makes no separate or additional warranties, express or implied, and assumes no liability or responsibility arising out of its use. It is the responsibility of each customer, RE-SELLER AND END USER of PPG's products to independently ascertain that their practices are legal, appropriate and constitute sound product stewardship. This "Ventura County APCD R74.18 (PPG Delfleet)" wall chart does not include all currently compliant Delfleet products. The representative products listed are compliant with Ventura County APCD R74.18 VOC limits as of the date of this wall chart; however, subsequent changes in Ventura County APCD R74.18 may change the compliance status of the listed products. It is the responsibility of the end user to review and comply with current regulations, including applicable coating category VOC limits, as of the date of product purchase and/or use. This document is not INTENDED to define or create legal rights or obligations. It is the responsibility of each customer, RE-SELLER AND END USER to comply with all applicable federal, state and local laws.



PPG Industries, Inc. Commercial Coatings 19699 Progress Drive Strongsville, OH 44149 1-800-647-6050

PPG Canada Inc. 2301 Royal Windsor Drive, Unit #6 Mississauga, Ontario L5J 1K5 1-888-310-4762