

State of Delaware

Mobile Equipment Repair and Refinishing **Title 7 Regulation 1124 Section 11.0** Amended: 10/11/2010 | In Effect: 1/1/2012



Any facility obtaining a permit after 10/10/10 is required to comply with this regulation immediately, those with a permit in place before that date must comply as of Jan 1, 2012 (as stated in 11.1.5)

Coating Category	Ibs/gal (g/L) Limit: VOC Regulatory (Less Water Less Exempts).		
Solvent (Surface Cleaner)*	0.21 (25)		
Pretreatment Coating	5.5 (660)		
Primer / Primer Surfacer	2.1 (250)		
Primer Sealer	2.1 (250)		
Single Stage Coating	2.8 (340)		
Color Coating	3.5 (420)		
Underbody Coating	3.6 (430)		
Clear Coating	2.1 (250)		
Adhesion Promoter	4.5 (540)	* VOC content applies to this category only.	

Product Code & Name	Hardener/Activator	Reducer	Mix Ratio	VOC Content
Solvent (Surface Cleaner)				Limit: 0.21 lbs/gal (25 g/L)
SWX350 H2O-So-Clean Wax & Grease Remover	-	-	-	0.17 (20)
SX1005 Low VOC Wax & Grease Remover	-	Water	1:1	0.21 (25)
SX1009 2.9 VOC Bug & Tar Remover*	-	-	-	2.89 (346)
*11.3.2.1 Special cleaning solvent for use in specific an	d difficult cleaning tasks assoc	viated with surface	preparation with VOC conten	It no greater than 350 g/l

*11.3.2.1 Special cleaning solvent for use in specific and difficult cleaning tasks associated with surface preparation with VOC content no greater than 350 g/L may be used at a volume equal to 2.5% of the preceding year's annual coating usage up to a maximum of 40 gallons per year.

Product Code & Name	Hardener/Activator	Reducer	Additives	Mix Ratio	Applied VOC Less Water Less Exempt
Pretreatment Coatings				Limit: 5	.5 lbs/gal (660 g/L)
SX1071 Etch Prime	SX1072	-	-	1:1	5.48 (657)
SXA1031 Etch Primer - Gray	-	-	-	Aerosol	N/A
Primer / Primer Surfacer				Limit 2	.1 lbs/gal (250 g/L)
DPLV 305X Acrylic Urethane Surfacer	DHLV3030	DT18XX Series	-	4:1:1	2.03 (243)
DPLV 305X Acrylic Urethane Surfacer	DHLV3030	-	-	4:1	2.03 (243)
DPLV 2.1 Epoxy Primer	DP401LV	DT18XX Series	-	2:1:1	2.09 (250)
DS1002 UV Cured Primer Surfacer	-	-	-	Aerosol	N/A
ECP1X A-Chromatic Surfacer	EH391	DT18XX Series	-	4:1:1	2.09 (250)
ECP1X A-Chromatic Surfacer	EH391	DT18XX Series	-	4:1	2.08 (249)
ECP1X A-Chromatic Surfacer	EH391	DT18XX Series	EA157	4:1:1 + 10%	2.09 (250)
EPW115 Waterborne Speed Prime	-	T494	-	1:13%	.72 (86)
NCP280 2.1 VOC Primer Surfacer	NCX285	-	-	2:1	2.10 (250)
NCP280 2.1 VOC Primer Surfacer	NCX285	-	-	2:1+10% Acetone	2.1 (250)
Primer Sealer (apply over previously co	oated surfaces)			Limit: 2	.1 lbs/gal (250 g/L)
ECS2X A-Chromatic LV Sealer	EH391	D8764, D8774, D8767	-	4:1:1	1.82 (246)
Single Stage Coating				Limit: 2	8 lbs/gal (340 g/L)
ENVIROBASE [®] Interior System	T584	T494	-	100:15:15	2.79 (334)



State of Delaware

Mobile Equipment Repair and Refinishing **Title 7 Regulation 1124 Section 11.0** Amended: 10/11/2010 In Effect: 1/1/2012



Any facility obtaining a permit after 10/10/10 is required to comply with this regulation immediately, those with a permit in place before that date must comply as of Jan 1, 2012 (as stated in 11.1.5)

Product Code & Name	Hardener/Activator	Reducer	Additives	Mix Ratio	Applied VOC Less Water Less Exempt
Color Coating				Lin	nit: 3.5 lbs/gal (420 g/L)
Envirobase Waterborne Basecoat	-	T494	-	100:10	3.35 (401)
Envirobase Waterborne Basecoat	-	T494	-	100:20	3.40 (407)
Envirobase Waterborne Basecoat	-	T494	-	100:30	3.50 (419)
Envirobase Waterborne Basecoat	-	-	T492	100:10	3.36 (403)
Envirobase Waterborne Basecoat	-	T494	T492	100:10:10	3.38 (405)
Envirobase Waterborne Basecoat	-	T494	T492	100:20:10	3.40 (407)
Envirobase Waterborne Basecoat	T581	T494	-	100:10:10	3.05 (336)
Envirobase Waterborne Basecoat	T581	T494	-	100:10:20	3.09 (370)
Envirobase Waterborne Basecoat	T581	T494	-	100:10:30	3.11 (373)
Underbody Coating				Lin	nit: 3.6 lbs/gal (430 g/L)
Internal Repair System	T581	T494	-	100:15:15	3.08 (369)
Clear Coating				Lin	nit: 2.1 lbs/gal (250 g/L)
DC3010 Deltron High Velocity Clear	DCH36XX	-	-	2:1	2.00 (240)
DC4010 Velocity Premium Clear	DCH36XX	D8767	-	3:1:10%	2.05 (246)
DC4010 Velocity Premium Clear	DCH36XX	-	-	4:1	2.08 (249)
DCU2010 2.1 Speed Clear	DCX20XX	-	-	2:1	2.05 (246)
DC4125 Ceramiclear Clearcoat	DCH4126	-	-	4:1	2.07 (248)
EC700 OneVisit Production Clear	ECH70XX	-	-	4:1	2.08 (249)
EC700 OneVisit Production Clear	ECH70XX	D87XX	EA10	4:1:0.5 +5%	2.08 (249)
EC750 OneVisit Appearance Clear	ECH70XX	-	-	4:1	2.08 (249)
EC800 Ultra Fast 2.1 Clearcoat	ECH8075 ECH8075	D8767, DT1855 ECA83	-	4:1:1 4:1:1	2.08 (249) 1.90 (228)

Additional Products (listing not intended to be all inclusive)			
DX101 Sanding Paste	SUA4903 Advanced Plastic Bond (Aerosol)	SXA1050 Plastic Adhesion Promoter (Aerosol)	
DX310 EZ Cleaner	SWX100 Waterborne Gun Cleaner	SX1047 High Build WB Flexible Surfacer	
SLV4985 Universal Flattening Agent	SXA840 Uniform Finish Blender (Aerosol)	SU460LV 1K Compliant Adhesion Promoter	
SLV73 Fisheye Eliminator	SXA1030 Black Guide Coat (Aerosol)	SU4901 Clean and Scuff Sponge	
SLV814 Universal Flexibilizer	SXA1033 Texture Spray		
SLV840 Uniform Finish Blender	SXA1041 Bumper Black (Aerosol)		

This "State of Delaware Title 7 Regulation 1124 Section 11.0 (PPG *Deltron*)" wall chart is intended to provide INFORMATION to PPG's customers. In providing this wall chart, PPG makes no separate or additional warranties, express or implied, and assumes no liability or responsibility arising out of its use. It is the responsibility of each customer, RE-SELLER AND END USER of PPG's products to independently ascertain that their practices are legal, appropriate and constitute sound product stewardship. This "State of Delaware Title 7 Regulation 1124 Section 11.0 (PPG *Deltron*)" wall chart does not include all currently compliant *Deltron* products. The representative products listed are compliant with State of Delaware Title 7 Regulation 11.0 VOC limits as of the date of this wall chart; however, subsequent changes in State of Delaware Title 7 Regulation 11.0 VOC limits, as of the date of this wall chart; however, subsequent changes applicable coating category VOC limits, as of the date of product purchase and/or use. This document is not INTENDED to define or create legal rights or obligations. It is the responsibility of each customer, RE-SELLER AND END USER to comply with all applicable federal, state and local laws.

The PPG logo, Deltron and Envirobase are registered trademarks of PPG Industries of Ohio, Inc.