


Canadian National Rule

VOC Concentration Limits for Automotive Refinishing Products Regulations





Coating Category	g/L/ lbs/U.S.gal Limit: VOC Regulatory (Less Water Less Exempts).		
Solvent (Surface Cleaner)*	50 (0.42)		
Pre-Treatment Wash Primer	660 (5.5)		
Primer Surfacer	250 (2.1)		
Primer Sealer	340 (2.8)		
Single Stage Coating	420 (3.5)		
Colour Coating	420 (3.5)		
Underbody Coating	430 (3.6)		
Clear Coating	250 (2.1)		
Uniform Finish Coating	540 (4.5)	*VOC concentration of a Surface Cleaner applies to this	
Adhesion Promoter	840 (7.0)	category.	

		Lie		
		Limit: 50 g/L (0.42 lbs/U.S. gal)		
-	-	-	20 (0.17)	
-	Water	1:2	24 (0.20)	
-	-	As is	50 (0.42)	
-	Water	1:1	25 (0.21)	
-	-	Aerosol	N/A	
-	-	Aerosol	N/A	
-	-	-	762 (6.36)	
	y bottle.	- Water	As is - Water 1:1 Aerosol Aerosol Aerosol	


Product Code & Name	Hardener/Activator	Reducer	Additives	Mix Ratio	Applied VOC Less Water Less Exempt
Pretreatment Wash Primer				Limit: 660 g/L	(5.5 lbs/U.S. gal)
SX1071 Etch Prime	-	SX1072	-	1:1	5.48 (657)
SXA1031 Etch Primer - Gray	-	-	-	Aerosol	N/A
Primer Surfacer				Limit: 250 g/L	(2.1 lbs/U.S. gal)
DPLV 2.1 Epoxy Primer	DP401LV	D8764, D8774, D8767	-	2:1:1	250 (2.09)
DPLV 2.1 Epoxy Primer	DP401LV	DT18XX	-	2:1:1	250 (2.09)
DS1002 UV Cured Primer Surfacer	-	-	-	Aerosol	N/A
ECP1X A-Chromatic Surfacer	EH391	D8764, D8774, D8767		4:1:1	249 (2.08)
ECP1X A-Chromatic Surfacer	EH391	D8764, D8774, D8767		4:1	249 (2.08)
ECP1X A-Chromatic Surfacer	EH391	D8764, D8774, D8767	EA157	4:1:1 + 10%	250 (2.09)
EPW115 Waterborne Speed Prime		T494		1:13%	86 (0.72)
NCP280 2.1 VOC Primer Surfacer	NCX285			2:1	250 (2.10)
NCP280 2.1 VOC Primer Surfacer	NCX285			2:1+10% Acetone	250 (2.10)
Primer Sealer (apply over previously c	oated surfaces)			Limit: 340 g/L	(2.8 lbs/U.S. gal)
ECS6X A-Chromatic Sealer	EH391, EH392	D8764, D8774, D8767	-	3:1:1	329 (2.75)
Single Stage Coating				Limit: 420 g/L	(3.5 lbs/U.S. gal)
ENVIROBASE® Interior System	T584	T494	-	100:15:15	334 (2.79)

© 2013 PPG Industries 1 VOC CAN DEL (9/13)



Canadian National Rule

VOC Concentration Limits for Automotive Refinishing Products Regulations



Published: 6/18/2009 Effective: 6/18/2009

Product Code & Name	Hardener/Activator	Reducer	Additives	Mix Ratio	Applied VOC Less Water Less Exempt
Color Coating				Limit: 4	20 g/L (3.5 lbs/U.S. gal)
Envirobase Waterborne Basecoat	-	T494	-	100:10	3.35 (401)
Envirobase Waterborne Basecoat	-	T494	-	100:20	3.40 (407)
Envirobase Waterborne Basecoat	-	T494	-	100:30	3.50 (419)
Envirobase Waterborne Basecoat	-	-	T492	100:10	3.36 (403)
Envirobase Waterborne Basecoat	-	T494	T492	100:10:10	3.38 (405)
Envirobase Waterborne Basecoat	-	T494	T492	100:20:10	3.40 (407)
Envirobase Waterborne Basecoat	T581	T494	-	100:10:10	3.05 (336)
Envirobase Waterborne Basecoat	T581	T494	-	100:10:20	3.09 (370)
Envirobase Waterborne Basecoat	T581	T494	-	100:10:30	3.11 (373)
Underbody Coating				Limit: 4	30 g/L (3.6 lbs/U.S. gal)
Internal Repair System	T581	T494	-	100:15:15	369 (3.08)
Clear Coating				Limit: 2	50 g/L (2.1 lbs/U.S. gal)
DC4010 Velocity Premium Clear	DCH36XX	-	-	4:1	244 (2.04)
DC4010 Velocity Premium Clear	DCH36XX	-	EA10	4:1 + 10%	244 (2.04)
DC4125 Ceramiclear Clearcoat	DCH4126	-	-	2:1	246 (2.05)
EC700 OneVisit Production Clearcoat	ECH70XX	-	=	4:1	249 (2.08)
EC700 OneVisit Production Clearcoat	ECH70XX	D87XX	-	4:1:.05	249 (2.08)
EC700 OneVisit Production Clearcoat	ECH70XX	D87XX	EA10	4:1:.05 + 10%	249 (2.08)
EC750 OneVisit Appearance Clearcoat	ECH70XX	D87XX		4:1	249 (2.08)
EC750 OneVisit Appearance Clearcoat	ECH70XX	D87XX	-	4:1:.05	249 (2.08)
EC800 Ultra Fast 2.1 Clearcoat	ECH8075 ECH8075	D8767/ DT1855 ECA83		4:1:1 4:1:1	249 (2.08) 249 (2.08)

Additional Products (listing not intended to be all inclusive)			
DPX801 Universal Plastics Primer	SU460LV 1K Compliant Adhesion Promoter	SXA1030 Black Guide Coat	
DX101 Sanding Paste	SU4901 Clean and Scuff Sponge	SXA1041 Bumper Black	
DX310 EZ Cleaner	SU4902 Plastic Prep Wipe	SXA1050 Plastic Adhesion Promoter	
SLV4985 Universal Flattening Agent	SU4903 Advanced Plastic Bond	SX1050 Plastic Adhesion Promoter	
SLV73 Fisheye Eliminator	SUA4903 Advanced Plastic Bond	SXA1033 Texture Spray	
SLV814 Universal Flexibilizer	SWX100 Waterborne Gun Cleaner		
SLV840 Uniform Finish Blender	SXA840 Uniform Finish Blender		

This "Canadian National Rule (PPG Deltron)" wall chart is intended to provide INFORMATION to PPG's customers. In providing this wall chart, PPG makes no separate or additional warranties, express or implied, and assumes no liability or responsibility arising out of its use. It is the responsibility of each customer, RE-SELLER AND END USER of PPG's products to independently ascertain that their practices are legal, appropriate and constitute sound product stewardship. This "Canadian National Rule (PPG Deltron)" wall chart does not include all currently compliant Deltron products. The representative products listed are compliant with Canadian National Rule VOC limits as of the date of this wall chart; however, subsequent changes in Canadian National Rule may change the compliance status of the listed products. It is the responsibility of the end user to review and comply with current regulations, including applicable coating category VOC limits, as of the date of product purchase and/or use. This document is not INTENDED to define or create legal rights or obligations. It is the responsibility of each customer, RE-SELLER AND END USER to comply with all applicable federal, state and local laws.