



FLEXcon[®] Fit Test Hood

Single-use Replacement Test Hoods for Qualitative Fit Testing

PRODUCT INFORMATION

FEATURES & BENEFITS

Product Contents Indications for Use	FLEXcon Fit Test Hood Single-use test hood Single-use replacement test hood for qualitative fit testing	Disposable	Disposable single use product that prevents cross-contamination between several users.
	nood for quantative in testing	Full Visibility	Optically clear PET material that provides full visibility and easy
Part Number	FLX068565		reading of test page.
Product Dimensions	ID 24" OD 27" Length 24" Hole size 7/8" Hole Placement 10" from edge Distance from top 14"	Sturdy Structure	Opening remains in position for an easy application of the nebulizer nozzle.
Thickness	5 mil (0.005 inch)	Comfortable	Great for claustrophobic users
Color	Clear		as it provides 360° visibility.
Material	Polyester Film	Recyclable	Made of PET material that can
Clarity	99.7%	- ,	be easily recycled.
Haze	< 1%		
Manufactured	Spencer, MA	Use	Can be used with any Respirator Fit Test kit.









BODY CONTACTING MATERIALS PET Film

DISCLAIMER

These single-use hoods are intended to be used as a replacement to the reuseable hood that accompanies most general fit test kits. Includes the replacement hood only.

For Orders Please visit our


Please visit our webpage by scanning the QR code or visit the following URL www.flexcon.com/products/test-hood

Manufactured by: FLEXcon, 1 FLEXcon Industrial Park, Spencer, MA www.flexcon.com






FLEXcon® Fit Test Hood | Single-use Replacement Test Hoods for Qualitative Fit Testing




Orient the single-use hood so that the bottom opening is easily accessible. There is no front or back.



Ask the participant to properly apply the face mask.



Open the hood and place on the participant, make sure it fits right on the shoulders.



Place the nebulizer in the hole and disperse the solution.



Instruct the participant to read the story passage and check if they can detect the smell or taste of the solution.



Upon completion of the test, remove the hood and discard in the recycle bin.

Made in USA

Patent Pending

DISCLAIMER

These single-use hoods are intended to be used as a replacement to the reuseable hood that accompanies most general fit test kits. Includes the replacement hood only.



FOR ORDERS

Please visit our webpage by scanning the QR code or visit the following URL www.flexcon.com/products/test-hood