

Swaging Chart

FINN-POWER P32 MS / P51 / FP110 / FP120 / FP140

Hose type	Hose dimensions				Internal skive		External skive		Ferrule dimensions				Swage diam. Ø +/- 0.1 mm	Die set ref.	Adjustment
	(Inch)	Inner Ø	Outer Ø	Layers	Ø	Length	Ø	Length	Part No.	Ø	Length	Prod.code			
1 braided layer - thin rubber - Standard: EN 853-1SN / SAE 100 R1AT															
NST-HF 5	3/16"	5	11,4	1					SFA-D1-05	19,0	24,0	AD1-03	14,8	14	0,8
NST-HF 6	1/4"	6	13,0						SFA-D1-06	22,0	24,7	AD1-04	17,2	16	1,2
NST-HF 8	5/16"	8	14,5						SFA-D1-08	23,0	24,7	AD1-05	18,9	16	2,9
NST-HF 10	3/8"	10	17,2						SFA-D1-10	26,0	29,7	AD1-06	21,4	19	2,4
NST-HF 13	1/2"	13	20,1						SFA-D1-13	29,0	30,5	AD1-08	24,7	22	2,7
NST-HF 16	5/8"	16	23,1						SFA-D1-16	32,0	30,5	AD1-10	27,8	26	1,8
NST-HF 20	3/4"	19	27,3						SFA-D1-20	36,0	36,0	AD1-12	31,7	30	1,7
NST-HF 25	1"	25	35,2						SFA-D1-25	44,0	36,7	AD1-16	39,4	39	0,4
NST-HF 32	1-1/4"	32	42,5						SFA-D1-32	53,0	48,6	AD1-20	47,5	45	2,5
NST-HF 40	1-1/2"	38	49,7						SFA-D1-40	62,0	48,6	AD1-24	54,4	51	3,4
2 braided layers - thin rubber - Standard: EN 853-2SN / SAE 100 R2AT															
HST-HF 5	3/16"	5	13,0	2					SFA-D2-05	21,0	24,0	AD2-03	16,3	16	0,3
HST-HF 6	1/4"	6	14,5						SFA-D2-06	23,0	24,7	AD2-04	18,2	16	2,2
HST-HF 8	5/16"	8	16,1						SFA-D2-08	25,0	24,7	AD2-05	20,1	19	1,1
HST-HF 10	3/8"	10	18,5						SFA-D2-10	27,0	29,7	AD2-06	22,3	22	0,3
HST-HF 13	1/2"	13	21,4						SFA-D2-13	30,0	30,5	AD2-08	25,4	22	3,4
HST-HF 16	5/8"	16	24,6						SFA-D2-16	33,0	30,5	AD2-10	28,8	26	2,8
HST-HF 20	3/4"	19	29,0						SFA-D2-20	37,0	36,0	AD2-12	32,5	30	2,5
HST-HF 25	1"	25	36,8						SFA-D2-25	45,0	36,7	AD2-16	39,9	39	0,9
HST-HF 32	1-1/4"	32	46,4						SFA-D2-32	56,0	48,6	AD2-20	49,6	45	4,6
HST-HF 40	1-1/2"	38	53,7						SFA-D2-40	64,0	48,5	AD2-24	56,7	51	5,7
HST-HF 50	2"	51	65,9					SFA-D2-50	77,0	48,6	AD2-32	70,8	69	1,8	
1 braided layer compact hose - Standard: EN 857-1SC															
NSK 6	1/4"	6	12,1	1					SFA-D1-06	22,0	24,7	AD1-04	16,5	16	0,5
NSK 8	5/16"	8	14,1						SFA-D1-08	23,0	24,7	AD1-05	18,1	16	2,1
NSK 10	3/8"	10	15,6						SFA-D1-10	26,0	29,7	AD1-06	20,4	19	1,4
NSK 13	1/2"	13	19,5						SFA-D1-13	29,0	30,5	AD1-08	23,9	22	1,9
2 braided layers compact hose - Standard: EN 857-2C															
HSK-HF 6	1/4"	6	13,2	2					SFA-D1-06	22,0	24,7	AD1-04	17,4	16	1,4
HSK-HF 8	5/16"	8	14,5						SFA-D1-08	23,0	24,7	AD1-05	19,0	19	0,0
HSK-HF 10	3/8"	10	17,0						SFA-D1-10	26,0	29,7	AD1-06	21,2	19	2,2
HSK-HF 13	1/2"	13	20,3						SFA-D1-13	29,0	30,5	AD1-08	24,8	22	2,8
HSK-HF 16	5/8"	16	23,9						SFA-D1-16	32,0	30,5	AD1-10	27,9	26	1,9
HSK-HF 20	3/4"	19	27,7						SFA-D1-20	36,0	36,0	AD1-12	31,7	30	1,7
HSK-HF 25	1"	25	34,6						SFA-D1-25	44,0	36,7	AD1-16	39,4	39	0,4

It is important to check our download center for updates on a regular basis.
 The swage dimensions listed in the tables are approximate data. Due to variations in hose, coupling tolerances and slight deviation in the swaging machine differences may occur. All of the information contained in this document has been composed with the utmost care. Taking all of this into consideration, we cannot accept liability for any imperfections within this document.

Swaging Chart

FINN-POWER P32 MS / P51 / FP110 / FP120 / FP140

Hose type	Hose dimensions				Internal skive		External skive		Ferrule dimensions				Swage diam.	Die set ref.	Adjustment	
	(Inch)	Inner Ø	Outer Ø	Layers	Ø	Length	Ø	Length	Part No.	Ø	Length	Prod.code	Ø +/- 0.1 mm			
2 braided layers compact hose - Exceeds Standard: EN 857-2SC - SAE 100-R16																
HSK-PQ 6	1/4"	6	13,0	2					SFA-D1-06	22,0	24,7	AD1-04	17,4	16	1,4	
HSK-PQ 8	5/16"	8	14,5						SFA-D1-08	23,0	24,7	AD1-05	18,9	16	2,9	
HSK-PQ 10	3/8"	10	16,8						SFA-D1-10	26,0	29,7	AD1-06	21,3	19	2,3	
HSK-PQ 13	1/2"	13	20,6						SFA-D1-13	29,0	30,5	AD1-08	25,1	22	3,1	
HSK-PQ 16	5/8"	16	23,2						SFA-D1-16	32,0	30,5	AD1-10	27,9	26	1,9	
HSK-PQ 20	3/4"	19	27,6						SFA-D1-20	36,0	36,0	AD1-12	31,7	30	1,7	
HSK-PQ 25	1"	25	35,5						SFA-D1-25	44,0	36,7	AD1-16	39,8	39	0,8	
HSK-PQ 32	1-1/4"	32	42,0						SFA-D1-32	53,0	48,6	AD1-32	47,1	45	2,1	
HSK-PQ 40	1-1/2"	38	49,9						SFA-D1-40	61,0	48,6	AD1-40	54,7	51	3,7	
HSK-PQ 50	2"	51	63,5						SFA-D1-50	75,0	48,6	AD1-50	68,5	63	5,5	
HSK-ST-6	1/4"	6	13,0		2					SFA-D1-06	22,0	24,7	AD1-04	17,4	16	1,4
HSK-ST-8	5/16"	8	14,5						SFA-D1-08	23,0	24,7	AD1-05	18,9	16	2,9	
HSK-ST-10	3/8"	10	16,8						SFA-D1-10	26,0	29,7	AD1-06	21,3	19	2,3	
HSK-ST-13	1/2"	13	20,6						SFA-D1-13	29,0	30,5	AD1-08	25,1	22	3,1	
HSK-ST-16	5/8"	16	23,2						SFA-D1-16	32,0	30,5	AD1-10	27,9	26	1,9	
HSK-ST-20	3/4"	19	27,6						SFA-D1-20	36,0	36,0	AD1-12	31,7	30	1,7	
HSK-ST-25	1"	25	35,5						SFA-D1-25	44,0	36,7	AD1-16	39,8	39	0,8	
1 braided layer high temperature blue hose - Standard: EN 853-1SN / SAE 100 R1AT																
HT1SN-06	1/4"	6	12,7	1					SFA-D1-06	22,0	24,7	AD1-04	17,2	16	1,2	
HT1SN-10	3/8"	10	16,5						SFA-D1-10	26,0	29,7	AD1-06	21,4	19	2,4	
HT1SN-13	1/2"	13	19,9						SFA-D1-13	29,0	30,5	AD1-08	24,7	22	2,7	
HT1SN-16	5/8"	16	22,7						SFA-D1-16	32,0	30,5	AD1-10	27,8	26	1,8	
HT1SN-20	3/4"	19	27,0						SFA-D1-20	36,0	36,0	AD1-12	31,7	30	1,7	
HT1SN-25	1"	25	35,8						SFA-D1-25	44,0	36,7	AD1-16	39,4	39	0,4	
HT1SN-32	1-1/4"	32	42,1						SFA-D1-32	53,0	48,6	AD1-32	47,5	45	2,5	
HT1SN-40	1-1/2"	38	49,2						SFA-D1-40	61,0	48,6	AD1-40	54,4	51	3,4	
2 braided layers high temperature blue hose - Standard: EN 853-2SN / SAE 100 R2AT																
HT2SN-06	1/4"	6	14,2	2			12,4	19	SFA-4S-06	22,0	26,3	H1100404-04	17,0	16	1,0	
HT2SN-10	3/8"	10	18,4					16,3	19	SFA-4S-10	25,0	28,5	H1100404-06	21,4	19	2,4
HT2SN-13	1/2"	13	21,1					19,3	25	SFA-4S-13	29,0	34,7	H1100404-08	25,6	22	3,6
HT2SN-16	5/8"	16	24,5					22,5	28	SFA-4S-16	33,0	37,5	H1100404-10	28,2	26	2,2
HT2SN-20	3/4"	19	29,0					26,6	33	SFA-4S-20	37,0	41,5	H1100404-12	32,4	30	2,4
HT2SN-25	1"	25	37,4					34,4	37	SFA-4S-25	45,0	47,7	H1100404-16	40,7	39	1,7

It is important to check our download center for updates on a regular basis.
 The swage dimensions listed in the tables are approximate data. Due to variations in hose, coupling tolerances and slight deviation in the swaging machine differences may occur. All of the information contained in this document has been composed with the utmost care. Taking all of this into consideration, we cannot accept liability for any imperfections within this document.

Swaging Chart

FINN-POWER P32 MS / P51 / FP110 / FP120 / FP140

Hose type	Hose dimensions				Internal skive		External skive		Ferrule dimensions				Swage diam. Ø +/- 0.1 mm	Die set ref.	Adjustment	
	(Inch)	Inner Ø	Outer Ø	Layers	Ø	Length	Ø	Length	Part No.	Ø	Length	Prod.code				
Thermoplastic hose - 1 braided Polyamid layer - Standard: SAE 100 R7																
CR 7-5A	3/16"	5	9,6	1					SFA-TP0-05	15,0	22,0	TP0-03	12,0	12	0,0	
CR 7-6A	1/4"	6	12,2						SFA-TP0-06	17,0	26,5	TP0-04	14,2	14	0,2	
CR 7-8A	5/16"	8	14,3						SFA-TP0-08	19,0	26,5	TP0-05	16,3	16	0,3	
CR 7-10A	3/8"	10	16,0						SFA-TP0-10	22,0	26,5	TP0-06	18,6	16	2,6	
CR 7-13A	1/2"	13	20,3						SFA-TP0-13	26,0	30,5	TP0-08	22,7	22	0,7	
Thermoplastic hose - 1 braided Steel layer																
CR 8-5A	3/16"	5	9,8	1					SFA-TP0-05	15,0	22,0	TP0-03	12,3	12	0,3	
CR 8-6A	1/4"	6	11,9						SFA-TP0-06	17,0	26,5	TP0-04	14,1	14	0,1	
CR 8-8A	5/16"	8	13,2						SFA-TP0-08	19,0	26,5	TP0-05	16,0	16	0,0	
CR 8-10A	3/8"	10	15,9						SFA-TP0-10	22,0	26,5	TP0-06	18,3	16	2,3	
CR 8-13A	1/2"	13	19,3						SFA-TP0-13	26,0	30,5	TP0-08	21,8	19	2,8	
Compact high pressure hose Black - Standard: EN 857-2SC																
SL 560-08	5/16"	8	15,0	2			12,9	19	SFA-SK1-08	21,0	25,5	SK1-05	18,0	16	2,0	
SL 560-10	3/8"	10	17,4					14,7	20	SFA-SK1-10	23,0	27,5	SK1-06	19,9	19	0,9
3 braided layers high pressure hose - 3SPT SUPERFOREST																
FXP313	1/2"	13	24,8	3				25	SFA-4S-13	29,0	34,7	H1100404-08	26,6	26	0,6	
FXP316	5/8"	16	28,3						28	SFA-4S-16	33,0	37,5	H1100404-10	29,7	26	3,7
FXP320	3/4"	19	32,2						33	SFA-4S-20	37,0	41,5	H1100404-12	33,6	30	3,6
FXP325	1"	25	40,4						37	SFA-4S-25	45,0	47,7	H1100404-16	41,9	39	2,9
Compact high pressure hose Blue - Standard: EN 857-1SC (Alfajet 210)																
SL 3010-06	1/4"	6	12,1	1					SFA-D1-06	22,0	24,7	AD1-04	16,5	16	0,5	
SL 3010-08	5/16"	8	14,1							SFA-TP0-08	19,0	26,5	TP0-05	15,2	14	1,2
SL 3010-10	3/8"	10	15,6							SFA-TP0-10	22,0	26,5	TP0-06	17,8	16	1,8
SL 3010-13	1/2"	13	19,5							SFA-TP0-13	26,0	30,5	TP0-08	21,2	19	2,2
Compact high pressure hose Blue - Standard: EN 857-2SC (Alfajet 400)																
SL 3020-06	1/4"	6	13,4	2			11,2	19	SFA-SK1-06	19,0	25,5	SK1-04	16,1	16	0,1	
SL 3020-08	5/16"	8	15,0					12,9	19	SFA-SK1-08	21,0	25,5	SK1-05	18,0	16	2,0
SL 3020-10	3/8"	10	17,4					14,7	20	SFA-SK1-10	23,0	27,5	SK1-06	19,9	19	0,9
SL 3020-13	1/2"	13	20,5					18,1	26	SFA-SK1-13	27,0	33,5	SK1-08	24,0	22	2,0
Suction/return hose - Standard: SAE 100-R4																
CR 4-20	3/4"	19	30,0	Helix					SFA-TX2-20	38,0	36,0	203-12	34,1	34	0,1	
CR 4-25	1"	25	35,0							SFA-TX2-25	48,0	42,5	203-16	40,8	39	1,8
CR 4-32	1-1/4"	32	41,0							SFA-TX2-32	53,0	56,5	203-20	46,8	45	1,8
CR 4-40	1-1/2"	38	51,0							SFA-TX2-40	60,0	61,5	203-24	53,1	51	2,1
CR 4-50	2"	51	62,0							SFA-TX2-50	76,0	73,5	203-32	66,9	63	3,9
CR6 hose - Standard: SAE 100 R6 - EN 854 R6																
CR 6-6A	1/4"	6	12,7	1					SFA-SK1-06	19,0	25,5	SK1-04	16,6	16	0,6	
CR 6-8A	5/16"	8	14,3							SFA-SK1-08	21,0	25,5	SK1-05	18,7	16	2,7
CR 6-10A	3/8"	10	15,9							SFA-SK1-10	23,0	27,5	SK1-06	20,0	19	1,0
CR 6-13A	1/2"	13	19,8							SFA-SK1-13	27,0	33,5	SK1-08	24,0	22	2,0
CR 6-16A	5/8"	16	23,0							SFA-SK1-16	30	36,5	SK1-10	27,5	26	1,5
CR 6-20A	3/4"	19	26,9							SFA-SK1-20	33,0	40,0	SK1-12	31,3	30	1,3
CR 6-25A	1"	25	33,5							SFA-SK1-25	41,0	46,5	SK1-16	37,8	34	3,8

It is important to check our download center for updates on a regular basis.
 The swage dimensions listed in the tables are approximate data. Due to variations in hose, coupling tolerances and slight deviation in the swaging machine differences may occur. All of the information contained in this document has been composed with the utmost care.
 Taking all of this into consideration, we cannot accept liability for any imperfections within this document.

Swaging Chart

FINN-POWER P32 MS / P51 / FP110 / FP120 / FP140

Hose type	Hose dimensions				Internal skive		External skive		Ferrule dimensions				Swage diam.	Die set ref.	Adjustment
	(Inch)	Inner Ø	Outer Ø	Layers	Ø	Length	Ø	Length	Part No.	Ø	Length	Prod.code	Ø +/- 0.1 mm		
2TE hose - Standard: EN 854 2TE															
2TE-DN06	1/4"	6	13,1	1					SFA-SK1-06	19,0	25,5	SK1-06	16,7	16	0,7
2TE-DN08	5/16"	8	14,9						SFA-SK1-08	21,0	25,5	SK1-08	19	19	0,0
2TE-DN10	3/8"	10	16,5						SFA-SK1-10	23,0	27,5	SK1-10	20,3	19	1,3
2TE-DN13	1/2"	13	19,7						SFA-SK1-13	27,0	33,5	SK1-13	24,4	22	2,4
2TE-DN16	5/8"	16	23,9						SFA-4S-16	33,0	37,5	4S-16	28,9	26	2,9
2TE-DN20	3/4"	19	27,0						SFA-4S-20	37,0	41,5	4S-20	32,4	30	2,4
2TE-DN25	1"	25	34,4						SFA-SK1-25	41,0	46,5	SK1-25	38,1	34	4,1
3TE hose - Standard: EN 854 3TE															
3TE-DN06	1/4"	6	14,4	2					SFA-TX2-06	23,0	24,7	TX2-06	18,4	16	2,4
3TE-DN08	5/16"	8	16,9						SFA-TX2-08	25,0	24,7	TX2-08	20,4	19	1,4
3TE-DN10	3/8"	10	18,5						SFA-TX2-10	27,0	29,7	TX2-10	22	19	3,0
3TE-DN12	1/2"	13	21,7						SFA-TX2-13	30,0	30,5	TX2-13	24,8	22	2,8
3TE-DN16	5/8"	16	25,9						SFA-TX2-16	34,0	35,5	TX2-16	29	26	3,0
3TE-DN20	3/4"	19	29,0						SFA-TX2-20	38,0	36,0	TX2-20	32,2	30	2,2
3TE-DN25	1"	25	35,9						SFA-TX2-25	48,0	42,5	TX2-25	39,1	39	0,1
3TE-DN31	1-1/4"	32	42,3						SFA-TX2-32	53,0	56,5	TX2-32	45,8	45	0,8
3TE-DN38	1-1/2"	40	49,3						SFA-TX2-40	60,0	61,5	TX2-40	52,4	51	1,4
3TE-DN51	2"	51	63,0						SFA-TX2-50	76,0	73,5	TX2-50	66,8	63	3,8

It is important to check our download center for updates on a regular basis.
 The swage dimensions listed in the tables are approximate data. Due to variations in hose, coupling tolerances and slight deviation in the swaging machine differences may occur. All of the information contained in this document has been composed with the utmost care. Taking all of this into consideration, we cannot accept liability for any imperfections within this document.

Swaging Chart

FINN-POWER P32 MS / P51 / FP110 / FP120 / FP140

Hose type	Hose dimensions				Internal skive		External skive		Ferrule dimensions				Swage diam.	Die Set Ref.	Adjustment
	(Inch)	Inner Ø	Outer Ø	Layers	Ø	Length	Ø	Length	Part No.	Ø	Length	prod.code	Ø +/- 0.1 mm		
AlfaBiotech - Non Skive - Standard Inserts															
ALFABIOTECH 4000 - MINETUFF ISO 18752															
ABT-4K-DN20-4S	3/4"	19	29,5	4					SFA-204-20	42,0	39,5	H1200204-12	35,7	34	1,7
ABT-4K-DN25-4S	1"	25	37,5		SFA-204-25	50,0	47,5	H1200204-16	43,4	39	4,4				
ABT-4K-DN32-4S	1-1/4"	32	45,7		SFA-204-32	62,0	50,2	H1200204-20	51,8	51	0,8				
ALFABIOTECH 5000 - MINETUFF ISO 18752															
ABT-5K-DN16-4S	5/8"	16	26,3	4					SFA-204-16	38,0	36,6	H1200204-10	30,9	30	0,9
Max. 280 bar															
ALFABIOTECH 6000 - MINETUFF ISO 18752 EXCEEDS SAE 100 R15															
ABT-6K-DN10-4S	3/8"	10	20,1	4					SFA-204-10	30,0	28,0	H1200204-06	24,5	22	2,5
Max. 280 bar															
ABT-6K-DN13-4S	1/2"	13	23,0						SFA-204-13	34,0	33,9	H1200204-08	28,2	26	2,2
Max. 280 bar															
AlfaBiotech - Non Skive - NS Inserts															
ALFABIOTECH 4000 - MINETUFF ISO 18752															
ABT-4K-DN40-4S	1-1/2"	38	51,8	4					SFA-NS4-40	70,0	89,5	H1300NS4-24	59,6	57	2,6
ABT-4K-DN50-4S	2"	51	66,8		SFA-NS4-50	87,0	125	H1300NS4-32	77,3	74	3,3				
ALFABIOTECH EVOLUTION 4000 - MINETUFF ISO 18752															
ABT-EV4K-DN40-4S	1-1/2"	38	50,6	4					SFA-NS4-40	70,0	89,5	H1300NS4-24	58,8	57	1,8
ABT-EV4K-DN50-4S	2"	51	64,7		SFA-NS4-50	87,0	125	H1300NS4-32	75,8	74	1,8				
ALFABIOTECH 5000 - MINETUFF ISO 18752															
ABT-5K-DN20-4S	3/4"	19	31,0	4					SFA-NS4-20	44,0	55	H1300NS4-12	36,8	34	2,8
ABT-5K-DN25-4S	1"	25	38,0		SFA-NS4-25	51,0	64	H1300NS4-16	43,1	39	4,1				
ABT-5K-DN32-4S	1-1/4"	32	45,8		SFA-NS4-32	61,0	99	H1300NS4-20	54,5	51	3,5				
ABT-5K-DN40-6S	1-1/2"	38	54,8	6					SFA-NS6-40	73,0	89,5	H1300NS6-24	63,2	63	0,2
ABT-5K-DN50-6S	2"	51	70,2		SFA-NS6-50	89,0	125	H1300NS6-32	80,5	78	2,5				
ALFABIOTECH EVOLUTION 5000 - MINETUFF ISO 18752															
ABT-EV5K-DN20-4S	3/4"	19	29,4	4					SFA-NS4-20	44,0	55	H1300NS4-12	36,1	34	2,1
ABT-EV5K-DN25-4S	1"	25	37,4		SFA-NS4-25	51,0	64	H1300NS4-16	43,1	39	4,1				
ABT-EV5K-DN32-4S	1-1/4"	32	44,0		SFA-NS4-32	61,0	99	H1300NS4-20	53,6	51	2,6				
ABT-EV5K-DN40-6S	1-1/2"	38	54,8	6					SFA-NS6-40	73,0	89,5	H1300NS6-24	62,2	57	5,2
ABT-EV5K-DN50-6S	2"	51	68,7		SFA-NS6-50	89,0	125	H1300NS6-32	79,6	78	1,6				
ALFABIOTECH 6000 - MINETUFF ISO 18752 EXCEEDS SAE 100 R15															
ABT-6K-DN20-4S	3/4"	19	31,4	4					SFA-NS4-20	44,0	55	H1300NS4-12	37,4	34	3,4
ABT-6K-DN25-4S	1"	25	38,6		SFA-NS4-25	51,0	64	H1300NS4-16	44,0	39	5,0				
ABT-6K-DN32-6S	1-1/4"	32	49,3		6				SFA-NS6-32	65,0	99	H1300NS6-20	56,8	51	5,8
ALFABIOTECH EVOLUTION 6000 - MINETUFF ISO 18752 EXCEEDS SAE 100 R15															
ABT-EV6K-DN20-4S	3/4"	19	30,6	4					SFA-NS4-20	44,0	55	H1300NS4-12	37,4	34	3,4
ABT-EV6K-DN25-4S	1"	25	38,0		SFA-NS4-25	51,0	64	H1300NS4-16	44,0	39	5,0				
ABT-EV6K-DN32-6S	1-1/4"	32	47,6		6				SFA-NS6-32	65,0	99	H1300NS6-20	55,6	51	4,6

It is important to check our download center for updates on a regular basis.
 The swage dimensions listed in the tables are approximate data. Due to variations in hose, coupling tolerances and slight deviation in the swaging machine differences may occur. All of the information contained in this document has been composed with the utmost care. Taking all of this into consideration, we cannot accept liability for any imperfections within this document.

Swaging Chart

FINN-POWER P32 MS / P51 / FP110 / FP120 / FP140

Hose type	Hose dimensions				Internal skive		External skive		Ferrule dimensions				Swage diam.	Die Set Ref.	Adjustment
	(Inch)	Inner Ø	Outer Ø	Layers	Ø	Length	Ø	Length	Part No.	Ø	Length	prod.code	Ø +/- 0.1 mm		
AlfaBiotech - Skive - Standard Inserts															
ALFABIOTECH 4000 - MINETUFF ISO 18752															
ABT-4K-DN20-4S	3/4"	19	29,5	4			26,6	33	SFA-4S-20	37,0	41,5	H1100404-12	32,3	30	2,3
ABT-4K-DN25-4S	1"	25	37,5				34,6	37	SFA-4S-25	45,0	47,7	H1100404-16	40,9	39	1,9
ALFABIOTECH EVOLUTION 4000 - MINETUFF ISO 18752															
ABT-EV4K-DN20-4S	3/4"	19	29,0	4			26,7	33	SFA-4S-20	37,0	41,5	H1100404-12	32,3	30	2,3
ABT-EV4K-DN25-4S	1"	25	37,2				34,6	37	SFA-4S-25	45,0	47,7	H1100404-16	40,9	39	1,9
ABT-EV4K-DN32-4S	1-1/4"	32	44,2				41,8	41	SFA-4S-32	55,0	54,5	H1100404-20	49,1	45	4,1
ABT-EV4K-DN40-4S	1-1/2"	38	50,6				48	47	SFA-4S-40	67,0	61,1	H1100404-24	58,4	57	1,4
ABT-EV4K-DN50-4S	2"	51	64,7				62,1	60	SFA-4S-50	82,0	75,1	H1100404-32	74,5	74	0,5
ALFABIOTECH 5000 - MINETUFF ISO 18752															
ABT-5K-DN16-4S	5/8"	16	26,3	4			23,5	28	SFA-4S-16	33,0	37,5	H1100404-10	28,9	26	2,9
ABT-5K-DN20-4S	3/4"	19	31,0				28,2	33	SFA-4S-20	37,0	41,5	H1100404-12	33,3	30	3,3
ABT-5K-DN25-4S	1"	25	38,0				34,8	37	SFA-4S-25	45,0	47,7	H1100404-16	41,2	39	2,2
ALFABIOTECH EVOLUTION 5000 - MINETUFF ISO 18752															
ABT-EV5K-DN16-4S	5/8"	16	25,4	4			23,2	28	SFA-4S-16	33,0	37,5	H1100404-10	29	26	3,0
ABT-EV5K-DN20-4S	3/4"	19	29,4				27,2	33	SFA-4S-20	37,0	41,5	H1100404-12	32,6	30	2,6
ABT-EV5K-DN25-4S	1"	25	37,4				34,8	37	SFA-4S-25	45,0	47,7	H1100404-16	41,2	39	2,2
ALFABIOTECH 6000 - MINETUFF ISO 18752 EXCEEDS SAE 100 R15															
ABT-6K-DN06-4S	1/4"	6	17,3	4			14,7	19	SFA-4S-06	22,0	26,3	H1100404-04	18,3	16	2,3
ABT-6K-DN10-4S	3/8"	10	20,1				17,5	19	SFA-4S-10	25,0	28,5	H1100404-06	22,0	19	3,0
ABT-6K-DN13-4S	1/2"	13	23,0				20,2	25	SFA-4S-13	29,0	34,7	H1100404-08	26,3	26	0,3
ALFABIOTECH EVOLUTION 6000 - MINETUFF ISO 18752 EXCEEDS SAE 100 R15															
ABT-EV6K-DN06-4S	1/4"	6	17,0	4			14,7	19	SFA-4S-06	22,0	26,3	H1100404-04	18,3	16	2,3
ABT-EV6K-DN10-4S	3/8"	10	19,8				17,5	19	SFA-4S-10	25,0	28,5	H1100404-06	22	19	3,0
ABT-EV6K-DN13-4S	1/2"	13	22,5				20,2	25	SFA-4S-13	29,0	34,7	H1100404-08	26,3	26	0,3

It is important to check our download center for updates on a regular basis.
 The swage dimensions listed in the tables are approximate data. Due to variations in hose, coupling tolerances and slight deviation in the swaging machine differences may occur. All of the information contained in this document has been composed with the utmost care. Taking all of this into consideration, we cannot accept liability for any imperfections within this document.

Swaging Chart

FINN-POWER P32 MS / P51 / FP110 / FP120 / FP140

Hose type	Hose dimensions				Internal skive		External skive		Ferrule dimensions				Swage diam.	Die Set Ref.	Adjustment
	(Inch)	Inner Ø	Outer Ø	Layers	Ø	Length	Ø	Length	Part No.	Ø	Length	prod.code	Ø +/- 0.1 mm		
AlfaBiotech - Skive - Interlock G2 (H) Inserts															
ALFABIOTECH 4000 - MINETUFF ISO 18752															
ABT-4K-DN25-4S	1"	25	37,5	4	29,3	16	34,6	48	SFA-H4-25	46,0	55,7	H1700200-16	41,6	39	2,6
ABT-4K-DN40-4S	1-1/2"	38	51,8		42,0	19	49,0	56	SFA-H4-40	62,0	68,0	H1700200-24	57,2	57	0,2
ABT-4K-DN50-4S	2"	51	66,8		56,8	26	64,0	69	SFA-H4-50	78,0	79,5	H1700200-32	73,3	69	4,3
ALFABIOTECH EVOLUTION 4000 - MINETUFF ISO 18752															
ABT-EV4K-DN25-4S	1"	25	37,2	4	29,1	16	34,6	48	SFA-H4-25	46,0	55,7	H1700200-16	41,6	39	2,6
ABT-EV4K-DN32-4S	1-1/4"	32	44,2		35,6	18	41,8	54	SFA-H4-32	55,0	66,0	H1700200-20	49,8	45	4,8
ABT-EV4K-DN40-4S	1-1/2"	38	50,6		42,2	19	48	56	SFA-H4-40	62,0	68,0	H1700200-24	56,4	51	5,4
ABT-EV4K-DN50-4S	2"	51	64,7		55,2	26	62,1	69	SFA-H4-50	78,0	79,5	H1700200-32	71,8	69	2,8
ALFABIOTECH 5000 - MINETUFF ISO 18752															
ABT-5K-DN20-4S	3/4"	19	31,0	4	22,9	14	28,2	42	SFA-H4-20	38,0	48,7	H1700200-12	33,6	30	3,6
ABT-5K-DN25-4S	1"	25	38,0		29,6	16	34,8	48	SFA-H4-25	46,0	55,7	H1700200-16	41,7	39	2,7
ABT-5K-DN32-4S	1-1/4"	32	45,8		36,6	18	43	56	SFA-H4-32	55,0	66,0	H1700200-20	50,7	45	5,7
ABT-5K-DN40-6S	1-1/2"	38	54,8	6	42,2	19	52,2	58	SFA-H46-40	69,5	68,0	H1700301-24	62,0	57	5,0
ALFABIOTECH EVOLUTION 5000 - MINETUFF ISO 18752															
ABT-EV5K-DN20-4S	3/4"	19	29,4	4	22,4	17	27,2	42	SFA-H4-20	38,0	48,7	H1700200-12	32,8	30	2,8
ABT-EV5K-DN25-4S	1"	25	37,4		29,6	16	34,8	48	SFA-H4-25	46,0	55,7	H1700200-16	41,7	39	2,7
ABT-EV5K-DN32-4S	1-1/4"	32	44,0		36,1	18	41,8	54	SFA-H4-32	55,0	66,0	H1700200-20	49,8	45	4,8
ABT-EV5K-DN40-6S	1-1/2"	38	54,8		6	42,2	19	52,2	58	SFA-H46-40	69,5	68,0	H1700301-24	62	57
ABT-EV5K-DN50-6S	2"	51	68,7	6	55,3	26	66,3	67	SFA-H46-50	88,0	79,5	H1700301-32	79,7	78	1,7
ALFABIOTECH 6000 - MINETUFF ISO 18752 EXCEEDS SAE 100 R15															
ABT-6K-DN16-4S	5/8"	16	28,2	4	20,3	14	25,4	39	SFA-H46-16	35,5	46,0	H1700301-10	32,0	30	2,0
ABT-6K-DN20-4S	3/4"	19	31,4		22,8	14	28,6	42	SFA-H4-20	38,0	48,7	H1700200-12	33,5	30	3,5
ABT-6K-DN25-4S	1"	25	38,6		29,3	16	35,8	48	SFA-H4-25	46,0	55,7	H1700200-16	41,7	39	2,7
ABT-6K-DN32-6S	1-1/4"	32	49,3	6	37,9	18	46,5	56	SFA-H46-32	62,0	66,0	H1700301-20	55,6	51	4,6
ABT-6K-DN40-6S	1-1/2"	38	56,5		43,9	19	53,7	58	SFA-H46-40	69,5	68,0	H1700301-24	63,2	63	0,2
ALFABIOTECH EVOLUTION 6000 - MINETUFF ISO 18752 EXCEEDS SAE 100 R15															
ABT-EV6K-DN16-4S	5/8"	16	27,8	4	19,1	14	25,5	39	SFA-H46-16	35,5	46,0	H1700301-10	32,0	30	2,0
ABT-EV6K-DN20-4S	3/4"	19	30,6		22,4	14	28,4	42	SFA-H4-20	38,0	48,7	H1700200-12	33,5	30	3,5
ABT-EV6K-DN25-4S	1"	25	38,0		29,0	16	35,6	48	SFA-H4-25	46,0	55,7	H1700200-16	41,7	39	2,7
ABT-EV6K-DN32-6S	1-1/4"	32	47,6		35,7	18	44,8	56	SFA-H46-32	62,0	66,0	H1700301-20	54,3	51	3,3
ABT-EV6K-DN40-6S	1-1/2"	38	54,4	6	42,1	19	51,8	58	SFA-H46-40	69,5	68,0	H1700301-24	61,6	57	4,6

It is important to check our download center for updates on a regular basis.
 The swage dimensions listed in the tables are approximate data. Due to variations in hose, coupling tolerances and slight deviation in the swaging machine differences may occur. All of the information contained in this document has been composed with the utmost care. Taking all of this into consideration, we cannot accept liability for any imperfections within this document.

Swaging Chart

FINN-POWER P32 MS / P51 / FP110 / FP120 / FP140

Hose type	Hose dimensions				Internal skive		External skive		Ferrule dimensions				Swage diam.	Die Set Ref.	Adjustment
	(Inch)	Inner Ø	Outer Ø	Layers	Ø	Length	Ø	Length	Part No.	Ø	Length	prod.code	Ø +/- 0.1 mm		
AlfaBiotech - Skive - Interlock (H) Inserts															
ALFABIOTECH 4000 - MINETUFF ISO 18752															
ABT-4K-DN25-4S	1"	25	37,5	4	29,3	17	34,6	65	SFA-4H-25	46,0	74,7	H1400200-16	41,6	39	2,6
ABT-4K-DN40-4S	1-1/2"	38	51,8		42,0	22	49,0	81	SFA-4H-40	70,0	89,5	H1400200-24	57,2	57	0,2
ABT-4K-DN50-4S	2"	51	66,8		56,8	29	64,0	85	SFA-4H-50	87,0	125	H1400200-32	73,3	69	4,3
ALFABIOTECH EVOLUTION 4000 - MINETUFF ISO 18752															
ABT-EV4K-DN25-4S	1"	25	37,2	4	29,3	17	34,6	65	SFA-4H-25	46,0	74,7	H1400200-16	41,6	39	2,6
ABT-EV4K-DN32-4S	1-1/4"	32	44,2		36,1	22	41,8	74	SFA-4H-32	55,0	88,2	H1400200-20	49,8	45	4,8
ABT-EV4K-DN40-4S	1-1/2"	38	50,6		42,2	22	48	81	SFA-4H-40	70,0	89,5	H1400200-24	56,4	51	5,4
ABT-EV4K-DN50-4S	2"	51	64,7		55,1	29	62,1	85	SFA-4H-50	87,0	125	H1400200-32	71,8	69	2,8
ALFABIOTECH 5000 - MINETUFF ISO 18752															
ABT-5K-DN20-4S	3/4"	19	31,0	4	22,9	15	28,2	52	SFA-4H-20	38,0	60,2	H1400200-12	33,6	30	3,6
ABT-5K-DN25-4S	1"	25	38,0		29,6	17	34,8	65	SFA-4H-25	46,0	74,7	H1400200-16	41,7	39	2,7
ABT-5K-DN32-4S	1-1/4"	32	45,8		36,6	22	43	74	SFA-4H-32	55,0	88,2	H1400200-20	50,7	45	5,7
ABT-5K-DN40-6S	1-1/2"	38	54,8	6	42,2	22	52,2	81	SFA-R15-40	69,5	94,0	H1400301-24	62,0	57	5,0
ABT-5K-DN50-6S	2"	51	70,2		56,6	29	67,4	85	SFA-R13-50	88,0	99,0	H1400301-32	80,6	78	2,6
ALFABIOTECH EVOLUTION 5000 - MINETUFF ISO 18752															
ABT-EV5K-DN20-4S	3/4"	19	29,4	4	22,4	15	27,2	52	SFA-4H-20	38,0	60,2	H1400200-12	32,8	30	2,8
ABT-EV5K-DN25-4S	1"	25	37,4		29,6	17	34,8	65	SFA-4H-25	46,0	74,7	H1400200-16	41,7	39	2,7
ABT-EV5K-DN32-4S	1-1/4"	32	44,0		36,1	22	41,8	74	SFA-4H-32	55,0	88,2	H1400200-20	49,8	45	4,8
ABT-EV5K-DN40-6S	1-1/2"	38	54,8		42,2	22	52,2	81	SFA-R15-40	69,5	94,0	H1400301-24	62	57	5,0
ALFABIOTECH 6000 - MINETUFF ISO 18752 EXCEEDS SAE 100 R15															
ABT-6K-DN16-4S	5/8"	16	28,2	4	20,3	15	25,4	50	SFA-R15-16	35,5	57,5	H1400301-10	31,7	30	1,7
ABT-6K-DN20-4S	3/4"	19	31,4		22,8	15	28,6	52	SFA-4H-20	38,0	60,2	H1400200-12	34,0	34	0,0
ABT-6K-DN25-4S	1"	25	38,6		29,3	17	35,8	65	SFA-4H-25	46,0	74,7	H1400200-16	41,7	39	2,7
ABT-6K-DN32-6S	1-1/4"	32	49,3	6	37,9	22	46,5	74	SFA-R15-32	62,0	88,0	H1400301-20	55,6	51	4,6
ABT-6K-DN40-6S	1-1/2"	38	56,5		43,9	22	53,7	81	SFA-R15-40	69,5	94,0	H1400301-24	63,2	63	0,2
ALFABIOTECH EVOLUTION 6000 - MINETUFF ISO 18752 EXCEEDS SAE 100 R15															
ABT-EV6K-DN16-4S	5/8"	16	27,8	4	19,1	15	25,5	50	SFA-R15-16	35,5	57,5	H1400301-10	31,7	30	1,7
ABT-EV6K-DN20-4S	3/4"	19	30,6		22,4	15	28,4	52	SFA-4H-20	38,0	60,2	H1400200-12	34,0	34	0,0
ABT-EV6K-DN25-4S	1"	25	38,0		29	17	35,6	65	SFA-4H-25	46,0	74,7	H1400200-16	41,7	39	2,7
ABT-EV6K-DN32-6S	1-1/4"	32	47,6		35,7	22	44,8	74	SFA-R15-32	62,0	88,0	H1400301-20	54,3	51	3,3
ABT-EV6K-DN40-6S	1-1/2"	38	54,4	6	42,1	22	51,8	81	SFA-R15-40	69,5	94,0	H1400301-24	61,6	57	4,6

It is important to check our download center for updates on a regular basis.
 The swage dimensions listed in the tables are approximate data. Due to variations in hose, coupling tolerances and slight deviation in the swaging machine differences may occur. All of the information contained in this document has been composed with the utmost care. Taking all of this into consideration, we cannot accept liability for any imperfections within this document.