

# TRANSPORTER

## **IMPRESSIVE** TRANSPORTATION **SOLUTIONS**







Seating Capacity 4-8

## TRANSPORTER

## TRANSPORTER XL



Max Speed Max Vehicle 17 mph Capacity 1500 lbs

The simplest way to a comprehensive transportation strategy.

When you need the versatility to transport passengers and cargo, Club Car Transporter vehicles provide the perfect solution. Vehicles can be configured to transport four, six, or eight passengers, and have the capability to be equipped with a cargo bed for tools and equipment. Whether you are transporting guests from the parking lot to the front door or taking your crew and their tools from the shop to a job, the Transporter and Transporter XL vehicles provide a solution that's right for your fleet.



#### Available Body Colors

Standard Colors









Dark Grav

Premium Colors









Classic Blue



Titanium









(COMM0132) ©2025 1.800.CLUBCAR | 1.706.863.3000 | carryall.com

	GASOLINE	ELECT HP ELEC		GASOLINE	ELECTRIC	
ENGINE	Kohler EFI Gas	48-volt DC	48-volt AC	Kohler EFI Gas	48-volt AC	
EPOWER	14 hp (10.3 kW) rated @ 3600 RPM per SAE J1940	3.7 hp (2.7 kW) rated; peak 20 hp (14.9 kW)	8 hp (6 kW) rated; peak 16 hp (11.7 kW)	14 hp (10.3 kW) rated @ 3600 RPM per SAE J1940	8 hp (6kW) peak 16 hp (11.7 kW)	
R GUARD	Ground speed	N/A		Ground speed	N/A	
TROLLER	N/A	500 Amp - Solid State	400 Amp - Solid State	N/A	400 Amp - Solid State	
ATTERIES	12-volt 500 CCA 105 min reserve	Eight 6-volt		12-volt 500 CCA 105 min reserve	Eight 6-volt flooded lead acid	

HORSEPOWER	3600 RPM per SAE J1940	peak 20 hp (14.9 kW)	peak 16 hp (11.7 kW)	3600 RPM per SAE J1940	peak 16 hp (11.7 kW)
GOVERNOR GUARD	Ground speed	N/A		Ground speed	N/A
CONTROLLER	N/A	500 Amp - Solid State	400 Amp - Solid State	N/A	400 Amp - Solid State
BATTERIES	12-volt 500 CCA 105 min reserve	Eight 6-volt flooded lead acid		12-volt 500 CCA 105 min reserve	Eight 6-volt flooded lead acid
CHARGER N/A		DeltaQ QuiQ (1 kW High Frequency)		N/A	DeltaQ QuiQ (1 kW High Frequency)
STEERING	Self-adjusting rack and pinion	Self-adjusting rack and pinion		Self-adjusting rack and pinion	Self-adjusting rack and pinion
FRONT SUSPENSION	Independent leaf spring with dual hydraulic shocks	Independent leaf spring with dual hydraulic shocks		Independent leaf spring with dual hydraulic shocks	Independent leaf spring with dual hydraul shocks
BRAKES	4-wheel mechanical drum		rheel ical drum	4-wheel mechanical drum	4-wheel mechanical drum
PARK BRAKE	Foot operated, multi-lock	Foot operated, multi-lock		Foot operated, multi-lock	Foot operated, multi-lock
BODY AND FINISH	ArmorFlex <sup>54</sup> with automotive paint/clearcoat, aluminum finish		ex™ with aint/clearcoat, ım finish	ArmorFlex™ with automotive paint/ clearcoat, aluminum finish	ArmorFlex™ with automotive paint/ clearcoat, aluminum finish
TIRES	20 x 10-10, 6-ply rated, premium tread	20 x 10-10, 6-ply rated, premium tread		20 x 10-10, 6-ply rated, premium tread	20 x 10-10, 6-ply rated, premium tread
BEDLXWXH	37 x 47.5 x 10.5 in (94 x 120 x 27 cm) (Cargo Box)	37 x 47.5 x 10.5 in (94 x 120 x 27 cm) (Cargo Box)		4-passenger: 64.5 x 47.5 x 10.5 in (164 x 120 x 27 cm) 6-passenger: 36.2 x 47.5 x 10.5 in (92 x 120 x 27 cm) 8-passenger: N/A	
WHEELBASE	99.1 in (252 cm)	99.1 in (252 cm)		132.1 in (336 cm)	132.1 in (336 cm)
GROUND CLEARANCE	5.6 in (14 cm)	5.2 in (14 cm)		5.6 in (14 cm)	5.2 in (14 cm)
FUEL TANK CAPACITY	5.5 gal (20.8 L)	N/A		5.5 gal (20.8 L)	N/A

932 lb (423 kg) stakeside; 1494 lb (678 kg) stakeside; 1104 lb (501 kg) 1646 lb (747 kg) **CURB WEIGHT** 943 lb (428 kg) 1505 lb (684 kg)

with rear seat

15-17 mph 15-17 mph 15-17 mph 17 mph SPEED RANGE (24-27 km/h) (24-27 km/h) (24-27 km/h) (24-27 km/h)

remaining vehicle

with rear seat

8 passenger

8 passenger

remaining vehicle

4 yr limited battery 4 vr limited battery 3 vr/3000 hr limited 3 yr/3000 hr limited 3 yr limited 3 yr limited powertrain/frame powertrain/frame **LIMITED WARRANTY** powertrain/frame powertrain/frame 2 yr limited 2 vr limited remaining vehicle 2 yr limited 2 yr limited remaining vehicle