

Lumen

A Sonepar Company

ATLANTIC

Special deals March - April 2023



AIR MILES.

Valid for Electrical Contractors
ESA and ECA members only

LEVITON®



Tamper Resistant Duplex Receptacle

15A - 120V, white

LEVT5325W



Tamper Resistant Duplex Receptacle

15A - 120V, black

LEVT5325E



Switch

Decora

15A, 1P, 120V, white

LEV5601P2W



Switch

Decora

15A, 3W, 120V, white

LEV5603P2W

Milwaukee



M12 Cable Stapler Kit

Coil-spring mechanism sinks the staples to the appropriate depth when fastening loomex NMD 90 (14/2, 14/3, 12/2, 12/3, 10/2, 10/3) and low voltage cables. Only compatible with our 1" insulated staples. Sink up to 1,200 staples on a fully charged M12 CP2.0ah battery. **Includes:** stapler 2448-20, battery M12 CP2.0 48-11-2420, battery charger 48-59-2401 and carrying bag.

Stapler kit # MIL244821

Tool only # MIL244820



Insulated Cable Staples for Stapler 2448

1 in - CUL approved for loomex NMD 90 cable (14/2, 14/3, 12/2, 12/3, 10/2, 10/3) installation.

Pack of 600

MILMNM1600

nVent HOFFMAN



Junction Box with Hinged Cover

NEMA 1

8 x 8 x 4 in

HOFAHE884

10 x 10 x 4 in

HOFAHE10104



Junction Box with Screw Cover

NEMA 1

6 x 6 x 4 in

HOFASE664

8 x 8 x 4 in

HOFASE884

10 x 10 x 4 in

HOFASE10104



LED Wall Pack

120 / 347V, full cut off, adjustable CCT (3 000K / 4 000K / 5 000K) and power (25W / 3 625LM, 40W / 5 640LM, 60W / 8 220LM), dimmable, photocell included, die cast aluminium housing, bronze finish, polycarbonate lens.

Replaces up to 400W, HID or 250W, HPS
STAWFCPS60A3Q3CBRP



LED BR30 Lamp

8W, dimmable
Replaces 65W, incandescent

650LM, 2 700K
STALEDBR30S28W27KSTD
700LM, 4 000K
STALEDBR30S28W40KSTD



LED Lamps

A19 - 9.5W, 800LM, non-dimmable. Pack of 4.
Replaces 60W, incandescent

3 000K # STAA1995W30KNDCHOICE4P
4 000K # STAA1995W40KNDCHOICE4P
5 000K # STAA1995W50KNDCHOICE4P



Suitable for wet location

LED Surface Mount Ceiling Fixture

7 in - 14W, 120V, 4 000K 1 000LM, with motion detector (passive infrared), frosted polycarbonate lens, steel housing, non-dimmable, white.

Replace 75W, incandescent
STACLDKMS7R14WA40WH



Suitable for damp location

LED Strip Fixture

Rocker switch, aluminium housing, frosted lens, 120° beam, interconnect up to 300W, for under-cabinet or task lighting, residential or commercial use (accessories sold separately).

12 in - 5W, 360LM
LUMLUUCFL12IN120V5W3KFR
24 in - 10W, 730LM
LUMLUUCFL24IN120V10W3KFR
36 in - 15W, 1 050LM
LUMLUUCFL36IN120V15W3KFR



Suitable for wet location

LED Surface Mount Ceiling Fixture

120V, 5 CCT (2 700 / 3 000 / 3 500 / 4 000 / 5 000K), dimmable, round.

4 in - 8W, 580LM
Replaces up to 60W, incandescent
STACLDK4R8WA5CWH
6 in - 15W, 1 000LM
Replaces up to 75W, incandescent
STACLDK6R15WA5CWH

KEENE
by @ignify



LED Ceiling Mount Fixture

28 / 40 / 60W, 120 / 347V, 4 100 to 8 650LM, 3 000 / 4 000 / 5 000K, die cast aluminium housing, polycarbonate lens, textured bronze finish

KEEGC60SCTG2SM510BZ

KEENE
by @ignify



LED Wall Pack

120 / 277V, 4 000K, 10W, 1 050LM, dark gray

Replaces up to 50W, HID
KEELPW7G38DGY

Day-Brite
CFI
by @ignify



LED Surface Fixture

4 ft - 120 / 277V, 4 000LM, adjustable CCT (3 000 / 3 500 / 4 000K), wraparound lens and occupancy sensor.

Replaces 2 X 32W, T8
CFINWL440L8CSTUNVDIMOCC

KEENE
by @ignify



LED Projector

120 / 277V, 4 000K, bronze finish

Knuckle or yoke mount

30W, 3 250LM
Replaces 150W, HID
KEETF30NWG1KFL8BZ
50W, 5 500LM
Replaces 150W, HID
KEETF50NWG1KFL8BZ

Yoke mount

100W, 12 400LM
Replaces up to 400W, MH
KEETF100NWG1YFL8BZ

KEENE
by @ignify



LED Wall Pack

120 / 347V, 3 000 / 4 000 / 5 000K, integrated selectable photocell, glass lens, die cast aluminium housing, bronze finish.

28 / 40 / 60W, 3 860 to 8 160LM
KEEWP60SCTG210BZ
70 / 80 / 90 / 100W, 9 240 to 13 600LM
KEEWP100SCTG210BZ

Day-Brite
CFI
by @ignify



LED High Bay Fixture

120 / 347V, selectable CCT (4 000 / 5 000K), suspension open hook, 6 ft cord, 0 / 10V dimmable, motion sensor receptacle, polycarbonate lens.

Selectable lumen output (14 000 / 21 000LM)
CFHICY1421L8CSTUN3DIM
Selectable lumen output (28 000 / 33 000LM)
CFHICY2833L8CSTUN3DIM



LED Surface Fixture

4 ft - 34W, 120/277V, 4 000K, 5 000LM, IP66, frosted polycarbonate lens, captive polycarbonate latches, dimmable 0/10V.

Replaces 2 X 32W, T8

LITCSVTL485000LMMV4K80CR



LED Surface Fixture

120/277V, 4 000K, dimmable, white acrylic lens.

2 ft - 32W, 3 000LM

Replaces 1 x 32W, T8

LITFMLWL24840ZTMVOLT

4 ft - 48W, 4 600LM

Replaces 2 x 32W, T8

LITFMLWL48840ZTMVOLT



LED Striplight

120/277V, 3 500/4 000/5 000K, frosted acrylic lens.

48 in - 3 000/4 000/5 000LM

LITCSSL48ALO3MVSWW380CRI

96 in - 6 000/8 000/10 000LM

LITCSSL96ALO4MVSWW380CRI



LED Panel for T-Bar Ceiling

120/277V, dimmable 0/10V, selectable output and CCT (3 500/4 000/5 000K)

1 x 4 # LITCPX1X4ALO7SWW7

2 x 2 # LITCPX2X2ALO7SWW7

2 x 4 # LITCPX2X4ALO8SWW7



Suitable for wet location

Recessed LED Fixture

4 in - 9.6W, 120V, 3 000K, 675LM, dimmable, junction box, approved for daisy chain installation, matte white. Sold in multiple of 6 only.

Replaces up to 65W, incandescent

LITWF4LED30KMWM6



Suitable for wet location

LED Recessed Fixture

120V, 5 CCT 2 700K to 5 000K, white

4 in - 9W, 670LM

Replaces up to 65W, incandescent

JUNWF4SWW590CRIMW

6 in - 13W, 950LM

Replaces 75W, incandescent

JUNWF6SWW590CRIMW



Control your lighting with the Pico remote control or through the Lutron app (smart hub required)

SKYLARK SERIES



Dimmer

120V, 600W incandescent or halogen, 150W LED or CFL, single and 3-way dimmer, white. Wallplate not included.

LUTSCL153PHWHC

MAESTRO SERIES



Dimmer

120V, 600W incandescent or halogen, 150W LED or CFL, single and 3-way dimmer, white. Wallplate not included.

LUTMACL153MHWHC

DIVA SERIES



Smart Dimmer Starter Kit

Includes: dimmer, smart hub, Pico remote control with mounting plate and faceplate, white

LUTDVRFBGD1DC



Luna Series

120V, adjustable CCT (2 700/3 000/3 500/4 000/5 000K)



Suitable for wet location

5 or 6 in

17W, 1 150LM

LITRA5617F90WHWH

20W, 1 435LM

LITRA5620F90WHWH

33W, 2 330LM

LITRA5633F90WHWH

LED Recessed Fixture

Dimmable, 40° beam, white finish



Suitable for wet location

3-1/2 in

White # LITRA3512RG90WH

Black # LITRA3512RG90BK

4 in

White # LITRA412RG90WH

Black # LITRA412RG90BK

3 000 to 2 000K - Warm dim

3-1/2 in

White # LITRA3512RGDTW90WH

Black # LITRA3512RGDTW90BK

LED Recessed Fixture

12W, adjustable gimbal, diffused mirror reflector

4 in

White # LITRA412RGDTW90WH

Black # LITRA412RGDTW90BK



Receptacle 125 / 250V

5.5 x 5.43 in - 3P, 4 wire, flush mount with integrated mounting plate, white.



50A - For oven
LEV1279S50



30A - For dryer
LEV1278S30

Receptacle 250V

2P, 3W, flush mount



30A - NEMA 6-30R
LEV5372S00



50A - NEMA 6-50R
LEV5374S00



24-Hour Mechanical Time Switch

40A
125V, 2HP
INTT10170
208/277V, 5HP
INTT10470



Mechanical Analog Timer

0 to 30 min, SPST-1 NO,
15A, 125/277V, plastic housing, white
INTFD30MWC70



600V Class CC Fuse

10A # FERATDR10
15A # FERATDR15
20A # FERATDR20
30A # FERATDR30



HUBBELL CANADA

Decorator Commercial Series



Duplex Receptacle
15A, 125V
HUBDR15WHI

Switch



15A, 1P, white
HUBCS115W
20A, 1P, white
HUBCS120W

Commercial Series

Duplex Receptacle



15A, white
HUBCR15WHI



20A, white
HUBCR20WHI



15A, isolated ground
HUBCR5252IG



Electrical Panel SPA Kit

120/240V - NEMA 3R

- 20A # SIEW0408ML112520
- 30A # SIEW0408ML112530
- 40A # SIEW0408ML112540
- 50A # SIEW0408ML112550
- 60A # SIEW0408ML112560



Iberville®



Octagonal Box
4 x 1-1/2 in
IBE54151L



Dry-Wall LHTQ Junction Box
14.5 cu. in, gangable
IBE1304LHTQ



EMT Set Steel Screw Fitting
1/2 in # APPTW50S
3/4 in # APPTW75S
1 in # APPTW100S



EMT Set Steel Screw Coupling
1/2 in # APPTWC50S
3/4 in # APPTWC75S
1 in # APPTWC100S

MICROELECTRIC

Service Entrance Masts and Accessories



Galvanized Ground Plate with JAB
BLA1016BTB



200AM
MICLUM2



200MH
MICLUM2MH



Meter Socket
600V
MICBQ2V



Meter Socket
200A, 120/240V, overhead, 2 gang.
C/w Siemens 2x Q2100H, 100A, 2P,
22kA rated circuit breakers.
MICCO12100HI



Entrance Mast
2-1/2 in x 10 ft
MICMM10
2-1/2 in x 12 ft
MICMM12

IPEX
by allaxis



Scepter PVC Molded Junction Boxes
NEMA 1 @ 13

4 x 4 x 2 in
SCEJBX442

4 x 4 x 4 in
SCEJBX444

5 x 5 x 2 in
SCEJBX552

6 x 3 x 4 in
SCEJBX634

6 x 6 x 4 in
SCEJBX664

6 x 6 x 6 in
SCEJBX666

8 x 8 x 4 in
SCEJBX884

8 x 8 x 7 in
SCEJBX887



M12 REDLITHIUM XC6.0 Battery

Switch to our REDLITHIUM XC6.0 Battery Pack to instantly upgrade the runtime and durability of your Milwaukee M12 cordless tools.

MIL48112460



M/2 2-Cutter SDS-Plus Rotary Hammer Drill Bits

5/32 in # MIL48207501
3/16 in # MIL48207511



Green Cross Line & Plumb Points Laser

USB rechargeable. Includes: REDLITHIUM USB 3.0 battery, 2 ft heavy duty cable, wall plug and carrying case.

MIL352221



PACKOUT Tool Box

100 lb capacity. Impact resistant polymers and metal reinforced corners for ultimate durability in harsh jobsite conditions. Featuring an IP65 rated weather seal.

MIL48228425



M12 FUEL 2-Tool Combo Kit

Includes: M12 FUEL 1/2 in hammer drill/driver, M12 FUEL 1/4 in hex impact driver, M12 REDLITHIUM XC 4.0 extended capacity battery pack, M12 REDLITHIUM CP2.0 battery, M12 lithium-ion battery charger and contractor bag.

MIL349722



M12 Soldering Iron Kit

Includes: M12 soldering iron, pointed tip, M12 REDLITHIUM compact battery pack, M12 charger and carrying case.

Iron kit # MIL248821
Tool only # MIL248820

BUY ONE OF 3 SELECTED BARE TOOLS AND GET A FREE M18, HQ, XC6.0 A.H. 48-11-1865 BATTERY



M18 FUEL Compact Bandsaw
MILKIT2829201865



1 in - M18 FUEL SDS Plus Rotary Hammer
MILKIT2912201865



M18 FUEL 4-1/2" / 6" Braking Grinder
MILKIT2980201865



Saw Keyhole

Pointed tip easily punches through drywall.

GRE301A



Bushing

7/8 in - Triple lock design holds bushing securely. Locks securely into metal studs from 24 gauge to 12 gauge (0.6 mm to 2.5 mm).

Pack of 100 # GRE711C
Pack of 1000 # GRE711M



Step drill bit #6

Minimum drill diameter 3/16 in, maximum drill diameter 1/2 in. Durable split-point tip for fast, accurate material penetration. Patented design optimizes chip load for fast, smooth cutting, and more holes per charge.

GREGSB06



11-PC Pro Folding Hex Keys

Includes: 1/2, 3/8, 5/16, 1/4, 7/32, 3/16, 5/32, 9/64, 1/8, 7/64, 3/32 in.

KLE70550



Hybrid Pliers

Strips 10-14 AWG solid and 12-16 stranded wire. 6-32 and 8-32 bolt shearing. Crimps non-insulated connectors, lugs and terminals.

KLEJ2158CR



Digital Circuit Breaker Finder

With GFCI outlet tester. CAT II 120V safety rating. **Includes:** transmitter, receiver and 9V battery.

KLEET310



Advanced Circuit Tracer Kit

Provides reliable tracing of energized or non-energized breakers, fuses, and wires. **Includes:** transmitter, receiver, blade and ground prongs, alligator clips, 3 ft and 20 ft lead adapters, AC plug leads, instructions, required batteries, and a hard carrying case.

KLEET450



Electrical Tester

Includes: Attached test leads with removable 4 mm probe caps, black AC285 SureGrip™ alligator clip and H-T6 holster.

FLUT61000PRO



Whistler™ Safety Helmet

Ultra-light. Manufactured in a high density polyethylene. "Sure-Lock" ratchet suspension. CSA certified to standard Z94. 1-15 type 1, in accordance to the vertical impact class E requirements.

- White # DYNHP241R01
- Yellow # DYNHP241R02
- Orange # DYNHP241R03
- Forest green # DYNHP241R04
- Sky blue # DYNHP241R07
- Navy blue # DYNHP241R08



Super 33+ Vinyl Electrical Tape

3/4 in x 66 ft - 7 mil.

All-weather, -18 to 105°C (0 to 220°F), black.

TRO333/4X66



Super 88 Vinyl Electrical Tape

3/4 in x 66 ft - 8.5 mil.

All-weather, -18 to 105°C (0 to 220°F), black.

TRO883/4X66



Linerless Rubber Splicing Tape

3/4 in x 30 ft - 30 mil.

130C, black.

TRO130C3/4X30



Nylon Safety Lockout Padlocks

1.77 in H x 1.5 in W x 0.82 in D - Keyed different, steel shackle. Key-retaining brass cylinder prevents key removal in the unlocked position for added safety and helps limit lost keys. Shackle Vertical Clearance: 1.5 in.



- Blue # BRASDPLBLU38STKD
- Green # BRASDPLGRN38STKD
- Orange # BRASDPLORG38STKD
- Yellow # BRASDPLYLW38STKD
- Red # BRASDPLRED38STKD

Red (pack of 12)
BRASDPLRED38STKD12

Red (pack of 24)
BRASDPLRED38STKD24



Aluminum Safety Lockout Padlocks

1.8 in H x 1.5 in W x 0.75 in D - Keyed different, steel shackle, durable, corrosion-resistant and ideal for general lockout applications. Shackle vertical clearance: 1.5 in.

- Blue # BRASDALBLU38STKD
- Green # BRASDALGRN38STKD
- Orange # BRASDALORG38STKD
- Yellow # BRASDALYLW38STKD
- Red # BRASDALRED38STKD

Red (pack of 12)
BRASDALRED38STKD12

Red (pack of 24)
BRASDALRED38STKD24

New EV series

32A
LEVEV320
48A
LEVEV480

- Optional access control: drivers can quickly and easily activate their charger by tapping their RFID card on the front of the unit
- For use with any SAE J1772™ compatible electric vehicle
- Cable design prevents cord from freezing and cracking in extreme weather
- For indoor and outdoor use with a thermoplastic, waterresistant enclosure rated NEMA Type 3R
- Dual Mount Pedestal, Front/Back, Cat. number EPED2

THE FUTURE IS ON®

LEVITON®

Set your clock forward on **Sunday, March 12th 2023** and don't forget to:



INSTALL
BRKSC9120LBLA
BRK9120BA



CLEAN
CRC74085



CHECK
CRC72105



REPLACE
DURPC1604BK



Download the Lumen app!



Place your orders directly
online at lumen.ca or via
the Lumen app.



Two branches to better serve Atlantic Canada!

DARTMOUTH

121, Ilsley Avenue, unit 119, Dartmouth (NS), B3B 1S4
Tel. : 902 468-7996 / Fax : 902 468-7997
Toll free : 1 844 516-0158

MONCTON

1070, St-George Blvd., unit 1A, Moncton (NB), E1E 4K7
Tel. : 506 382-1396 / Fax : 506 382-9376
Toll free : 1 844 311-1396

Lumen
A Sonepar Company

Prices are subject to change without notice. All images are for illustrative purposes only. Air Miles program is reserved to the Electrical Contractor ESA or ECA members only. We are currently experiencing an exceptionally high demand for many popular products. As a result, some products advertised in this flyer may not be available. Please check your local branch for availability or visit lumen.ca. We are currently working on replenishing supplies as quickly as possible and apologize for any inconvenience this may cause.



FSC
POUR POSITION
SEULEMENT