

WWS450H

2D CORDLESS SCANNER



The Wasp WWS450H 2D healthcare barcode scanner offers fast, efficient barcode scanning. Accurately read 1D and 2D barcodes with the WWS450H aggressive digital imager scan engine.

Simply plug the USB adapter (or optional PS2, RS232) into a PC to rapidly scan barcodes up to 160 feet away from the communication stand using wireless connectivity. Pair the WWS450H with an AndroidTM or iOS[®] device, including iPhone[®], iPad[®], or iPod[®], to monitor operations in the field from up to 30' away from the smartphone or tablet device. Barcode data is instantly added to a spreadsheet, document, or database, without time consuming manual data entries or inaccuracies.

With built-in Microban[®] antimicrobial technology, the WWS450H is ideal for use in pharmaceutical or hospital facilities, where protection against odor-and-stain causing bacteria is needed. The disinfectant-friendly housing allows for repeated disinfection and safeguards the WWS450H against discoloration, corrosion, and hardware malfunction.

■ WASP WWS450H FEATURES

- Read 1D barcodes up to 20" away and 2D barcodes up to 12" away
- Ideal for use in healthcare, pharmacies, and medical packaging use
- Withstands multiple 4' drops to concrete
- Compatible with Android and iOS devices
- Connect wirelessly up to 160' (light of sight) from a PC and 30' from a mobile device
- Holds up to 256 scans in buffer memory should scanner be out of range
- Antimicrobial protection against odor-and-stain causing bacteria
- Support up to 7 scanners per base station

■ BENEFITS

- High speed, low power consumption eliminates the need to rescan
- Ergonomic design ensures comfortable use
- Durable construction eliminates down-time due to breakage
- Eliminate time-consuming manual data entry
- WASP WWS450H COMMON USES
 - Healthcare
 - Pharmacies
 - Medical packaging



WWS450H

2D CORDLESS SCANNER



■ SPECIFICATIONS

SFLUII IUATIUNS	
OPTICAL FEATURES	Light source: 625 nm Optical sensor: 752 x 480 pixels Resolution: 1D 3 mil, 2D 5 mil Depth of field: 0.8" to 22.4" (2.1 cm to 56.9 cm) Scan rate: 1D 100 scans/sec, 2D 60 frames/sec
ELECTRICAL Characteristics	Operating voltage: +5 V ±10% Current consumption: Idle 35 mA, Operating 230 mA Working hours: 16 hours (based on 1 scan/5 sec)
MECHANICAL Characteristics	Dimensions: 6.0" H x 2.4" L x 3.7" W (15.3 cm H x 6.1 cm L x 9.3 cm W) Net weight: 6.5 oz (184 g)
ENVIRONMENT Characteristics	Operating temperature: 32°F to 122°F (0°C to 50°C) Storage temperature: -4°F to 140°F (-20°C to 60°C) Relative humidity: 5% to 95% (non-condensing) Mechanical shock: Withstands repeated 4 ft. (1.2 m) drops to concrete Ingress protection: IP30 Electrostatic discharge: ±8 kV contact ±15 kV air
SAFETY Certification	BSMI, CE, C-trick, FCC, IC, NCC, KC, SRMC, TELEC
1D (LINEAR) Symbologies read	Codabar, Code 39, Code 93, Code 128, GS1 DataBar (RSS), Industrial 2 of 5, Interleave 2 of 5, ISBT-128, Italian, Matrix 2 of 5, MSI, UPC-A, UPC-E, EAN-8, EAN-13, GS1-128 (EAN-128)
2D SYMBOLOGIES Read	PDF417, MicroPDF417, Composite, RSS, TLC-39, Datamatrix, QR code, Micro QR code, Aztec, MaxiCode
POSTAL CODES READ	US PostNet, US Planet, UK Postal, Australian Postal, Japan Postal, Dutch Postal (KIX)
PART NUMBERS	WWS450H 2D Healthcare Barcode Scanner with USB Base: 633808121549 WaspProtect 2-Year Extended Warranty for WWS450/WWS450H Barcode Scanner: 633808391294 WaspProtect 1-Year Renewal for WWS450/WWS450H Barcode Scanner: 633808600419