Wasp

BARCODE TECHNOLOGIES

Wasp Time Clocks

| Wasp B3000 Biometric Time Clock
Wasp BC150 Barcode Time Clock
Wasp HD350 HID Time Clock
Wasp RF250 RFID Time Clock

Key Features

- Wi-Fi and PoE on mainboard as standard feature on all Wasp time clock devices
- User friendly UI and menu system design
- Hardware level clock authentication
- System and data backup in-clock or external storage
- Self-service information acquisition
- User level duplicated punch prevention
- Multiple level job code punch
- Enhanced encryption system for data integrity and security
- Enhanced network management

Wasp Time Clocks

PRODUCT	Wasp B3000 Biometric Time Clock	Wasp BC150 Barcode Time Clock	Wasp HD350 HID Time Clock	Wasp RF250 RFID Time Clock
CLOCK TYPE	Biometric	Barcode	HID	RFID
DISPLAY	2.8-inch TFT	2.8-inch TFT	2.8-inch TFT	2.8-inch TFT
DIMENSIONS	6.5 in. W 5.5 in. H 1.8 in. D	6.5 in. W 5.5 in. H 1.8 in. D	6.5 in. W 5.5 in. H 1.8 in. D	6.5 in. W 5.5 in. H 1.8 in. D
APPLICATIONS	Office and retail environments	High-traffic, industrial environments	High-traffic, industrial environments	High-traffic, industrial environments
WEIGHT	.95 lb (15.2 oz)	.95 lb (15.2 oz)	.95 lb (15.2 oz)	.95 lb (15.2 oz)
INSTALLATION	Wall-mount or desktop	Wall-mount or desktop	Wall-mount or desktop	Wall-mount or desktop
POWER SUPPLY	12 V DC, 1.5 A	12 V DC, 1.5 A	12 V DC, 1.5 A	12 V DC, 1.5 A
ENVIRONMENT	Operating Temperature: 32º F to 113º F (0° C to 45° C) Operating Humidity: 5% to 80%	Operating Temperature: 32º F to 113º F (0° C to 45° C) Operating Humidity: 5% to 80%	Operating Temperature: 32º F to 113º F (0° C to 45° C) Operating Humidity: 5% to 80%	Operating Temperature: 32º F to 113º F (0° C to 45° C) Operating Humidity: 5% to 80%
BENEFITS	Employees clock in and out using a fingerprint. Biometric technology delivers secure log-in and eliminates buddy punching.	Employees clock in and out by swiping a barcode badge through the clock.	Employees clock in and out by passing a HID badge in front of the clock. HID badges make it easy for large numbers of employees to clock in quickly.	Employees clock in and out by passing a RFID badge in front of the clock. RFID badges make it easy for large numbers of employees to clock in quickly.
PART NUMBER	Wasp B3000 Biometric Time Clock (633809010330)	Wasp BC150 Barcode Time Clock (633809010347)	Wasp HD350 HID Time Clock (633809010354)	Wasp RF250 RFID Time Clock (633809010361)

Learn more about Wasp tracking solutions at **www.waspbarcode.com**.

Wasp Time Clocks

Wasp B3000 Biometric Time Clock

CLOCK TYPE	Biometric
DISPLAY	2.8-inch TFT
DIMENSIONS	6.5 in. W x 5.5 in. H x 1.8 in. D
APPLICATIONS	Office and retail environments
WEIGHT	.95 lb (15.2 oz)
INSTALLATION	Wall-mount or desktop
POWER SUPPLY	12 V DC, 1.5 A
ENVIRONMENT	Operating Temperature: 32º F to 113º F (0° C to 45° C) Operating Humidity: 5% to 80%
BENEFITS	Employees clock in and out using a fingerprint. Biometric technology delivers secure log-in and eliminates buddy punching.
PART NUMBER	Wasp B3000 Biometric Time Clock (633809010330)

Wasp BC150 Barcode Time Clock

CLOCK TYPE	Barcode
DISPLAY	2.8-inch TFT
DIMENSIONS	6.5 in. W x 5.5 in. H x 1.8 in. D
APPLICATIONS	High-traffic, industrial environments
WEIGHT	.95 lb (15.2 oz)
INSTALLATION	Wall-mount or desktop
POWER SUPPLY	12 V DC, 1.5 A
ENVIRONMENT	Operating Temperature: 32º F to 113º F (0° C to 45° C) Operating Humidity: 5% to 80%
BENEFITS	Employees clock in and out by swiping a barcode badge through the clock.
PART NUMBER	Wasp BC150 Barcode Time Clock (633809010347)

Wasp North America
1400 10th Street
Plano, Texas 75074
1-866-547-9277
www.waspbarcode.com

Wasp Europe
Dunstable Road
Redbourn, St Albans
AL3 7PR, UK
0845-430-1971
www.waspbarcode.co.uk

Wasp International
+1 214-547-4100

Learn more about Wasp tracking solutions at **www.waspbarcode.com.**

Wasp Time Clocks

Wasp HD350 HID Time Clock

CLOCK TYPE	HID
DISPLAY	2.8-inch TFT
DIMENSIONS	6.5 in. W x 5.5 in. H x 1.8 in. D
APPLICATIONS	High-traffic, industrial environments
WEIGHT	.95 lb (15.2 oz)
INSTALLATION	Wall-mount or desktop
POWER SUPPLY	12 V DC, 1.5 A
ENVIRONMENT	Operating Temperature: 32º F to 113º F (0° C to 45° C) Operating Humidity: 5% to 80%
BENEFITS	Employees clock in and out by passing a HID badge in front of the clock. HID badges make it easy for large numbers of employees to clock in quickly.
PART NUMBER	Wasp HD350 HID Time Clock (633809010354)

Wasp RF250 RFID Time Clock

CLOCK TYPE	RFID
DISPLAY	2.8-inch TFT
DIMENSIONS	6.5 in. W x 5.5 in. H x 1.8 in. D
APPLICATIONS	High-traffic, industrial environments
WEIGHT	.95 lb (15.2 oz)
INSTALLATION	Wall-mount or desktop
POWER SUPPLY	12 V DC, 1.5 A
ENVIRONMENT	Operating Temperature: 32º F to 113º F (0° C to 45° C) Operating Humidity: 5% to 80%
BENEFITS	Employees clock in and out by passing a RFID badge in front of the clock. RFID badges make it easy for large numbers of employees to clock in quickly.
PART NUMBER	Wasp RF250 RFID Time Clock (633809010361)

Wasp North America
1400 10th Street
Plano, Texas 75074
1-866-547-9277
www.waspbarcode.com

Wasp Europe
Dunstable Road
Redbourn, St Albans
AL3 7PR, UK
0845-430-1971
www.waspbarcode.co.uk

Wasp International
+1 214-547-4100

Learn more about Wasp tracking solutions at **www.waspbarcode.com.**