

OTU-8000 Optical Test Unit

Rack-mounted fiber test for backbone, metro, and access networks



The OTU-8000 Optical Test Unit lies at the core of the Viavi Solutions® optical network monitoring system (ONMSi). Combining optical time-domain reflectometry (OTDR) and optical-switch technology, a single OTU-8000 unit can test hundreds of fiber links. When a fiber fault occurs, the ONMSi reports the GPS location of the fault within minutes.

The modularity of the OTU-8000 meets all of the requirements for monitoring light or dark fiber-optic networks. Integrated with the latest technology, it can monitor both long-haul and FTTH networks.

With the OTU-8000 installed at the central office, providers can test hundreds of live passive optical networks (PONs), regardless of the split ratio. It can accelerate PON installations when setting up new customers and troubleshooting by enabling technicians to sectionalize the network to determine the cause of a fault.

Organizations concerned with network security issues can use the OTU-8000 to detect and locate fiber tapping after only a few tenths of a decibel are inserted.

Key Benefits

- Reduce MTTR by locating fiber optic faults in minutes instead of hours
- Reduce operational costs by eliminating erroneous dispatches
- Anticipate service disruptions by detecting fiber degradation before it affects service
- Protect your fiber investment by monitoring the long-term performance of installed fibers
- Reduce construction costs by accelerating test processes and empowering test staff
- Protect network integrity by quickly detecting and locating fiber intrusion

Key Features

- Dual IP communication channels
- Switch scalability up to 1080 ports
- Web-browser access
- Advanced fault location
- E-mail and SMS notifications
- Small size (2 RU)
- Dual power feeds
- Solid-state disk
- Low power consumption
- LAN-based firmware downloads
- Expandable by adding an additional test module
- Very fast fault detection

Applications

- Fiber monitoring for service providers, utilities, and dark-fiber providers
- FTTH construction, provisioning, and maintenance tests
- Fiber-tapping detection for critical applications

Specifications (typical at 25°C)

Base Unit	
Height	2 RU
Width	19, 21 (ETSI), or 23"
Depth	260 mm (ETSI) 280 mm (19 or 23")
Operating temperature	-20 to 50°C
Storage temperature	-20 to 60°C
Humidity	95% without condensing
EMI/ESD	CE compliant
Interfaces	2 RJ45 Ethernet 10/100/1000BaseT ports, GSM in option
Media	Solid-state disk
Power Supply consumption	-36 to -60V 35W
Optical Switch	
Number of ports	4, 8, 12, 16, 24, 36, 48 nx36 More than 1000 by cascading 36 ports
Insertion loss (excluding connectors)	0.6 dB
Backreflection	-60 dB
Repeatability	±0.01 dB
Wavelength range	1260-1670 nm
Lifetime	100 million cycles
Housing Up to 48 ports Higher port counts	Included in the OTU-8000 External 1 RU racks

OTDR (general)				
Laser safety	Class 1			
Number of data points	Up to 512,000			
Sampling resolution	From 4 cm			
Distance range	Up to 360 km			
Distance accuracy	±0.75 m ±sampling resolution ±distance x 1.10 ⁻⁵			
OTDR	Module B	Module C	Module D	UHR
Wavelength ¹ (nm)	1550/1625/1650	1550/1625/1650	1550/1625/1650	1650
Wavelength accuracy ¹ (nm)	±20/±20/+15, -5	±20/±10/±1	±20/±10/±1	±5
Dynamic range ² (dB)	40/40/43	45/44/43	50/50/48	43
Pulse width	5 ns to 20 µs	2 ns to 20 µs	2 ns to 20 µs	2 ns to 20 µs
Event dead zone ³ (m)	0.65	0.6	0.5	0.3
Attenuation dead zone ⁴ (m)	2	2	2.5	2
Splitter attenuation dead zone ⁵ (m)	25	25	15	25

- Laser at 25°C and measured at 10 µs. 1650 nm ±1 nm for the E81165C module.
- The one way difference between the extrapolated backscattering level at the start of the fiber and the RMS noise level, after 3 minutes averaging and using the largest pulsewidth.
- Measured at ±1.5 dB down from the peak of an unsaturated reflective event using the shortest pulsewidth.
- Measured at ±0.5 dB from the linear regression using a FC/PC reflectance and using the shortest pulsewidth.
- Measured on a 15 dB attenuation with -70 dB reflectance.

Ordering Information

Description	Part Number
Base Unit	
OTU-8000 base unit - Front Power Input	E98-FP-RF
Base Unit Options	
GSM interface for alarm notification	E98EGSM
Relay for external alarm reporting device	E98RELAYS
23 in rack-mounting kit for OTU-8000	E98KIT23
21 in rack-mounting kit for OTU-8000	E98KIT21
19 in rack-mounting kit for OTU-8000	E98KIT19
AC/DC converter (external unit)	E98ACDC
Optical Switch Plug-In Modules	
Optical switch 1x4 plug-in module (SC/APC)	E98X04
Optical switch 1x8 plug-in module (SC/APC)	E98X08
Optical switch 1x12 plug-in module (SC/APC)	E98X12
Optical switch 1x16 plug-in module (SC/APC)	E98X16
Optical switch 1x24 plug-in module (SC/APC)	E98X24
Optical switch 1x36 plug-in module (LC/APC)	E98X36LCAPC
Optical switch 1x48 plug-in module (LC/APC)	E98X48LCAPC

Optical Switch (external unit)	
External optical switch 1x36 (1 RU, 19", SC/APC)	EOSX8000
Kit to connect OSX-8000 to OTU-8000	E98OTUXOSX
Kit to cascade OSX-8000	E98OSXXOSX
23 in brackets for OSX-8000	E98OSXRK23
21 in brackets for OSX-8000	E98OSXRK21
OTDR Plug-In Modules	
OTDR module D with 1550 nm wavelength	E8115D
OTDR module D with 1625 nm filtered wavelength	E81162D
OTDR module D with 1650 nm filtered wavelength	E81165D
OTDR module D 1550/1625 nm	E8129D
Ultra high resolution filtered 1650 nm OTDR	E8118RUHR65
OTDR module C with 1550 nm wavelength	E8115C
OTDR module C with 1625 nm filtered wavelength	E81162C
OTDR module C with 1650 nm filtered wavelength	E81165C
OTDR module B with 1650 nm filtered wavelength	E81165B
OTDR module B with 1550 nm wavelength	E81115B
OTDR module B 1310/1550/1625 nm	E8136B



Contact Us **+1 844 GO VIAVI**
(+1 844 468 4284)

To reach the Viavi office nearest you,
visit viavisolutions.com/contacts.

© 2016 Viavi Solutions Inc.
Product specifications and descriptions in this
document are subject to change without notice.
otu8000-ds-fop-tm-ae
30149002 912 1216