

FCB1 FRAnalyzer Calibration Box

Technical Data



© OMICRON electronics GmbH 2015. All rights reserved.

This technical data was extracted from the following manual: FCB1.AE.1

All rights including translation reserved. Reproduction of any kind, for example, photocopying, microfilming, optical character recognition and/or storage in electronic data processing systems, requires the explicit consent of OMICRON.

The document content represents the technical status at the time of writing and is subject to change without prior notice.

We have done our best to ensure that the information given in this document is useful, accurate and entirely reliable. However, OMICRON does not assume responsibility for any inaccuracies which may be present.

OMICRON translates this document from the source language English into a number of other languages. Any translation of this document is done for local requirements, and in the event of a dispute between the English and a non-English version, the English version of this document shall govern.

1 Technical data

1.1 Specifications

Table 1-1 *FCB1* Specifications

Characteristic		Rating
0 dB Attenuation	Tolerance as shipped (DC values)	< ± 0.1 dB
	Stability (1 year)	< ± 0.02 dB
	Stability (5 years)	< ± 0.04 dB
	Frequency response (DC up to 10 MHz)	< 0.1 dB
20 dB Attenuation	Tolerance as shipped (DC values)	< ± 0.1 dB
	Stability (1 year)	< ± 0.03 dB
	Stability (5 years)	< ± 0.06 dB
	Frequency response (DC up to 10 MHz)	= Ref
50 dB Attenuation	Tolerance as shipped (DC values)	< ± 0.1 dB
	Stability (1 year)	< ± 0.05 dB
	Stability (5 years)	< ± 0.06 dB
	Frequency response (DC up to 10 MHz)	< ± 0.10 dB
80 dB Attenuation	Tolerance as shipped (DC values)	< ± 0.1 dB
	Stability (1 year)	< ± 0.08 dB
	Stability (5 years)	< ± 0.16 dB
	Frequency response (DC up to 10 MHz)	< 0.1 dB

Table 1-1 *FCB1* Specifications

Characteristic		Rating
Connectors		BNC
Cables	Impedance	$50\ \Omega \pm 2\ \Omega$
	Inner conductor	Cu Ag 1x0.90 mm, \varnothing 0.90 mm
	Insulation material	PE, \varnothing 2.95 mm
	Shield	Cu Ag
	2 nd Shield	Cu Ag
	Jacket	PVC (black), \varnothing 5.50 mm
	Weight	57 kg/km
	Capacitance	97 nF/km
	Velocity of propagation	66%
Input		5 V/0 Hz ... 10 MHz

1.2 Environmental conditions

Table 1-2 Climate

Characteristic		Rating
Temperature	Operating and storage	+5...+35 °C (+41...+95 °F)
Relative humidity	Operating and storage	45...75%; non-condensing Tested according to IEC 60068-2-78

1.3 Mechanical data

Table 1-3 Mechanical Data

Characteristic	Rating
Dimensions (W x H x D)	89.3 x 114.5 x 55.3 mm (3.5 x 4.5 x 2.2 in.)
Weight	<400 g (0.9 lb), without measuring cables

1.4 Safety standards

Table 1-4 Safety Standards

Certified Safety Standards	
Europe	EN 61010-1
International	IEC 61010-1
USA	UL 61010-1

1.5 Cleaning



Warning: Prior to cleaning disconnect the *FCB1*.

To clean the *FCB1*, use a cloth dampened with isopropanol alcohol or water.

