# Keysight J7211A/B/C Attenuation Control Units

# Every Step Counts...

- 1. Measurement relative to a specific attenuation value
- 2. 6 value-added features for application-specific purposes
- 3. Soft-keypad for easy attenuation value settings
- 4. Intensity rotary knob for easy navigation
- 5. Built-in half-rack (2U) with handle; high portability
- 6. RF connector options of SMA, Type-N and 3.5 mm (J7211C)



## Complete connectivitystandard!

Powered by LXI class C compliance





## Key features

- 0.03 dB RF repeatability per section for entire
  5 million cycles
  - Minimize system uncertainty and system setup cost
- Excellent attenuation accuracy and flatness
  Maximize measurement accuracy
- Keysight calibrated data correction value
  Allow accurate and precise measurement
- Application specific attenuation sweep function
  Set your desired attenuation, step size, dwell time and number of cycles to suite your application requirement



#### Product specifications

Model	J7211A	J7211B	J7211C
Frequency range	DC to 6 GHz	DC to 18 GHz	DC to 26.5 GHz
Attenuation range	0 to 121 dB	0 to 121 dB	0 to 101 dB
Attenuation step size	1, 5 and 10 dB	1, 5 and 10 dB	1, 5 and 10 dB
Insertion loss (at 0 dB)	< 2.5 dB	< 5.00 dB	< 5.00 dB
Return loss (VSWR)	< 14 dB (1.50)	< 10 dB (1.90)	< 7 dB (2.61)
RF repeatability	0.03 dB	0.03 dB	0.05 dB
Maximum power input	1 W (+30 dBm)	1 W (+30 dBm)	1 W (+30 dBm)
Switching speed	20 ms	20 ms	20 ms
Operating life	5 million cycles	5 million cycles	5 million cycles

### Ordering information

001	
001	Type-N (f) connector
002	SMA (f) connector
UK6	Commercial calibration certificate with test data
001	Type-N (f) connector
002	SMA (f) connector
UK6	Commercial calibration certificate with test data
UK6	Commercial calibration certificate with test data
	002 UK6 001 002 UK6

<sup>1. 3.5</sup> mm (f) connectors only.



Three-Year Warranty

www.keysight.com/find/ThreeYearWarranty

Keysight's commitment to superior product quality and lower total cost of ownership. The only test and measurement company with three-year warranty standard on all instruments, worldwide.

Keysight Assurance Plans



www.keysight.com/find/AssurancePlans

Up to five years of protection and no budgetary surprises to ensure your instruments are operating to specification so you can rely on accurate measurements.



LXI is the LAN-based successor to GPIB, providing faster, more efficient connectivity. Keysight is a founding member of the LXI consortium. www.lxistandard.org

For more detail information on "Keysight attenuation control unit", please refer to product literature number 5989-8323EN.

To find a distributor in your area, go to: www.keysight.com/find/distributors  $\,$ 

For more information on Keysight attenuators, please visit:

www.keysight.com/find/attenuators

Download or order from www.keysight.com/find/mta

