

P7330 * P6330

Differential Probes

Characteristics

Bandwidth (Probe Only) - P6330 - 3.0 GHz, P7330 - 3.5 GHz (typical).

Rise Time - < 140 ps (< 130 ps typical).

Attenuation - 5X.

Differential Input C - < 0.5 pF (typical).

Differential Input Resistance - 100 kilohm.

Differential Input Range - ± 2 V (20°C to 30°C).

Common Mode Input Range - +5 to -4 V.

Max Voltage (Nondestruct) - ± 25 V (DC plus peak AC).

CMRR - >60 dB @ 1 MHz (typical).

Noise - Approx. 35 nV/root Hz.

Interface -

P6330: TEKPROBE® BNC.

P7330: TekConnect.

Cable Length - 1.3 m.



[Features](#)

[> Specs](#)

[Ordering Information](#)

[Pricing Information](#)

[Print Data Sheet \(145kB\)](#)



[Request a Quote](#)



[Top of Page](#)



Tektronix Measurement products are manufactured in ISO registered facilities.



60W-13756-0Bp1, 06/2000, 04/17/2001

[Features](#)

[> Specs](#)

[Ordering Information](#)

[Pricing Information](#)

[Print Data Sheet \(145kB\)](#)



[Request a Quote](#)