

Features

- **Linear Type**
- **Single O/P**
- **Very Stable & Reliable**
- Fully variable
- Complete Output Protection
- Automatic C/V & C/C
- 2 LED DPMs for display of V & I (4 Digits)
- Live Control of O/P Voltage in O/P Off Position (O/P Pause Function).



Specifications :

Line Regulation	: CV : $\leq 0.01\% + 5 \text{ mV}$	CC : $\leq 0.01\% + 5 \text{ mA}$
Load Regulation	: CV : $\leq 0.1\% + 5 \text{ mV}$	CC : $\leq 0.1\% + 5 \text{ mA}$
Ripple And Noise	: CV : $\leq 10 \text{ mV rms}$	CC : $\leq 10 \text{ mA rms}$
Protection	: Constant Current & Short-Circuit Protection	
Indication Accuracy	: $\leq (1\% + 1 \text{ Digit})$	
Input Voltage	: 220 V AC $\pm 10\%$, 50Hz $\pm 2\text{Hz}$	
Operating Environment	: Temperature ; 0 ~ + 40 °C & R.H. : < 90%	
Dimensions	: 125W x 160H x 260D mm.	
Weight	: ~ 4 Kg.	
Accessories	: Power Cord & Instruction Manual.	