

GROUND RESISTANCE TESTERS

CLAMP-ON



MODELS 6416 & 6417

Provides high safety level with new ground voltage indication feature

SPECIFICATIONS

MODELS	6416 & 6417			
ELECTRICAL				
Ground Resistance	Measurement Range	Resolution	Accuracy (% of Reading)	
	0.010 to 0.099Ω	0.001Ω	±1.5% ±0.01Ω	
	0.10 to 0.99Ω	0.01Ω	±1.5% ±0.02Ω	
	1.0 to 49.9Ω	0.1Ω	±1.5% ±0.1Ω	
	50.0 to 99.5Ω	0.5Ω	±2% ±0.5Ω	
	100 to 199Ω	1Ω	±3% ±1Ω	
	200 to 395Ω	5Ω	±5% ±5Ω	
	400 to 590Ω	10Ω	±10% ±10Ω	
Auto-Ranging 0.01 to 1499Ω	600 to 1150Ω	50Ω	20% approx	
	1200 to 1500Ω	50Ω	25% approx	
	Current Measurement	0.200 to 0.999mA	1μA	±2% ±50μA
		1.000 to 2.990mA	10μA	±2% ±50μA
		3.00 to 9.99mA		
		10.00 to 29.90mA	100μA	±2% ±100μA
30.0 to 99.9mA				
Auto-Ranging 1mA to 40A	100.0 to 299.0mA	1mA	±2% ±1mA	
	0.300 to 0.990A			
	1.000 to 2.990A	10mA	±2% ±10mA	
3.00 to 39.9A				
Selectable Measurement Frequency	50, 60, 128 or 2083Hz			
Current Measurement Frequency	47 to 800Hz			
Inductance Measurement	10 to 100μH; 100 to 500μH			
Current Overload	OL displayed above 39.99Arms			
Communication	Bluetooth connection (Model 6417 only)			
Power Source	4x1.5V LRG (AA) Alkaline batteries or 4 NiMH batteries; Battery life: 12 hours, or 1440 30-second measurements approx.			



*Model 6417 only

FEATURES

- Ground Integrity® Measurement
- Ground voltage indication (warns of possible unsafe conditions)
- Large multi-function bright yellow organic LED display (OLED)
- Selectable test frequency (improves accuracy in inductive environments)
- Clamping diameter of 1.37" (35mm) with large jaw design
- Storage of measurements (Ω and/or A, with time-stamping)
- Model 6416: up to 300 measurements stored
- Model 6417: up to 2000 measurements stored
- View stored measurements on the OLED display or via Bluetooth (Class 2 - communicates up to 30ft) to a PC or the Android™ based mobile application (Model 6417)
- Auto Power OFF function
- Alarm function with adjustable set point and buzzer for quick field checks for volts, amps and ohms
- Rugged Lexan® head and body construction resists breakage
- Alarm settings and stored memory information saved during shutdown
- Includes DataView® software for data retrieval, real-time display, analysis, report generation and system configuration (Model 6417)
- Noise icon and buzzer alert user to presence of dangerous voltage and current levels
- Designed to EN 61010-1, 600V CAT IV safety standards

PRODUCT INCLUDES

MODEL 6416

includes a hard carrying case, calibration loop, four 1.5V AA batteries and user manual.

MODEL 6417

also includes a Bluetooth USB adapter, quick start guide, and a USB drive with DataView® software, ground workbook and user manual.



CATALOG NO.	DESCRIPTION
2141.01	Ground Resistance Tester Model 6416 (Clamp-On, Alarm, Memory)
2141.02	Ground Resistance Tester Model 6417 (Clamp-On, Bluetooth, Alarm, Memory)



Technical Assistance (800) 343-1391

www.aemc.com 75

GROUND RESISTANCE TESTERS

CLAMP-ON

Functional Displays

Disturbance indicator (current) in the loop
 HOLD Function active
 Buzzer is displayed when active
 Measurement date/time display
 Advanced Mode selection
 Indicates when the inductive component is negligible in Advanced Mode
 Main measurement display
 Measurement unit display
 Data Storage Mode
 Memory Recall Mode
 Memory index number display
 Bluetooth connection indicator (6417 only)

Incorrect jaw closing indicator
 Auto Power OFF active
 Battery charge indicator
 4000-count upper measurement display
 Upper display measurement unit
 Main display measurement unit
 Hazardous voltage indicator (not available on model 6418)
 Alarm measurement display unit
 Alarm threshold display
 Alarm active indicator

Note: Display shown larger than real size.

MEASUREMENT RESULTS



Displays the leakage current and loop impedance at the test frequency

MEMORY RECALL MODE



Measurement storage date-time screen

ALARM



Indicates voltage/current alarm threshold along with the direction of impedance

LOOP DETECTION



Detects and displays possible false readings associated with metal loops

GROUND VOLTAGE



Indicates voltage potential at the point of measurement

IMPEDANCE OVER RANGE



Indicates that the impedance is greater than 15000Ω

GROUND RESISTANCE TESTERS

SELECTION CHART

AEMC MODEL NUMBER	AEMC CATALOG NUMBER	RESISTANCE RANGE	POWER SOURCE	2 POINT TEST	3 POINT TEST	4 POINT/ SELECTIVE	SOIL RESISTIVITY TEST	EARTH COUPLING	2 CLAMP	BONDING	DISPLAY	VOLTAGE INDICATION	INDUCTANCE INDICATION	SWEEP FREQUENCY	
6416	2141.01	0.01 to 1500Ω	Battery	Clamp-On Ground Resistance Tester w/Alarm & Memory				-	-	✓**	Digital	Voltage Displayed (noise icon, buzzer)	✓	-	
6417	2141.02	0.01 to 1500Ω	Battery	Clamp-On Ground Resistance Tester w/Alarm, Memory & Bluetooth communication				-	-	✓**	Digital	Voltage Displayed (noise icon, buzzer)	✓	-	
Groundflex® Field Kit Model 6474	2136.03	0.001Ω to 99.99kΩ	Rechargeable Battery	-	✓	✓	✓	✓	-	✓	Digital	Value Displayed	-	✓	
6471 (SR182 probes not included)	2135.48	0.01 to 99.99kΩ	Rechargeable Battery												
6471	2135.49			✓	✓	✓	✓	✓	✓	✓	Digital	Value Displayed	-	-	
6471 Kit 300FT	2135.50														
6472	2135.51	0.01 to 99.99kΩ	Rechargeable Battery												
6472 Kit 300FT	2135.53			✓	✓	✓	✓	✓	✓	✓	Digital	Value Displayed	-	✓	
6472 Kit 500FT	2135.54														
4620	2130.43	0.0 to 1999Ω	Battery	✓	✓	-	✓	-	-	-	Digital	LED/Buzzer	-	-	
4620 Kit 150FT	2135.19						✓*								
4620 Kit 300FT	2135.20	0.0 to 2000Ω	Battery	✓	✓	-	✓	-	-	-	Digital	LED/Buzzer	-	-	
4620 Kit 500FT	2135.21	0.0 to 1999Ω													
4630	2130.44	0.0 to 1999Ω	Rechargeable Battery				✓								
4630 Kit 150FT	2135.22			✓	✓	-	✓*					Digital	LED/Buzzer	-	-
4630 Kit 300FT	2135.23														
4630 Kit 500FT	2135.24							✓							

* Performing soil resistivity tests with this kit requires two additional auxiliary electrodes not supplied in the 150ft kit and one additional test lead.

** Clamp-on Ground Resistance Tester can measure system continuity inclusive of all bonding points.